88M TRACTOR TRAILER AND HEMTT PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://8mmtractortrailerhemtt.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. **What could occur if the trailer handbrake control is used while driving?**

   A. The trailer may skid

   B. The trailer may accelerate

   C. The engine may stall

   D. The brakes may lock up

2. **What is the maximum time to engage the starter during cold weather starting?**

   A. 5 seconds

   B. 10 seconds

   C. 15 seconds

   D. 20 seconds

3. **What must an operator remember before using the LHS hydraulic selector switch?**

   A. Vehicle must be in neutral

   B. Engine must be at idle

   C. Parking brake must be engaged

   D. Transmission must be in drive

4. **If the oil pressure gauge does not indicate any pressure within 10-15 seconds during cold weather starting, what action should you take?**

   A. Continue to start the engine

   B. Check the fuel level

   C. Shut off the engine

   D. Report to maintenance

5. **What temperature triggers the high transmission temperature indicator to illuminate?**

   A. 350 degrees

   B. 400 degrees

   C. 482 degrees

   D. 500 degrees

SAMPLE

6. What is the purpose of the ether canister on the M1120?

A. To improve fuel efficiency

B. To aid in cold weather starting

C. To assist in lubrication

D. To control air pressure

7. What is the purpose of the M915 primary air tank pull lanyard?

A. To release air pressure

B. Manual evacuation of water in the system

C. To test the brakes

D. To activate the emergency system

8. What flag is attached to a load that exceeds 4ft beyond the vehicle bed?

A. White 8x8 flag

B. Red 12x12 flag

C. Yellow 10x10 flag

D. Blue 6x6 flag

9. How many cylinders should be used for driving on level roads with light loads on the M915?

A. 1

B. 2

C. 3

D. 4

10. What is the maximum side slope percentage for adequate traction surface on the M1120?

A. 20%

B. 25%

C. 30%

D. 35%

SAMPLE

Answers

SAMPLE

1. A
2. C
3. B
4. C
5. C
6. B
7. B
8. B
9. B
10. C

SAMPLE

Explanations

SAMPLE

1. What could occur if the trailer handbrake control is used while driving?

A. The trailer may skid

B. The trailer may accelerate

C. The engine may stall

D. The brakes may lock up

Using the trailer handbrake control while driving can lead to the trailer skidding. This is primarily because the handbrake, when engaged, applies braking force to the trailer wheels while the vehicle is in motion. If the handbrake is used improperly or at high speeds, it can create a significant disparity in wheel speed between the trailer and the towing vehicle, resulting in a loss of traction. The skidding could lead to a dangerous situation, possibly causing the driver to lose control of both the trailer and the truck. The other potential outcomes, while they may seem plausible, do not align with the mechanics of how handbrakes work in conjunction with vehicle speed. For instance, the trailer would not accelerate as applying the handbrake would reduce speed, and stalling the engine is not typically a consequence of using the handbrake. Additionally, while the risks of locking up the brakes is a legitimate concern in certain conditions, it's not the primary immediate effect that results from using the handbrake while driving.

2. What is the maximum time to engage the starter during cold weather starting?

A. 5 seconds

B. 10 seconds

C. 15 seconds

D. 20 seconds

The maximum time to engage the starter during cold weather starting is 15 seconds. This timeframe is crucial to prevent overheating of the starter motor and to ensure reliable engine starting in cold conditions. When temperatures drop, the engine oil becomes thicker, which makes the engine harder to crank. Engaging the starter for an extended period could cause damage to the starter itself by overheating, potentially leading to a failure during operation. By limiting the engagement time to 15 seconds, operators can give the starter an adequate chance to turn the engine while mitigating the risk of overheating. If the engine does not start within this time frame, it is recommended to allow a cooldown period (typically around 30 seconds) before attempting to restart. This practice helps maintain the integrity of the starting system and enhances the chances of a successful start under cold weather conditions.

SAMPLE

3. What must an operator remember before using the LHS hydraulic selector switch?

A. Vehicle must be in neutral

B. Engine must be at idle

C. Parking brake must be engaged

D. Transmission must be in drive

The correct answer is that the engine must be at idle before using the LHS hydraulic selector switch. This is crucial for ensuring safe and effective operation of the hydraulic systems on the vehicle. When the engine is at idle, it reduces the risk of any unintended movements or sudden surges in hydraulic pressure that could occur if the engine were running at higher RPMs. This precaution helps prevent accidents and prevents damage to the hydraulic components by ensuring they operate within their intended parameters. By adhering to this guideline, operators can manipulate the hydraulic systems smoothly and effectively, ensuring that they are in complete control of the vehicle's functions. Other factors, such as placing the vehicle in neutral or securing the parking brake, may contribute to safe operating procedures in a broader sense, but the critical condition specifically related to the operation of the hydraulic selector switch is that the engine should be at idle to prevent complications during hydraulic engagements and disengagements.

4. If the oil pressure gauge does not indicate any pressure within 10-15 seconds during cold weather starting, what action should you take?

A. Continue to start the engine

B. Check the fuel level

C. Shut off the engine

D. Report to maintenance

When the oil pressure gauge does not indicate any pressure within 10-15 seconds during cold weather starting, the appropriate action is to shut off the engine. This is critical because a lack of oil pressure can indicate that the oil may not be circulating properly within the engine. Continuing to run the engine under such conditions can lead to significant damage, as sufficient oil pressure is essential for lubricating engine components and preventing wear or engine seizure. In cold weather, oil can become thicker, and if the pump is unable to circulate the oil, it poses a risk to engine integrity. Shutting off the engine promptly allows for further investigation, such as checking the oil level and ensuring the proper grade of oil is being used for the temperature conditions. This proactive measure helps to avoid potentially costly repairs and maintain the vehicle's operational reliability. Taking no action or attempting to continue running the engine could lead to severe damage. Thus, it is essential to address the lack of oil pressure immediately by shutting off the engine.

5. What temperature triggers the high transmission temperature indicator to illuminate?

A. 350 degrees

B. 400 degrees

C. 482 degrees

D. 500 degrees

The high transmission temperature indicator typically illuminates at 482 degrees Fahrenheit. At this temperature, the transmission fluid may begin to break down, leading to potential overheating and damage to the transmission system. Monitoring this indicator is crucial for ensuring the vehicle operates within safe temperature ranges, thereby preventing costly repairs and maintaining optimal performance. Understanding the significance of this temperature is essential for drivers of heavy vehicles, such as those operating tractor trailers and HEMTTs, as it helps them respond appropriately to avoid transmission failure.

SAMPLE

6. What is the purpose of the ether canister on the M1120?

A. To improve fuel efficiency

B. To aid in cold weather starting

C. To assist in lubrication

D. To control air pressure

The ether canister on the M1120 is designed specifically to aid in cold weather starting. In lower temperatures, diesel engines can experience difficulties in starting due to fuel gelling or inadequate vaporization. The ether canister provides a starting fluid that enhances the combustion process in cold conditions. When the ether is introduced into the engine intake, it lowers the ignition temperature and helps the engine fire up more easily, ensuring reliable operation in cold environments. This is particularly important for military vehicles, which may be required to operate in a variety of challenging weather conditions. Other options do not accurately represent the function of the ether canister. For instance, while fuel efficiency is important for any vehicle, the ether canister's role does not directly relate to improving fuel efficiency. Similarly, while lubrication is critical for engine operation, that is managed through other means and not the ether canister. Controlling air pressure is also a function of different systems within the vehicle, not related to the ether canister's purpose.

7. What is the purpose of the M915 primary air tank pull lanyard?

A. To release air pressure

B. Manual evacuation of water in the system

C. To test the brakes

D. To activate the emergency system

The primary air tank pull lanyard on the M915 is primarily designed for manual evacuation of water from the system. This is important because moisture can accumulate in the air tanks due to condensation, which can lead to issues with air system performance and potentially affect the braking system. By using the pull lanyard, operators can effectively release any collected water, helping to maintain optimum performance and safety. Managing water accumulation in the air system is critical, especially in environments with fluctuating temperatures. This manual evacuation process ensures that the system remains clear of obstructions that could hamper operation and compromise safety during operation.

8. What flag is attached to a load that exceeds 4ft beyond the vehicle bed?

A. White 8x8 flag

B. Red 12x12 flag

C. Yellow 10x10 flag

D. Blue 6x6 flag

A load that extends more than 4 feet beyond the vehicle bed is typically required to be marked with a specific flag for safety and visibility. The correct choice of a red 12x12 flag is standard because it is easily noticeable and typically used to signal that there is an overhanging load that poses a potential hazard. This bright color and size help ensure that other drivers can see the extended load from a distance, reducing the likelihood of accidents. The size of 12x12 inches provides enough surface area to be visible, even in varying light conditions. Using a proper flag is crucial, especially for larger vehicles like tractor trailers, where loads can obscure the view of the vehicle itself. By ensuring that the flag is both compliant with regulations and highly visible, drivers can alert others to the potential dangers of protruding loads.

SAMPLE

9. How many cylinders should be used for driving on level roads with light loads on the M915?

A. 1

B. 2

C. 3

D. 4

The M915 is designed to optimize fuel efficiency and performance under various load and terrain conditions. When driving on level roads with light loads, it is most efficient to engage two cylinders. Using two cylinders allows the engine to operate efficiently without wasting fuel while still providing enough power for light loads. Engaging more cylinders than necessary could lead to reduced fuel economy, as the engine would be consuming more fuel than required for the lighter conditions. This balance of power and efficiency is crucial for modern heavy trucks like the M915, which are often equipped with advanced engine management systems allowing for such selective cylinder operation. This practice is part of managing the vehicle's performance effectively in different driving environments.

10. What is the maximum side slope percentage for adequate traction surface on the M1120?

A. 20%

B. 25%

C. 30%

D. 35%

The maximum side slope percentage for adequate traction surface on the M1120 is established at 30%. This specification is crucial for ensuring that the vehicle maintains stability and traction when operating on inclines or uneven terrain. If the side slope exceeds this percentage, the risk of tipping or losing control increases significantly. Understanding this limit is vital for operators, as it guides safe maneuvering of the M1120 in various environments, particularly in military applications where precise terrain navigation is essential. Operating beyond the recommended side slope can lead to dangerous situations and compromise overall operational effectiveness. This guideline is rooted in the vehicle's design and testing, which ensures that it can safely handle specific gradients while carrying maximum loads, thus enhancing both safety and performance on side slopes.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://8mmtractortrailerhemtt.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE