
ACADEMIC BLOCK 2 – SYSTEMS 1 (SY190), UPT 2.5 PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://acad2sy90upt25.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. **Is normal flap operation and position indication available when the battery bus has failed?**

   A. Yes

   B. No

   C. Only in emergency situations

   D. Contingent on auxiliary power availability

2. **What is the operating range for propeller operation while on the ground?**

   A. 45-70% Np

   B. 62-80% Np

   C. 80-95% Np

   D. 90-100% Np

3. **True or False: The T-6 can be defueled from the over the wing gravity refueling ports.**

   A. True

   B. False

   C. Only under certain conditions

   D. It depends on the tank level

4. **What does "interlocked" refer to in electrical switches?**

   A. Simultaneous operation of switches

   B. Sequential operation of switches

   C. When one goes on, the other goes off

   D. Automatic reset of switches

5. **What occurs when the gear handle is not DOWN and weight is on wheels?**

   A. The gear handle light illuminates red

   B. An aural landing gear warning tone sounds

   C. The fire warning lights activate

   D. The aircraft loses power

SAMPLE

6. Where is rudder balancing achieved?

A. Rudder Horn

B. Tail section

C. Main wing

D. Control panel

7. What is the maximum permissible differential pressure at an aircraft pressure altitude of 18,069 ft?

A. 3.0 +/- 0.1

B. 3.6 +/- 0.2

C. 4.0 +/- 0.2

D. 4.6 +/- 0.2

8. How does the EDM manage fuel auto balancing?

A. By manually adjusting fuel valves

B. It reads gauges and automatically chooses a tank to take fuel from

C. By using an external control unit

D. It relies on pilot input to manage fuel

9. An "EHYD PX LO" light signals what condition?

A. Low reservoir fluid level

B. Emergency Accumulator Pressure below a specific threshold

C. Hydraulic system overheating

D. Engine power loss

10. Which unit is responsible for regulating and monitoring the starter/generator?

A. Battery Control Unit

B. Generator Control Unit (GCU)

C. Power Management Unit (PMU)

D. Starter Relay Unit

SAMPLE

Answers

SAMPLE

1. B
2. B
3. B
4. C
5. B
6. A
7. B
8. B
9. B
10. B

SAMPLE

Explanations

SAMPLE

1. Is normal flap operation and position indication available when the battery bus has failed?

A. Yes

B. No

C. Only in emergency situations

D. Contingent on auxiliary power availability

In the event of a battery bus failure, normal flap operation and position indication are not available. The battery bus powers various systems on the aircraft, including the flap controls and indicators. Without the battery bus functioning, these systems cannot receive the necessary power to operate as intended, which means that neither flap operation nor accurate position indication can be assured. While some aircraft may have backup systems or alternative means of operation, a complete failure of the battery bus typically implies that the standard electronic systems are offline. This scenario emphasizes the importance of electrical system reliability and the potential consequences of power failures on flight operations. Understanding the functioning of the flap system within the context of an electrical failure helps highlight the significance of having operational backup systems and protocols in place.

2. What is the operating range for propeller operation while on the ground?

A. 45-70% Np

B. 62-80% Np

C. 80-95% Np

D. 90-100% Np

The correct choice indicates that the operating range for propeller operation while on the ground is between 62-80% Np. This range is significant because it represents the optimal settings for engine performance and efficiency during ground operations, such as taxiing or run-up procedures, without risking damage to the propeller or engine. Operating within this range ensures that the propeller generates sufficient thrust while also maintaining appropriate engine speeds for safe operation. This range balances performance needs with safety considerations, as it helps avoid excessive wear or overheating that could occur at either too low or too high settings. In contrast, the other ranges provided do not align with the operational needs during ground maneuvers. Higher ranges could lead to unnecessary strain on the propeller and engine, while ranges that are too low may not provide enough thrust for effective ground control. Thus, the selection of 62-80% Np reflects a well-considered standard for maintaining both efficiency and safety during ground operations.

3. True or False: The T-6 can be defueled from the over the wing gravity refueling ports.

A. True

B. False

C. Only under certain conditions

D. It depends on the tank level

The correct choice is that the T-6 cannot be defueled from the over the wing gravity refueling ports. This is based on the design and operational protocols associated with the aircraft's fuel system. Typically, defueling procedures for aircraft are structured to utilize the designated defueling system, which is more efficient and controlled than using the gravity refueling ports. The over the wing ports are primarily intended for refueling purposes, not for defueling. This separation of functions ensures that the processes involved in both fueling and defueling can be managed effectively without risking potential issues such as spilling or contamination. Therefore, the inability to use the over the wing gravity refueling ports for defueling aligns with standard aircraft operational protocols and safety measures.

SAMPLE

4. What does "interlocked" refer to in electrical switches?

A. Simultaneous operation of switches

B. Sequential operation of switches

C. When one goes on, the other goes off

D. Automatic reset of switches

The term "interlocked" in the context of electrical switches refers to a configuration where the operation of one switch directly influences the state of another switch. Specifically, when one switch is activated, it prevents the other from being turned on, and vice versa. This mechanism is crucial for ensuring safety and preventing conflicting operations in electrical systems. The interlock feature is particularly important in systems where the simultaneous operation of switches could lead to dangerous conditions, such as in control panels or machinery that has multiple operational modes. By utilizing this feature, the design guarantees that certain functions can only occur under specific conditions, thus protecting machinery and operators. In contrast, simultaneous operation of switches would allow them to function together without restrictions, while sequential operation governs the order in which switches are activated, which does not inherently involve the restriction aspect of interlocking. Automatic reset of switches pertains to the functionality of switching back to the default state after operation, which is unrelated to the interlocking concept.

5. What occurs when the gear handle is not DOWN and weight is on wheels?

A. The gear handle light illuminates red

B. An aural landing gear warning tone sounds

C. The fire warning lights activate

D. The aircraft loses power

When the gear handle is not in the DOWN position and there is weight on the wheels, it signals that the landing gear is not properly deployed while the aircraft is on the ground. This condition triggers an aural landing gear warning tone. The purpose of the warning tone is to alert the flight crew of a potentially unsafe condition, reminding them to ensure that the landing gear is correctly configured before taking off or during critical phases of operation. The aural warning serves to enhance safety by providing immediate feedback to the pilots, allowing them to address the situation before it results in a mishap. In this scenario, the other potential outcomes do not align with the specified condition of the gear handle and weight on the wheels. For instance, the gear handle light illuminating red typically indicates a problem with the gear system rather than the handle's position with weight on the wheels. The activation of fire warning lights relates to the presence of fire or overheating, which is unrelated to the status of the landing gear. Finally, an aircraft losing power would refer to an entirely different issue not directly connected to the gear handle's position and weight on the wheels. This further emphasizes why the landing gear warning tone is the appropriate response in this situation.

SAMPLE

6. Where is rudder balancing achieved?

A. Rudder Horn

B. Tail section

C. Main wing

D. Control panel

Rudder balancing is primarily achieved at the rudder horn. The rudder horn is the component that provides the pivot point for the rudder and is critical in determining how effectively the rudder can operate. When a rudder is balanced properly, it can maintain control and respond quickly to pilot inputs without requiring excessive force. This balancing is necessary because it allows the rudder to return to its neutral position when not under active control, which enhances the aircraft's stability and responsiveness. By positioning the balancing weights or adjusting the design at the rudder horn, control can be optimized for aerodynamic efficiency and handling characteristics. Other parts of the aircraft, such as the tail section, do contribute to overall control surfaces and stability but are not specifically where the fine-tuning and balancing of the rudder takes place. The main wing and control panel also are essential for flight operations but do not have a direct function in the balancing of the rudder itself.

7. What is the maximum permissible differential pressure at an aircraft pressure altitude of 18,069 ft?

A. 3.0 +/- 0.1

B. 3.6 +/- 0.2

C. 4.0 +/- 0.2

D. 4.6 +/- 0.2

To determine the maximum permissible differential pressure at an aircraft pressure altitude of 18,069 feet, one must consider the guidelines set by aviation regulatory bodies and the engineering specifics related to aircraft cabin pressure systems. At this altitude, the allowable differential pressure is affected by factors such as structural integrity, safety, and cabin pressurization laws. The correct answer reflects the standard maximum differential pressure specified for that altitude, which is typically set to ensure that the aircraft's fuselage can safely withstand the stresses of pressurization, while also providing a safe environment for the occupants. It is established through certification data and operational safety practices. In this case, 3.6 +/- 0.2 is aligned with accepted safety measures for commercial aircraft at that altitude. The other options, despite being valid numbers, do not fall within the established parameters for maximum differential pressure at 18,069 feet. Each figure represents a different potential performance value, but 3.6 +/- 0.2 is particularly chosen based on the industry standards that apply to the altitude in question.

SAMPLE

8. How does the EDM manage fuel auto balancing?

A. By manually adjusting fuel valves

B. It reads gauges and automatically chooses a tank to take fuel from

C. By using an external control unit

D. It relies on pilot input to manage fuel

The management of fuel auto balancing in the EDM (Electronic Display Module) is achieved by the system's ability to read fuel gauges and automatically select the appropriate tank from which to draw fuel. This process ensures that fuel levels between multiple tanks are balanced, which is crucial for maintaining optimal aircraft performance and stability. When the EDM monitors the fuel levels, it assesses the data from the various tanks. If it detects discrepancies in fuel levels, it can automatically adjust the fuel supply by choosing the tank that will maintain an even distribution of fuel. This automated decision-making reduces pilot workload and enhances the efficiency of fuel management during flight. The other options suggest methods that either require manual intervention or depend solely on pilot input, which would not provide the same level of efficiency or automation as the EDM's system. By automating this function, the EDM helps to ensure that fuel distribution is effectively managed without additional input needed from the pilot, contributing to safer and more efficient flying conditions.

9. An "EHYD PX LO" light signals what condition?

A. Low reservoir fluid level

B. Emergency Accumulator Pressure below a specific threshold

C. Hydraulic system overheating

D. Engine power loss

The "EHYD PX LO" light indicates that the emergency accumulator pressure is below a specific threshold. This warning is crucial because the emergency accumulator is a vital component in hydraulic systems, especially in aircraft, as it provides hydraulic pressure when the primary system fails or if there is a loss of pressure. Maintaining adequate pressure in the emergency accumulator is essential to ensure that critical systems remain operational in case of an emergency. When this light is illuminated, it alerts the crew to check the hydraulic system's pressure and take necessary actions to manage the situation effectively, safeguarding the aircraft's operational integrity. Understanding that this warning pertains to accumulator pressure is important for immediate troubleshooting and maintaining safety protocols, distinguishing it from alerts related to fluid levels, overheating, or engine performance.

SAMPLE

10. Which unit is responsible for regulating and monitoring the starter/generator?

A. Battery Control Unit

B. Generator Control Unit (GCU)

C. Power Management Unit (PMU)

D. Starter Relay Unit

The Generator Control Unit (GCU) plays a critical role in regulating and monitoring the starter/generator system in aircraft. Its primary function is to ensure that the generator operates within specified parameters, managing voltage output, frequency, and other operational characteristics essential for the electrical system's stability and reliability. The GCU monitors the performance of the starter/generator, handling functions such as load sharing and protecting against issues like overvoltage or overcurrent conditions. This involves controlling the excitation of the generator, which is vital for maintaining the correct electrical output during various phases of engine operation, including starting and generating power once the engine is running. In contrast, while other units like the Battery Control Unit and Power Management Unit are important for their specific roles in the overall electrical system, they do not directly manage the starter/generator's performance. The Starter Relay Unit primarily acts as a switch to engage or disengage the starter motor and is not responsible for the regulation and monitoring of the generator functions. Thus, the GCU's specialized function makes it the correct answer for this question.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://acad2sy90upt25.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE