ACI CONCRETE FIELD TESTING TECHNICIAN - GRADE I PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://aci-i.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. **When rodding each upper layer of concrete in a cylinder, how far should the tamping rod penetrate into the underlying layer?**

   A. 1/2 in. [13 mm]

   B. 1 in. [25 mm]

   C. 1 1/2 in. [38 mm]

   D. 2 in. [50 mm]

2. **How often should the temperature measuring device be calibrated?**

   A. Every six months

   B. Annually

   C. Every two years

   D. Only when damaged

3. **The container for obtaining the concrete sample can be any of the following except?**

   A. Plastic bucket

   B. Metal pan

   C. Wheelbarrow

   D. Flat, clean nonabsorbent mixing board

4. **What is the maximum transportation time allowed for test specimens?**

   A. 2 hours

   B. 6 hours

   C. 4 hours

   D. 8 hours

5. **What is the minimum frequency of an internal vibrator used in concrete testing procedures?**

   A. 6000 vibrations per minute [100 Hz]

   B. 7500 vibrations per minute [125 Hz]

   C. 9000 vibrations per minute [150 Hz]

   D. 12000 vibrations per minute [200 Hz]

SAMPLE

6. Where is the measurement for slump taken from?

A. The bottom of the mold

B. The top of the mold to the original center of the specimen

C. The base of the mold to the top of the slumped concrete

D. The overflow area around the mold

7. The temperature and moisture environment for field cured cylinders must be consistent with what?

A. The surrounding environment

B. The structural work

C. The laboratory conditions

D. The curing room specifications

8. Which test provides a quick estimate of workability in freshly mixed concrete?

A. Vebe test

B. Slump test

C. Compression test

D. Tensile test

9. What is the main purpose of the air meter test method in concrete field testing?

A. To determine concrete compressive strength

B. To measure the air content in fresh concrete

C. To assess the workability of concrete

D. To evaluate the temperature of the concrete mix

10. What is the recommended action to protect a concrete sample from contamination?

A. Rapid evaporation

B. Use of a protective cover

C. Immediate transportation to a lab

D. Avoid mixing with other samples

SAMPLE

Answers

SAMPLE

1. B
2. B
3. C
4. C
5. C
6. B
7. B
8. B
9. B
10. B

SAMPLE

Explanations

SAMPLE

1. When rodding each upper layer of concrete in a cylinder, how far should the tamping rod penetrate into the underlying layer?

A. 1/2 in. [13 mm]

B. 1 in. [25 mm]

C. 1 1/2 in. [38 mm]

D. 2 in. [50 mm]

The correct approach for rodding the upper layer of concrete in a cylinder involves the tamping rod penetrating into the underlying layer by a depth of 1 inch (25 mm). This penetration ensures proper bonding and integration of the layers, which is essential for achieving a uniform and consistent sample. The reason for this specific depth is to avoid creating weak interfaces between layers, which could compromise the integrity of the sample and lead to inaccurate strength measurements during testing. By allowing the rod to penetrate by this specified depth, it helps to consolidate the upper layer effectively, ensuring that there are no significant air pockets or voids, and that the concrete is properly compacted throughout. This standard practice aligns with the guidelines set by organizations such as the American Concrete Institute (ACI), emphasizing the importance of maintaining consistency in testing procedures to obtain reliable and comparable results.

2. How often should the temperature measuring device be calibrated?

A. Every six months

B. Annually

C. Every two years

D. Only when damaged

The recommended frequency for calibrating the temperature measuring device is annually. This regular calibration ensures that the device remains accurate and reliable in measuring the temperature of concrete. Accurate temperature measurement is crucial because it can significantly affect the properties of the concrete mix, including workability, strength development, and curing efficiency. By calibrating annually, users can maintain confidence in the measurements taken during concrete testing, which is vital for quality control and compliance with industry standards. While other intervals may seem reasonable, they could allow the device to drift out of calibration, leading to potential errors in temperature readings. This can impact the overall integrity of the concrete work, making annual calibration the best practice in maintaining measurement accuracy.

3. The container for obtaining the concrete sample can be any of the following except?

A. Plastic bucket

B. Metal pan

C. Wheelbarrow

D. Flat, clean nonabsorbent mixing board

When obtaining a concrete sample, the selected container for collection should be clean and nonabsorbent to prevent contamination and ensure the integrity of the sample. A wheelbarrow, while practical for transporting concrete, is not suitable for sampling because it may not provide a stable or sufficiently clean environment for capturing an accurate representation of the concrete's properties. On the other hand, a plastic bucket, metal pan, and a flat, clean nonabsorbent mixing board are all appropriate choices since they can be easily cleaned, are stable for holding the concrete, and do not introduce substances that could alter the composition of the sample. Each of these options allows for a clear and uncontaminated collection process, essential for ensuring accurate testing results. Using a wheelbarrow as a collection tool can lead to inconsistent sampling and diminish the reliability of test outcomes.

SAMPLE

4. What is the maximum transportation time allowed for test specimens?

A. 2 hours

B. 6 hours

C. 4 hours

D. 8 hours

The correct answer regarding the maximum transportation time allowed for test specimens is four hours. This duration is critical to ensure the integrity and reliability of the samples being tested. Transportation time impacts the temperature, hydration, and overall condition of concrete specimens. If specimens are transported for too long, they can begin to set or cure, leading to inaccurate test results. This four-hour timeframe allows sufficient time for concrete samples to be delivered to the testing location while minimizing any alterations in their properties that could arise from extended transportation. Maintaining this limit ensures compliance with industry standards and reinforces the validity of the testing process, which is pivotal for assessing the quality and performance of concrete. Adhering to this guideline plays an essential role in producing reliable data for engineers and project managers.

5. What is the minimum frequency of an internal vibrator used in concrete testing procedures?

A. 6000 vibrations per minute [100 Hz]

B. 7500 vibrations per minute [125 Hz]

C. 9000 vibrations per minute [150 Hz]

D. 12000 vibrations per minute [200 Hz]

The correct response regarding the minimum frequency of an internal vibrator used in concrete testing procedures aligns with industry standards that emphasize the efficiency of consolidation when working with freshly mixed concrete. An internal vibrator with a frequency of 9000 vibrations per minute, which translates to 150 Hz, is often recommended for effectively removing air pockets and ensuring uniform distribution of materials within the concrete mix. This frequency helps achieve optimal results in achieving the desired workability without compromising the concrete's integrity. Utilizing a vibrator at this level ensures that the concrete is cohesive and free from segregation. Frequencies below this threshold may not be effective enough for proper consolidation, which could lead to voids or weak spots in the poured concrete. Higher frequencies, while they may seem effective, could introduce excessive vibration that may lead to segregation or other issues in the concrete mix. Thus, a frequency of 9000 vibrations per minute is recognized as the correct standard for effective internal vibration in concrete testing.

6. Where is the measurement for slump taken from?

A. The bottom of the mold

B. The top of the mold to the original center of the specimen

C. The base of the mold to the top of the slumped concrete

D. The overflow area around the mold

The measurement for slump is specifically taken from the top of the mold to the original center of the specimen. This method is crucial because it provides an accurate representation of the deformation of the concrete after the mold has been removed. The slump test is intended to measure the consistency and workability of fresh concrete, and the distance measured reflects how much the concrete has settled under its own weight. Using the original center of the specimen as a reference point ensures that variations in concrete placement or density do not skew the results, thus allowing for reliable comparisons across different tests. Each slump measurement is then standardized to this starting point to maintain consistency and accuracy in evaluating the concrete's properties.

SAMPLE

7. The temperature and moisture environment for field cured cylinders must be consistent with what?

A. The surrounding environment

B. The structural work

C. The laboratory conditions

D. The curing room specifications

The correct answer emphasizes the importance of ensuring that the temperature and moisture environment for field-cured cylinders is consistent with the structural work being performed. This is critical because the conditions under which concrete is cured can significantly affect its properties, such as strength and durability. When field curing cylinders, it is essential that the conditions mimic those of the actual concrete in place to provide a meaningful assessment of the concrete's performance. By aligning the curing environment of the test specimens with that of the structure, it ensures that any tests conducted on the cylinders accurately reflect the concrete that will be in service. Field-cured specimens subjected to different curing conditions may yield results that do not correlate with the actual in-situ concrete. Thus, maintaining consistency with the structural work allows for reliable comparison and evaluation of the concrete's expected behavior and performance over time.

8. Which test provides a quick estimate of workability in freshly mixed concrete?

A. Vebe test

B. Slump test

C. Compression test

D. Tensile test

The slump test is widely recognized as a quick and effective method to estimate the workability of freshly mixed concrete. It involves measuring the vertical settlement of a conical mold filled with concrete. The degree of slump indicates how easily the concrete can be mixed, placed, and finished, which are crucial factors for construction applications. A higher slump value generally signifies a more workable mix that can flow easily into place, while a lower slump indicates a stiffer mix that may be more difficult to work with. This test is particularly favored in the field due to its simplicity and quick results, allowing technicians to assess the consistency and suitability of the concrete for a specific job without the need for extensive equipment or lengthy procedures. While other tests, like the Vebe test, can also assess workability, they are not as commonly used for a quick estimate in everyday field testing. The compression and tensile tests are primarily designed to evaluate the strength of concrete rather than its workability, focusing on different properties altogether. Thus, the slump test stands out as the benchtop technique for determining the workability of freshly mixed concrete efficiently.

SAMPLE

9. What is the main purpose of the air meter test method in concrete field testing?

A. To determine concrete compressive strength

B. To measure the air content in fresh concrete

C. To assess the workability of concrete

D. To evaluate the temperature of the concrete mix

The primary objective of the air meter test method is to measure the air content in fresh concrete. This test is crucial because the amount of air entrained in the concrete mix plays a significant role in enhancing the durability and workability of the concrete. Air-entrained concrete can resist freeze-thaw cycles, which is particularly important in cold climates. By determining the air content, testers can ensure that the concrete has the desired properties for its intended use, reducing the risk of cracking and failure. While the other options pertain to important aspects of concrete testing, they do not capture the main purpose of the air meter test. For instance, assessing compressive strength, workability, or temperature are conducted through different testing methods, such as cylinder breaking, slump tests, or thermometers, respectively. Therefore, measuring air content is the specific focus of this test method.

10. What is the recommended action to protect a concrete sample from contamination?

A. Rapid evaporation

B. Use of a protective cover

C. Immediate transportation to a lab

D. Avoid mixing with other samples

To protect a concrete sample from contamination, using a protective cover is the most effective action. This approach helps to prevent exposure to environmental factors such as dust, debris, and moisture that can alter the sample's characteristics and lead to inaccurate test results. A cover can be placed over the sample immediately after collection to shield it from any potential contaminants. While other actions, like rapid evaporation or immediate transportation to a lab, might address certain aspects of sample integrity, they do not directly prevent contamination during storage and transportation. Avoiding mixing with other samples is also important but does not provide a protective barrier against environmental contaminants specifically. Therefore, utilizing a protective cover is the best practice for maintaining the purity and reliability of a concrete sample prior to testing.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://aci-i.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE