ALABAMA CONTRACTORS LICENSE PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://alabamacontractors.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. **How often should PEX tubing support hangers be installed based on their maximum spacing?**

   A. Every 1 foot

   B. Every 2 feet

   C. Every 3 feet

   D. Every 4 feet

2. **What is the minimum screw size for fastening gypsum board to a cold-formed structural steel wall?**

   A. No. 5

   B. No. 6

   C. No. 7

   D. No. 8

3. **What type of properties do Group R facilities typically encompass?**

   A. Commercial properties

   B. Industrial facilities

   C. Residential properties

   D. Public buildings

4. **Nebraska is located in the moist area of the US. Is this statement true or false?**

   A. True

   B. False

   C. Depends on the definition of moist

   D. Not enough information

5. **In which situation are vapor retarders not required according to moisture damage standards in zones 5, 6, 7, 8, and Marine 4?**

   A. Where temperature remains constant

   B. Where moisture or freezing will not damage materials

   C. Where insulation is used

   D. Where construction is raised off the ground

SAMPLE

6. What is the minimum drip edge overlap at the eaves and gables of shingle roofs?

A. 1 inch

B. 2 inches

C. 3 inches

D. 4 inches

7. Lintels must be provided for all openings greater than how many feet in width?

A. 2

B. 3

C. 4

D. 6

8. Must switching devices be located less than 5 feet from the inside walls of a pool?

A. TRUE

B. FALSE

9. An accessory structure cannot exceed how many square feet?

A. 1,000

B. 2,000

C. 3,000

D. 4,000

10. What type of wire should be used for supporting metal ducts according to standard practices?

A. 10-gage galvanized wire

B. 12-gage galvanized wire

C. 16-gage galvanized wire

D. 18-gage galvanized wire

SAMPLE

Answers

SAMPLE

1. B
2. B
3. C
4. B
5. B
6. C
7. B
8. A
9. C
10. C

SAMPLE

Explanations

SAMPLE

1. How often should PEX tubing support hangers be installed based on their maximum spacing?

A. Every 1 foot

B. Every 2 feet

C. Every 3 feet

D. Every 4 feet

The correct answer is based on the manufacturer's guidelines and plumbing codes, which specify that PEX tubing support hangers should be installed at a maximum spacing of every 2 feet. This spacing ensures that the PEX tubing remains properly secured and does not sag, which could result in kinking or other damage to the tubing. Adequate support is crucial to maintain the integrity and functionality of the plumbing system. Choosing a spacing that is too far apart, such as every 3 or 4 feet, would increase the risk of unsupported lengths that could lead to problems over time, including potential leaks or reduced flow due to bending. While the suggestion of every 1 foot may seem cautious, it is not practical as it could lead to unnecessary labor and material costs without providing significant benefits. Therefore, the standard and most accepted practice is to use support hangers every 2 feet for PEX tubing installation.

2. What is the minimum screw size for fastening gypsum board to a cold-formed structural steel wall?

A. No. 5

B. No. 6

C. No. 7

D. No. 8

Fastening gypsum board to a cold-formed structural steel wall typically requires a screw size that can adequately secure the board while ensuring it can support the material's weight and resist shear forces. A No. 6 screw is recognized as the minimum size for this purpose. No. 6 screws provide sufficient holding power and are specifically designed to penetrate the steel and anchor securely, thereby creating a stable attachment for the gypsum board. Using smaller sizes may not offer the necessary strength to withstand the potential stresses in the wall system. Larger sizes, while suitable, may unnecessarily complicate the installation process or cause damage to the gypsum board. Thus, the No. 6 screw stands out as the optimal choice for this application in adhering gypsum board to cold-formed steel.

3. What type of properties do Group R facilities typically encompass?

A. Commercial properties

B. Industrial facilities

C. Residential properties

D. Public buildings

Group R facilities primarily consist of residential properties, which are designed for living accommodations. This classification includes various types of housing such as single-family homes, multi-family units, and dormitories. The defining characteristic of Group R facilities is their purpose as living spaces where individuals reside, either temporarily or permanently. Understanding this classification is crucial for contractors, as it influences design, building codes, and safety regulations tailored to residential environments. For example, these facilities must comply with specific fire safety standards and accessibility requirements that differ from those applicable to commercial or industrial properties. This knowledge is essential for anyone involved in construction, remodeling, or inspection of residential buildings to ensure compliance with relevant laws and regulations.

SAMPLE

4. Nebraska is located in the moist area of the US. Is this statement true or false?

A. True

B. False

C. Depends on the definition of moist

D. Not enough information

The statement is false because Nebraska is primarily located in a region characterized by a semi-arid climate, particularly in its western parts. While there are areas within Nebraska that receive adequate rainfall, the overall climate does not align with what is typically defined as "moist." Instead, much of Nebraska experiences significant temperature variations and periods of drought. The definition of "moist" generally refers to areas with consistent and substantial rainfall throughout the year, such as certain regions on the coasts or in the southeastern United States. In contrast, Nebraska's climate, especially in the western areas, tends to be drier, making it less fitting for the term "moist." Thus, stating that Nebraska is located in a moist area of the U.S. is inaccurate.

5. In which situation are vapor retarders not required according to moisture damage standards in zones 5, 6, 7, 8, and Marine 4?

A. Where temperature remains constant

B. Where moisture or freezing will not damage materials

C. Where insulation is used

D. Where construction is raised off the ground

The correct answer is that vapor retarders are not required in situations where moisture or freezing will not damage materials. This aligns with the moisture damage standards, which recognize that if there is no risk of moisture infiltration leading to potential damage, the need for additional barriers such as vapor retarders is lessened or eliminated. In climates categorized under zones 5, 6, 7, 8, and Marine 4, the potential for moisture accumulation and the resulting damage varies significantly based on environmental conditions. When materials are not susceptible to moisture-related damage, the protective function of vapor retarders becomes unnecessary. This consideration is vital for effective building practices, as it allows for more tailored construction methods based on site-specific conditions. The other situations listed do not generally exempt the requirement for vapor retarders. For instance, if temperature remains constant, moisture can still condense; insulation alone might not prevent moisture intrusion; and while having construction raised off the ground can help with moisture management, it does not inherently negate the need for vapor protection. Therefore, the context of moisture sensitivity of materials is key in understanding why vapor retarders may not be required under specific conditions.

SAMPLE

6. What is the minimum drip edge overlap at the eaves and gables of shingle roofs?

A. 1 inch

B. 2 inches

C. 3 inches

D. 4 inches

The minimum drip edge overlap at the eaves and gables of shingle roofs is set to ensure proper water management and to prevent any potential water infiltration into the roofing system. An overlap of 3 inches is specified to provide a suitable barrier against wind-driven rain and to direct water away from the underlying structures effectively. This helps in maintaining the integrity of the roof and protects the roofing materials and components from rot and damage over time. The other options suggest overlaps that may not provide sufficient protection against water seepage in adverse weather conditions. A smaller overlap could lead to vulnerabilities where water can penetrate, potentially compromising the roof's performance and durability. Thus, adhering to the 3-inch minimum for drip edge overlap helps uphold construction standards and prolongs the lifespan of the roofing system.

7. Lintels must be provided for all openings greater than how many feet in width?

A. 2

B. 3

C. 4

D. 6

Lintels are structural members used to support loads above openings in walls, such as windows and doors. In construction practices, their placement is critical for the stability and integrity of the structure. Openings in walls, even if they appear small, can lead to significant loads and stresses when loads from the building above are transferred through these openings. The requirement for lintels over openings greater than three feet in width is grounded in building codes and engineering practices, which recognize that larger openings increase the potential for structural issues if not properly supported. Specifically, at widths exceeding three feet, the risk of sagging, cracking, or even failure of the wall structure becomes more significant. Therefore, providing lintels in such scenarios is necessary to distribute loads evenly and maintain the structural integrity of the wall. While smaller openings may not require a lintel, this three-foot threshold is a common standard adopted to ensure safety and compliance with building regulations, as well as to safeguard against future structural problems. It's crucial for contractors to follow these guidelines closely to ensure that their work is up to code and the structures they build are safe for occupants.

SAMPLE

8. Must switching devices be located less than 5 feet from the inside walls of a pool?

A. TRUE

B. FALSE

The statement that switching devices must be located less than 5 feet from the inside walls of a pool is based on safety regulations established to protect individuals using the pool area. Specifically, the National Electrical Code (NEC) mandates that electrical equipment, including switching devices, must be positioned at a safe distance from water to minimize the risk of electrical shock or other hazards. In this context, having switching devices located too close to the pool could pose a serious danger. This regulation is in place to ensure that if someone were to come into contact with the pool water, they would not also come into contact with electrical currents from nearby equipment. The requirement of keeping switching devices at least 5 feet away creates a buffer zone that enhances safety for both swimmers and non-swimmers in the vicinity. This code is part of broader electrical safety standards designed to protect life and property around swimming pools, and adherence to these standards is critical in construction and maintenance practices for pools. Therefore, the assertion that switching devices must be located less than 5 feet from the inside walls of a pool aligns with established safety guidelines.

9. An accessory structure cannot exceed how many square feet?

A. 1,000

B. 2,000

C. 3,000

D. 4,000

The correct answer is based on the regulations governing accessory structures in many jurisdictions, which often have specified limits to maintain zoning and aesthetic standards within communities. In Alabama, as part of building codes and local ordinances, an accessory structure typically refers to a secondary building on a property, such as a shed, garage, or other supportive facilities. In this context, the limit of 3,000 square feet allows for a substantial structure while still ensuring it remains subordinate to the primary dwelling. By setting this limit, regulatory agencies aim to balance land use, minimize the potential for overdevelopment on a single lot, and ensure that such structures do not dominate the landscape or infringe on neighboring properties. Other options may reflect different interpretations or may be more applicable in different jurisdictions. However, the specific limit of 3,000 square feet is aligned with common standards found in Alabama, which is why this answer is the accurate choice. Understanding this regulatory framework is crucial for contractors to ensure compliance with local zoning laws when planning or constructing accessory buildings.

SAMPLE

10. What type of wire should be used for supporting metal ducts according to standard practices?

A. 10-gage galvanized wire

B. 12-gage galvanized wire

C. 16-gage galvanized wire

D. 18-gage galvanized wire

The use of 16-gage galvanized wire for supporting metal ducts aligns with established industry standards that take into consideration both strength and versatility. Galvanized wire effectively prevents rust and corrosion, which is particularly important in environments where moisture and various elements may be a concern. The 16-gage wire strikes a balance between being strong enough to support the weight of metal ducts while also being lightweight enough to handle and manipulate easily during installation. This specific gage ensures that the wire can bear the required loads without excessive strain, providing stability and safety for the ductwork. While other gauges of wire might be available, they may either be too weak or too strong for the specific applications related to ductwork support. For instance, a thicker gage could be more rigid and difficult to work with, which could complicate installation efforts. Thus, the choice of 16-gage galvanized wire is guided by both practical and compliance considerations in construction practices.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://alabamacontractors.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE