
AMT AIRFRAME ORAL AND PRACTICAL (O&P) PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://amtairframeoandp.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. What might indicate air in the hydraulic system during a brake check?

A. Excessive noise from the brake unit

B. Spongy action of brake pedals

C. Hard pressure when applying brakes

D. Inconsistency in brake fluid levels

2. What is an advantage of using halogenated hydrocarbons in fire extinguishing systems?

A. They are inexpensive

B. They leave no residue and are non-toxic

C. They are easily obtainable

D. They can be refilled easily

3. Which of the following conditions can lead to poor paint flow?

A. Excessive thinning of paint

B. High ambient temperature

C. Low air pressure and incorrect gun distance

D. Applying multiple coats

4. When splicing tubing by the inner sleeve method, what method can be used to insert a tight fitting inner sleeve into the replacement tube?

A. Heating the sleeve before insertion

B. Using a hydraulic press on the sleeve

C. Chilling the sleeve with dry ice or in cold water

D. Lubricating the sleeve for easy fit

5. What test can be performed to identify existing paint finishes?

A. Apply a coat of linseed oil to the surface

B. Apply a coat of engine oil to a small area

C. Use a heat gun to observe reactions

D. Wipe with water to see paint solubility

SAMPLE

6. What is windshield delamination?

A. The separation of the plies

B. The cracking of the windshield

C. The fading of the windshield tint

D. A structural failure of the frame

7. What is the purpose of a pressure relief valve in a hydraulic system?

A. To increase the flow rate of hydraulic fluid

B. To limit the amount of pressure in the system

C. To filter contaminants from the fluid

D. To enhance the power output of the hydraulic system

8. What is the function of an air-oil separator in a pneumatic deicing system?

A. To enhance the deicing process

B. To collect moisture from the air

C. To prevent rubber boot deterioration from oil

D. To cool the deicing boots

9. Where are anti-tear strips installed on aircraft and why?

A. On wing leading edges due to high stress

B. On the bottom surface of wings to enhance aerodynamics

C. Under reinforcing tape over ribs for aircraft exceeding 250 mph

D. Along the cockpit for structural support

10. What should the pressure of acetylene gas be when actually welding?

A. 10 psi

B. 5 psi

C. 15 psi

D. 20 psi

SAMPLE

Answers

SAMPLE

1. B
2. B
3. C
4. C
5. B
6. A
7. B
8. C
9. C
10. B

SAMPLE

Explanations

SAMPLE

1. What might indicate air in the hydraulic system during a brake check?

A. Excessive noise from the brake unit

B. Spongy action of brake pedals

C. Hard pressure when applying brakes

D. Inconsistency in brake fluid levels

A spongy action of brake pedals is a clear indication of air in the hydraulic system during a brake check because the presence of air bubbles in the hydraulic fluid disrupts the system's ability to transmit force effectively. When the brake pedal is pressed, the hydraulic fluid should create a firm, direct response due to the incompressibility of liquids. However, when air is introduced into the system, it creates compressible spaces that prevent the brake fluid from transmitting pressure uniformly. This results in a sensation of sponginess or vagueness in the pedal's feel, which suggests that the hydraulic system may need to be bled to remove the entrapped air and restore proper function. In contrast, excessive noise from the brake unit is more commonly associated with mechanical issues or low fluid levels rather than air in the system. Hard pressure when applying brakes suggests that the system is functioning correctly and that the brake fluid is free of air. Lastly, inconsistencies in brake fluid levels may point to leaks or other issues but do not directly indicate air present in the system during a pedal check.

2. What is an advantage of using halogenated hydrocarbons in fire extinguishing systems?

A. They are inexpensive

B. They leave no residue and are non-toxic

C. They are easily obtainable

D. They can be refilled easily

Halogenated hydrocarbons are widely used in fire extinguishing systems primarily because they leave no residue and are considered non-toxic to humans when handled properly. This is a significant advantage in various environments, particularly in aircraft and electronic equipment, where residue from traditional extinguishing agents can cause damage to sensitive equipment and require extensive cleanup efforts. The absence of residue means that after a fire event, there is minimal secondary damage from the extinguishing agent itself, which can save both time and costs related to repairs and cleaning. Furthermore, being non-toxic is crucial in ensuring the safety of personnel during and after a fire suppression event, allowing for quick re-entry into an area that has experienced a fire, without the risk of harmful exposure to chemicals typically associated with other types of extinguishing agents. While other choices mention attributes like cost or ease of acquisition, the unique benefit of no residue and low toxicity sets halogenated hydrocarbons apart in specialized fire protection scenarios.

SAMPLE

3. Which of the following conditions can lead to poor paint flow?

A. Excessive thinning of paint

B. High ambient temperature

C. Low air pressure and incorrect gun distance

D. Applying multiple coats

Poor paint flow can result from low air pressure and incorrect gun distance because these factors directly influence how the paint is atomized and how evenly it is applied onto the surface. When the air pressure is too low, the paint may not spray out in a fine mist but rather in larger droplets or may not atomize properly, leading to uneven application and poor coverage. Similarly, if the gun is too far from the surface, the paint can begin to dry or lose its proper consistency before it reaches the substrate, causing issues with adherence and flow. These combined conditions can greatly affect the quality of the finish and the overall appearance of the paint job, resulting in a rough surface or inadequate coverage. Proper adjustment of both air pressure and gun distance is crucial for achieving an optimal spray pattern, ensuring that the paint flows smoothly and adheres properly to the intended surface.

4. When splicing tubing by the inner sleeve method, what method can be used to insert a tight fitting inner sleeve into the replacement tube?

A. Heating the sleeve before insertion

B. Using a hydraulic press on the sleeve

C. Chilling the sleeve with dry ice or in cold water

D. Lubricating the sleeve for easy fit

Inserting a tight-fitting inner sleeve into a replacement tube can be effectively achieved by chilling the sleeve with dry ice or in cold water. This method causes the material of the sleeve to contract, reducing its size and allowing easier insertion into the replacement tube. Once the sleeve is positioned where needed, it will return to its original size, creating a snug fit. This is a common practice in tube splicing because it leverages the physical properties of materials, making it easier to fit parts together while ensuring a secure and reliable bond once the sleeve returns to temperature. The use of cold substances to facilitate assembly is widely applied in various engineering scenarios. The other methods may not be as effective; for example, heating the sleeve could potentially expand it, leading to difficulties in insertion or an unstable fit. A hydraulic press might provide excessive force that could damage the sleeve or tube. Lubrication could create a loose fit that does not provide the level of stability needed in a splice joint. Thus, chilling is the preferred and most effective method in this scenario.

5. What test can be performed to identify existing paint finishes?

A. Apply a coat of linseed oil to the surface

B. Apply a coat of engine oil to a small area

C. Use a heat gun to observe reactions

D. Wipe with water to see paint solubility

Applying a coat of engine oil to a small area of the paint finish can help identify the existing paint type. Engine oil interacts differently with various paints. For example, it may soften certain types of finishes, allowing for a visual assessment of the paint's properties. If the paint dissolves or becomes tacky, it may indicate that the finish is a type that is susceptible to oils, such as certain enamels or lacquers. If the paint remains unaffected, it could suggest a more durable or modern paint formulation. Understanding how different chemicals and substances interact with paint is crucial in aircraft maintenance. This method allows technicians to determine the condition and compatibility of the existing paint, thereby assisting in any necessary repainting or finishing processes.

SAMPLE

6. What is windshield delamination?

A. The separation of the plies

B. The cracking of the windshield

C. The fading of the windshield tint

D. A structural failure of the frame

Windshield delamination refers to the separation of the layers or plies that make up the windshield. This phenomenon can occur due to factors such as exposure to extreme temperatures, moisture ingress, or prolonged UV exposure, which can weaken the adhesive bond between the layers. When delamination happens, it compromises the structural integrity of the windshield, leading to potential visibility issues and the risk of water leaks into the aircraft. Identifying and addressing delamination early is essential in maintaining safety and performance standards in aviation.

7. What is the purpose of a pressure relief valve in a hydraulic system?

A. To increase the flow rate of hydraulic fluid

B. To limit the amount of pressure in the system

C. To filter contaminants from the fluid

D. To enhance the power output of the hydraulic system

The purpose of a pressure relief valve in a hydraulic system is to limit the amount of pressure in the system. This valve plays a crucial role in preventing excessive pressure that could potentially damage system components, such as pumps, cylinders, and hoses. By acting as a safety mechanism, the pressure relief valve opens when the pressure exceeds a predetermined level, allowing hydraulic fluid to escape and thereby reducing the pressure to a safe range. Maintaining proper pressure is vital for efficient operation and safety; if the pressure were to rise beyond capacity, it could lead to component failure, leaks, or even system collapse. Therefore, the pressure relief valve ensures that the hydraulic system operates within its designed limits, protecting both the equipment and personnel involved.

8. What is the function of an air-oil separator in a pneumatic deicing system?

A. To enhance the deicing process

B. To collect moisture from the air

C. To prevent rubber boot deterioration from oil

D. To cool the deicing boots

The function of an air-oil separator in a pneumatic deicing system is primarily to prevent rubber boot deterioration from oil. In these systems, air is used for deicing, and the compressed air can sometimes carry oil from the compressor. If this oil mixes with the air that is directed to the deicing boots, it can lead to the degradation of the rubber material, causing it to crack or deteriorate prematurely. By utilizing an air-oil separator, the system effectively removes oil from the air before it reaches the boots, thus preserving their structural integrity and ensuring that the deicing system functions properly over time. While some options may suggest enhancing the deicing process, collecting moisture, or cooling the boots, these do not accurately reflect the primary role of an air-oil separator, which is predominantly focused on protecting the integrity of the deicing boots from the harmful effects of oil contamination.

SAMPLE

9. Where are anti-tear strips installed on aircraft and why?

A. On wing leading edges due to high stress

B. On the bottom surface of wings to enhance aerodynamics

C. Under reinforcing tape over ribs for aircraft exceeding 250 mph

D. Along the cockpit for structural support

Anti-tear strips are specifically installed under reinforcing tape over ribs, particularly in aircraft that experience speeds exceeding 250 mph. This strategic placement is crucial because higher speeds can lead to more significant aerodynamic forces acting on the aircraft structure. The anti-tear strips serve to reinforce the connection between the skin of the aircraft and the underlying ribs, enhancing the overall strength and durability of the aircraft's structure. By preventing the tearing of the fabric or material covering the ribs, these strips help maintain the integrity of the aircraft's surface, which is essential for maintaining aerodynamic performance and ensuring safety at high speeds. Their use becomes especially vital in higher-performance aircraft, where the stresses on the structure are considerably greater than in slower, less demanding designs. This helps ensure that the reinforcing tape remains effective, extending the longevity and reliability of the aircraft's surface.

10. What should the pressure of acetylene gas be when actually welding?

A. 10 psi

B. 5 psi

C. 15 psi

D. 20 psi

The optimum pressure for acetylene gas when welding is generally around 5 psi. This pressure is considered ideal because it allows for a stable flame that is necessary for effective welding. At this pressure, the gas provides a sufficiently hot and controllable flame while minimizing the risk of flashback, which can occur if the pressure is too high. Additionally, operating at around 5 psi ensures that the acetylene remains in a dissolved state within the cylinder, preventing it from becoming unstable. Higher pressures can lead to an incomplete combustion and a less efficient welding process, potentially affecting the quality of the weld joint. Therefore, maintaining the pressure around 5 psi is crucial for achieving optimal welding results.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://amtairframeoandp.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE