ATPL INTENSIVE PROGRAM (IP) PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://atplip.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. Which factors limit the effective range of VHF transmissions under normal conditions?

A. Curvature of the Earth and height of the ionospheric layers.

B. Line-of-sight and height of the ionospheric layers.

C. Height of the ionospheric layers and angle of the radio wave.

D. Curvature of the Earth and line-of-sight.

2. Which of the following is NOT a warning provided by the ground proximity warning system (GPWS)?

A. Impending stall

B. Altitude loss after take-off or go-around

C. Incorrect landing configuration

D. Excessive climb rate

3. GPS system satellites transmit their signals on two carrier waves 1575 MHz and 1227 MHz. What does commercial aviation use?

A. Only the 1575 MHz carrier wave and two codes.

B. Only the 1575 MHz carrier wave and one code.

C. Only the 1227 MHz carrier wave and one code.

D. The two carrier waves and one public code.

4. How does the speed range between low speed buffet and high speed buffet change with increasing mass and altitude?

A. Decreases with altitude only.

B. Narrows with increasing mass and increasing altitude.

C. Is only limiting at low altitudes.

D. Increases with increasing mass.

5. Which coordinate system is used by the NAVSTAR GPS receiver for position determination?

A. PZ-90.

B. WGS 84.

C. ED 87.

D. ED 50.

SAMPLE

6. What happens to induced drag and parasite drag with increasing speed in straight and level flight?

A. Induced drag decreases and parasite drag increases.

B. Induced drag increases and parasite drag increases.

C. Induced drag decreases and parasite drag decreases.

D. Induced drag increases and parasite drag decreases.

7. Which statement about the alignment procedure for Inertial Navigation Systems (INS) at mid-latitudes is correct?

A. INS/IRS can only be aligned in the ALIGN mode.

B. INS/IRS can be aligned in either the ALIGN or NAV mode.

C. INS/IRS can be aligned in either the ALIGN or ATT mode.

D. INS/IRS can only be aligned in NAV mode.

8. During descent to the surface over land in the northern hemisphere, what change in wind direction and speed will a pilot typically experience?

A. Veering ca. 10 degrees, speed reduced by ca. 30%

B. Backing ca. 30 degrees, speed reduced by ca. 50%

C. Veering ca. 30 degrees, speed reduced by ca. 50%

D. Backing ca. 10 degrees, speed reduced by ca. 30%

9. Which statement about RNAV-routes is correct?

A. RNAV-routes are only used in terminal areas in order to make more efficient use of the approach and landing facilities of an airport.

B. All Waypoints of RNAV-routes are called phantom stations.

C. In general RNAV routes coincide with standard routes in order to make optimum use of the available VOR/DME-stations.

D. A method of navigation which permits aircraft operation on any desired flight path.

10. At 18,000 feet, approximately how much lower is the pressure compared to sea level?

A. 50% of the pressure at sea level.

B. 30% of the pressure at sea level.

C. 25% of the pressure at sea level.

D. 75% of the pressure at sea level.

SAMPLE

Answers

SAMPLE

1. D
2. D
3. B
4. B
5. B
6. A
7. B
8. B
9. D
10. A

SAMPLE

Explanations

SAMPLE

1. Which factors limit the effective range of VHF transmissions under normal conditions?

A. Curvature of the Earth and height of the ionospheric layers.

B. Line-of-sight and height of the ionospheric layers.

C. Height of the ionospheric layers and angle of the radio wave.

D. Curvature of the Earth and line-of-sight.

The effective range of Very High Frequency (VHF) transmissions is primarily influenced by two critical factors: the curvature of the Earth and the line-of-sight propagation characteristics. As radio waves travel, they tend to follow the curvature of the Earth. This means that as the distance from the transmitting antenna increases, radio signals may not reach a receiving antenna that is beyond the horizon. The height of the transmitting and receiving antennas can mitigate this effect to some extent, but the fundamental issue remains that signals are limited by how far they can travel before they encounter the Earth's curvature. Additionally, VHF signals primarily propagate via line-of-sight, which means the transmitting and receiving antennas must be within clear sight of each other for effective communication. Obstacles such as buildings, mountains, or even the Earth's terrain can block these signals, further limiting their range. Therefore, the combination of the Earth's curvature, which affects how far the signal can travel before being obstructed, and the line-of-sight requirement between antennas, are the primary factors that limit the effective range of VHF transmissions under normal conditions.

2. Which of the following is NOT a warning provided by the ground proximity warning system (GPWS)?

A. Impending stall

B. Altitude loss after take-off or go-around

C. Incorrect landing configuration

D. Excessive climb rate

The ground proximity warning system (GPWS) is designed to prevent controlled flight into terrain and provide warnings to pilots about potential hazards. It does this by monitoring the aircraft's altitude, configuration, and flight path. The warning issued for an impending stall is critical because it alerts pilots when the aircraft's speed is dropping to a level that could lead to a stall, which can occur if the aircraft is not at an appropriate angle of attack or speed. Altitude loss after take-off or during a go-around is also crucial, providing warnings about potentially dangerous situations where the aircraft is losing altitude unexpectedly after it has become airborne, which can lead to terrain collision if not corrected. Incorrect landing configuration is another important warning that informs the pilot when the aircraft is not in a proper configuration for landing (e.g., flaps or landing gear not correctly set). This warning is essential to ensure a safe landing approach. In contrast, excessive climb rate is not a recognized warning from the GPWS because the system primarily focuses on alerts that are critical for preventing terrain conflicts rather than monitoring performance in climb scenarios. A climb rate that is deemed excessive does not directly correlate to the potential for ground proximity issues or terrain collision, thus it is not part of the GPWS alert features.

SAMPLE

3. GPS system satellites transmit their signals on two carrier waves 1575 MHz and 1227 MHz. What does commercial aviation use?

A. Only the 1575 MHz carrier wave and two codes.

B. Only the 1575 MHz carrier wave and one code.

C. Only the 1227 MHz carrier wave and one code.

D. The two carrier waves and one public code.

In the context of commercial aviation and GPS technology, the correct understanding revolves around the use of the L1 frequency, which operates at 1575 MHz. This frequency is primarily used for civilian applications, including commercial aviation. The L1 signal includes a specific code called the C/A code, which stands for Coarse/Acquisition code. This code allows for navigation and position fixing for aircraft and other civilian users. The use of only the 1575 MHz carrier wave and one code is specifically designed to meet the needs of civilian aviation, providing appropriate accuracy while also being less complex than using multiple frequencies. This makes it more accessible for standard aviation applications without requiring additional, more advanced capabilities found in other services. In contrast, the other frequencies and codes that exist (such as the L2 frequency at 1227 MHz) are mainly used for more specialized applications or for military purposes, where higher precision and redundancy are required. Therefore, commercial aviation typically employs the L1 frequency along with the C/A code for effective operation and navigation.

4. How does the speed range between low speed buffet and high speed buffet change with increasing mass and altitude?

A. Decreases with altitude only.

B. Narrows with increasing mass and increasing altitude.

C. Is only limiting at low altitudes.

D. Increases with increasing mass.

The correct answer reflects the relationship between the speed range of buffet and two key factors: mass and altitude. As aircraft mass increases, the stall speed also rises. This means that at a higher mass, the aircraft is less responsive to control inputs and experiences buffet at higher speeds compared to when it is lighter. On the other hand, as altitude increases, the air density decreases, which influences the aerodynamic characteristics of the aircraft. At high altitudes, the aircraft operates at lower overall air densities, leading to a reduction in lift and a different stall behavior. This can contribute to the narrowing of the speed range between low speed buffet and high speed buffet. Together, these factors result in a combined effect where the range in which buffet occurs becomes narrower as both mass and altitude increase. Thus, the understanding of flight dynamics at varying masses and altitudes is critical in maintaining safety and control during flight, particularly as they pertain to stall warnings and buffet onset.

SAMPLE

5. Which coordinate system is used by the NAVSTAR GPS receiver for position determination?

A. PZ-90.

B. WGS 84.

C. ED 87.

D. ED 50.

The NAVSTAR GPS system utilizes the WGS 84 (World Geodetic System 1984) coordinate system for position determination. This global reference frame provides a consistent geodetic framework for navigation and mapping worldwide. WGS 84 includes a standardized set of parameters that describe the Earth's shape, such as its ellipsoid model, to accurately represent geographic locations in three-dimensional space. WGS 84 is instrumental for the GPS system as it facilitates the integration of satellite data to compute positions. The system is designed to meet the requirements for various applications, including military, civilian, and aviation usage, allowing accurate and reliable positioning across the globe. In contrast, the other choices represent different geodetic systems that either are region-specific or less commonly used in GPS technology. For example, PZ-90 is a geocentric coordinate system used in Russia, ED 87 and ED 50 refer to European datum systems that are more localized to specific geographical regions. These alternatives do not provide the global applicability and precision required for the functionality of GPS systems.

6. What happens to induced drag and parasite drag with increasing speed in straight and level flight?

A. Induced drag decreases and parasite drag increases.

B. Induced drag increases and parasite drag increases.

C. Induced drag decreases and parasite drag decreases.

D. Induced drag increases and parasite drag decreases.

In straight and level flight, as the speed of the aircraft increases, induced drag and parasite drag behave differently. Induced drag is primarily a byproduct of lift generation and is inversely related to airspeed; as speed increases, the angle of attack required to maintain lift decreases, leading to a reduction in induced drag. This phenomenon occurs because a higher airspeed allows the wings to generate the necessary lift at a lower angle of attack, thus decreasing the vortex strength and subsequently the induced drag. On the other hand, parasite drag, which encompasses all drag not associated with the generation of lift (such as form drag, skin friction, and interference drag), increases with speed. The faster an aircraft travels through the air, the greater the friction and pressure differential created, resulting in an increase in parasite drag. Therefore, as speed increases in straight and level flight, induced drag decreases while parasite drag increases. This relationship is foundational in understanding aircraft performance and efficiency at varying speeds.

SAMPLE

7. Which statement about the alignment procedure for Inertial Navigation Systems (INS) at mid-latitudes is correct?

A. INS/IRS can only be aligned in the ALIGN mode.

B. INS/IRS can be aligned in either the ALIGN or NAV mode.

C. INS/IRS can be aligned in either the ALIGN or ATT mode.

D. INS/IRS can only be aligned in NAV mode.

The correct assertion regarding the alignment procedure for Inertial Navigation Systems (INS) at mid-latitudes is that INS/IRS can be aligned in either the ALIGN or NAV mode. In the context of INS operations, alignment refers to the process of initializing the system with accurate positional data to enable it to function correctly. During this procedure, the system seeks to establish a position and orientation based on inertial measurements and perhaps other available data. The ALIGN mode is specifically designed for establishing the initial conditions of the system, which is crucial for precise navigational calculations. However, mid-latitude operations allow for additional flexibility, as the system can also transition to NAV mode while maintaining alignment. This is vital for systems that operate in dynamic environments where real-time position updates are needed. The ability of the INS/IRS to operate in both modes provides greater adaptability and efficiency. In NAV mode, the system can utilize navigation data from various sources to enhance positional accuracy, further optimizing performance under changing conditions. Thus, recognizing that both ALIGN and NAV modes provide pathways for effective alignment underscores the operational versatility and adaptability of modern inertial navigation systems, particularly at mid-latitudes, where unique challenges may arise.

8. During descent to the surface over land in the northern hemisphere, what change in wind direction and speed will a pilot typically experience?

A. Veering ca. 10 degrees, speed reduced by ca. 30%

B. Backing ca. 30 degrees, speed reduced by ca. 50%

C. Veering ca. 30 degrees, speed reduced by ca. 50%

D. Backing ca. 10 degrees, speed reduced by ca. 30%

When an aircraft descends to the surface over land in the northern hemisphere, it generally experiences a backing of the wind direction. This change is associated with a decrease in wind speed as the aircraft approaches the ground. More specifically, backing refers to the wind changing direction in a counterclockwise manner, typical of the effects of surface friction and the change in airflow patterns as the altitude decreases. The significant reduction in wind speed, about 50%, occurs due to this frictional drag as the aircraft gets closer to the surface. The air slows down as it interacts with the terrain, resulting in a lower speed experienced by the aircraft. This is particularly relevant for pilots to understand, as these changes can affect both the aircraft's performance and handling characteristics during the final approach and landing phase. In summary, during a descent over land in the northern hemisphere, the typical phenomena include a noticeable backing of the wind direction and a substantial decrease in wind speed, which aligns with the provided correct answer.

SAMPLE

9. Which statement about RNAV-routes is correct?

A. RNAV-routes are only used in terminal areas in order to make more efficient use of the approach and landing facilities of an airport.

B. All Waypoints of RNAV-routes are called phantom stations.

C. In general RNAV routes coincide with standard routes in order to make optimum use of the available VOR/DME-stations.

D. A method of navigation which permits aircraft operation on any desired flight path.

The statement that RNAV routes allow aircraft to operate on any desired flight path highlights the essence of Area Navigation (RNAV) systems. RNAV technology enables aircraft to navigate along a predetermined flight path using waypoints defined by coordinates rather than being constrained to conventional navigation aids like VORs (VHF Omnidirectional Range). This flexibility allows for more efficient routing, optimizing air traffic flow and reducing flight times. In the context of RNAV, pilots can utilize GPS or other navigation systems to follow flight paths that are more direct and economical. This capability is vital for enhancing the overall efficiency of airspace utilization, ultimately leading to reduced fuel consumption and lower emissions. The focus on any desired flight path captures the core benefit of RNAV, setting it apart from traditional navigation systems, which depend on a network of ground-based beacons. This adaptability becomes particularly advantageous in congested airspace or when aiming for specific routing that minimizes impact on surrounding communities and maximizes operational efficiency.

10. At 18,000 feet, approximately how much lower is the pressure compared to sea level?

A. 50% of the pressure at sea level.

B. 30% of the pressure at sea level.

C. 25% of the pressure at sea level.

D. 75% of the pressure at sea level.

At 18,000 feet, the atmospheric pressure is indeed significantly lower than at sea level, generally around 50% of the sea level pressure. At sea level, the standard atmospheric pressure is approximately 1013 hPa (hectopascals), whereas at 18,000 feet, the pressure drops to about 500 hPa. This drop represents a reduction in pressure by nearly half. Understanding how pressure changes with altitude is important in aviation, as it affects aircraft performance, engine efficiency, and pilot physiology. The actual pressure at a specific altitude can vary based on factors like temperature and weather conditions, but the general guideline is that, at 18,000 feet, pilots can expect the pressure to be around 50% of what it is at sea level, which is critical knowledge when flying and in operational planning.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://atplip.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE