COMMUNICATION, NAVIGATION, POSITION AND WARNING PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://commnavpositionwarning.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. On a magnetic compass, the fixed line used for directional reference is called what?

A. Lubber line

B. North line

C. Bearing line

D. Card line

2. Turbine engine exhaust gas temperatures are measured by using

A. Thermistors

B. Bimetal strips

C. Thermocouples

D. Resistance Temperature Detectors

3. Describe the procedure used to route coaxial cable from an antenna to a receiver.

A. The cable should be supported every 2 feet, bends should be 10 times the cable diameter, and it should be routed separately from other wires.

B. The cable should be routed along power cables to utilize space

C. The cable should be routed inside the aircraft skin

D. The cable should be run in a metal conduit that is grounded.

4. Why are two antennas usually required for an ILS system?

A. The localizer requires more power than the glideslope.

B. The localizer and glideslope signals are transmitted on different frequencies.

C. They operate on the same frequency but different polarizations.

D. One antenna monitors signals for redundancy.

5. What is the main purpose of a servo in an autopilot system?

A. Move flaps to adjust lift

B. Apply torque to the designed flying surfaces

C. Sense aircraft attitude

D. Provide electrical power to avionics

SAMPLE

6. What is the purpose of the annunciation system?

A. To alert the crew of an imminent problem

B. To display engine temperatures

C. To record flight data

D. To control autopilot

7. A gasket or sealant is used between the antenna mast and fuselage skin for what purpose?

A. To prevent moisture and corrosion

B. To improve RF transmission

C. To reduce weight

D. To seal the antenna mount

8. What are the two antennas usually required for an ILS system?

A. VOR and DME

B. ADF loop and sense

C. Glide slope and localizer

D. Localizer and glide slope reflector

9. The angle of attack indicator's operation is based on differential pressure measurement at a point where the airstream flows in a direction

A. Parallel to the travel of the aircraft

B. At rest in a stall condition

C. Perpendicular to the travel of the aircraft

D. Not parallel to the travel of the aircraft

10. Color markings on an instrument indicate what?

A. Normal operating range

B. Calibration constants

C. Minimums and maximums

D. Alarm thresholds

SAMPLE

Answers

SAMPLE

1. A
2. C
3. A
4. B
5. B
6. A
7. A
8. C
9. D
10. C

SAMPLE

Explanations

SAMPLE

1. On a magnetic compass, the fixed line used for directional reference is called what?

A. Lubber line

B. North line

C. Bearing line

D. Card line

The line that stays fixed on a magnetic compass for reading direction is the lubber line. It's attached to the compass housing and is aligned with the vessel's fore-and-aft axis, so it provides a consistent reference point as the compass card rotates to show magnetic north. When you read a bearing, you look at the number on the rotating card that lines up with the lubber line—the bearing is the direction relative to that fixed reference. This setup lets you relate the ship's direction to the compass reading accurately. Other terms aren't standard for this fixed reference on a marine compass, which is why they aren't used in practice.

2. Turbine engine exhaust gas temperatures are measured by using

A. Thermistors

B. Bimetal strips

C. Thermocouples

D. Resistance Temperature Detectors

Exhaust gas temperature in turbine engines is measured with thermocouples because they tolerate the very high temperatures and provide a fast, direct electrical signal that can be read by engine controls. A thermocouple consists of two dissimilar metals joined at the sensing junction; when the hot exhaust heats this junction, a small voltage is produced that changes with temperature, allowing the control system to determine the exhaust temperature. This setup works well in harsh, high temperature exhaust environments and doesn't require an external power source to generate the signal, which is why it's favored in aviation. In practice, high temperature variants like Type K are commonly used to endure the corrosive gases and thermal cycling of jet engines. Thermistors, while accurate, have a limited high temperature range and a nonlinear response that isn't ideal for the extreme conditions of engine exhaust. Bimetal strips are simple mechanical devices used for switches or indicators, not precise temperature measurement. Resistance temperature detectors are accurate and stable but typically have lower maximum temperatures and require electronic excitation, making them less suitable for the extreme, fast swings found in turbine exhaust compared to thermocouples.

SAMPLE

3. Describe the procedure used to route coaxial cable from an antenna to a receiver.

A. The cable should be supported every 2 feet, bends should be 10 times the cable diameter, and it should be routed separately from other wires.

B. The cable should be routed along power cables to utilize space

C. The cable should be routed inside the aircraft skin

D. The cable should be run in a metal conduit that is grounded.

Routing coax from an antenna to a receiver is all about protecting the signal and preventing interference in the aircraft environment. Keeping the cable supported every two feet helps avoid sag, fatigue on connectors, and movement that can loosen connections during vibration. A bend radius of about ten times the cable diameter avoids sharp turns that can change impedance, create reflections, or damage the shielding, which would degrade the received signal. Placing the coax away from other wires prevents EMI and crosstalk from power or data cables, preserving the integrity of the RF path. The other approaches invite problems: running coax alongside power cables increases noise pickup; routing inside the skin risks abrasion, heat, and damage and isn't a standard protective pathway; using a metal conduit adds weight and routing complexity without necessarily improving performance for a typical antenna feed. Following these practices keeps the RF path clean, reliable, and easy to service.

4. Why are two antennas usually required for an ILS system?

A. The localizer requires more power than the glideslope.

B. The localizer and glideslope signals are transmitted on different frequencies.

C. They operate on the same frequency but different polarizations.

D. One antenna monitors signals for redundancy.

The main idea is that the two parts of an ILS provide different kinds of guidance and must be received separately. The localizer gives horizontal guidance and operates in a VHF band, while the glideslope provides vertical guidance and uses a different frequency band (UHF-like). Because these signals live in separate frequency ranges, they can be transmitted and received without interfering with each other, allowing the aircraft to tune and process both streams simultaneously with dedicated receivers. This separation also lets each antenna be optimized for its specific beam pattern and coverage—one located at the far end of the runway for the localizer, and another near the approach end for the glideslope. The other ideas—more power, the same frequency with different polarizations, or relying on redundancy—don't explain why two antennas are used for the dual guidance signals.

5. What is the main purpose of a servo in an autopilot system?

A. Move flaps to adjust lift

B. Apply torque to the designed flying surfaces

C. Sense aircraft attitude

D. Provide electrical power to avionics

The main idea is that a servo in an autopilot system is an actuator that turns electrical commands into physical movement of the aircraft's control surfaces. It provides the torque needed to deflect the surfaces such as the elevator, ailerons, and rudder, letting the autopilot shape the airplane's attitude and flight path. Sensors determine how the aircraft is oriented, and the autopilot sends a signal to the servo to move the surfaces to the desired position. This role is different from sensing attitude or supplying power to avionics, and while servos can work with flaps, their primary purpose is to move the control surfaces to achieve the commanded flight attitude.

SAMPLE

6. What is the purpose of the annunciation system?

A. To alert the crew of an imminent problem

B. To display engine temperatures

C. To record flight data

D. To control autopilot

An annunciation system exists to grab the crew's attention when something abnormal or potentially problematic occurs, so quick action can be taken. It uses visual indicators and audible alarms to signal warnings and cautions, guiding pilots on what needs priority attention and what might require action now. Displaying engine temperatures is done through the cockpit instruments and displays, not the annunciation system. Recording flight data is the job of data recorders, separate from annunciations. And autopilot control is handled by the flight-control system, not by annunciation signaling.

7. A gasket or sealant is used between the antenna mast and fuselage skin for what purpose?

A. To prevent moisture and corrosion

B. To improve RF transmission

C. To reduce weight

D. To seal the antenna mount

The main idea here is weather sealing at the mounting joint. A gasket or sealant between the antenna mast and fuselage skin keeps moisture and humidity from seeping into the gap. When water gets in, it can cause corrosion of the skin, fasteners, and mounting hardware, and it can also affect the electrical connection at the mount, which in turn can degrade the antenna's reliability and performance over time. So preventing moisture intrusion and the resulting corrosion is the primary purpose. This isn't primarily about boosting RF transmission, and it isn't about reducing weight. While a good seal can help maintain a stable electrical ground at the mount, the driving reason is keeping the joint dry and corrosion-free, not simply sealing the mount itself.

8. What are the two antennas usually required for an ILS system?

A. VOR and DME

B. ADF loop and sense

C. Glide slope and localizer

D. Localizer and glide slope reflector

The essential idea is that an ILS provides two guidance cues—one horizontal and one vertical—through two dedicated antennas. The best answer is the combination of glide slope and localizer because these are the two antennas that form the ILS approach: the localizer supplies lateral guidance to keep you on the runway centerline, while the glide slope provides vertical guidance to establish the proper descent path to the runway. The localizer antenna is placed at the far end of the runway and creates a beam that guides you left or right to align with the centerline. The glide slope antenna is positioned near the approach end and generates a vertical guidance signal that tells you whether you're too high or too low on the descent, typically aiming for a 3-degree glide path. Together, they give precision on both axes to land safely. Other options don't fit because VOR and DME are separate navigation aids, not part of the ILS approach's two main antennas; an ADF loop and sense pertain to ADF navigation, not ILS; and a reflector isn't used for ILS—the system relies on dedicated transmitter arrays, not a reflector arrangement.

SAMPLE

9. The angle of attack indicator's operation is based on differential pressure measurement at a point where the airstream flows in a direction

A. Parallel to the travel of the aircraft

B. At rest in a stall condition

C. Perpendicular to the travel of the aircraft

D. Not parallel to the travel of the aircraft

An angle-of-attack indicator works by sensing how the airspeed component that meets the sensing port changes as the relative wind direction shifts with angle of attack. The pressure difference it uses comes from airflow hitting a port in which the flow is not aligned with the aircraft's motion. If the air were flowing parallel to the flight path, there would be little or no change in that pressure difference with small changes in angle, so the indicator wouldn't reflect the angle of attack accurately. Therefore the measurement point must be where the airstream flows in a direction not parallel to the travel of the aircraft. Contexts like "at rest in stall" describe conditions, not how the sensor operates, and choosing a direction that is exactly perpendicular to travel would still be an example of not-parallel flow, but the essential principle is simply that the flow direction at the sensing point is not parallel to the aircraft's path.

10. Color markings on an instrument indicate what?

A. Normal operating range

B. Calibration constants

C. Minimums and maximums

D. Alarm thresholds

Color markings on an instrument are there to show the limits of what's acceptable for that parameter. They mark the minimum and maximum values you should stay within, so you can tell at a glance whether the reading is within safe operating bounds or approaching a limit. This helps you quickly assess performance without calculating from the scale. They aren't calibration constants, which would be fixed adjustments to the instrument's readings, and they aren't the exact alarm thresholds themselves, though moving into a marked zone may indicate you're leaving the safe range and could trigger alarms.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://commnavpositionwarning.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE