CONSTRUCTION SUPERVISOR LICENSE PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://constructionsupervisor.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. **Which type of gypsum board is recommended for high-moisture areas?**

   A. Type C

   B. Type A

   C. Type X

   D. Water-resistant board

2. **How many and what size nails are required between a rafter and a top plate in a house?**

   A. 2-10d

   B. 2-12d

   C. 3-12d

   D. 3-10d

3. **What is the minimum thickness required for concrete slabs directly on ground in an industrial park?**

   A. 3 inches with an approved vapor barrier

   B. 4 inches without an approved vapor barrier

   C. 3½ inches with or without an approved vapor barrier

   D. 5 inches on a stone base without an approved vapor barrier

4. **What is the minimum clearance required between combustibles and an interior masonry chimney?**

   A. Zero clearance

   B. 1 inch

   C. 2 inches

   D. 4 inches

5. **What is the minimum pitch roof onto which metal roof shingles may be installed?**

   A. 1

   B. 4

   C. 2

   D. 3

SAMPLE

6. What is the required width for a residential driveway?

A. 10 feet

B. 12 feet

C. 8 feet

D. 6 feet

7. Where a slab is below grade, how thick is the sand base course to be?

A. 2 "

B. 3 "

C. 4 "

D. 6 "

8. How many square feet of shingles are in a bundle of architectural shingles, assuming that there are three bundles to a square?

A. 33 1/3

B. 25

C. 100

D. 50

9. For assembly use groups, what is the maximum floor area allowed per occupant for standing room in an exhibition hall?

A. One person per 5 $ft.^2$

B. One person per 7 $ft.^2$

C. One person per 15 $ft.^2$

D. One person per 20 $ft.^2$

10. What is the required height range for manual fire alarm boxes to the activating handle above the finished floor?

A. 36", 48"

B. 36", 54"

C. 42", 48"

D. 42", 54"

SAMPLE

Answers

SAMPLE

1. D
2. D
3. C
4. C
5. D
6. B
7. C
8. A
9. A
10. C

SAMPLE

Explanations

SAMPLE

1. Which type of gypsum board is recommended for high-moisture areas?

A. Type C

B. Type A

C. Type X

D. Water-resistant board

Water-resistant board is specifically designed for high-moisture areas, making it the ideal choice in environments such as bathrooms, kitchens, and laundry rooms. This type of gypsum board is treated to enhance its moisture resistance and reduce the potential for mold growth, which is critical for maintaining indoor air quality and the integrity of the building structure. In contrast, other types of gypsum boards such as Type C, Type A, and Type X serve different purposes. Type C is often used for sound control and is not specifically designed for moisture resistance. Type A is a general-purpose gypsum board, suited for a variety of applications but lacking the special properties required for high-moisture environments. Type X offers fire resistance but does not provide the moisture-proof qualities necessary for areas exposed to high humidity or direct water exposure. Therefore, water-resistant board stands out as the most suitable option for such conditions.

2. How many and what size nails are required between a rafter and a top plate in a house?

A. 2-10d

B. 2-12d

C. 3-12d

D. 3-10d

The requirement for the number and size of nails used to connect rafters to the top plate is based on building codes and best practices for structural integrity. In most cases, building codes dictate that a rafter should be secured to the top plate using three nails. The typical size for these nails is 10d (10-penny), which provides sufficient holding power while also facilitating easier installation and adequate penetration into both the rafter and the top plate. Using three 10d nails helps ensure that the connection is robust enough to withstand various stresses such as wind uplift and the load of the roofing materials. This connection detail is crucial for maintaining the overall structural stability of the roof framing system in residential construction. Alternative options such as two or three nails of larger sizes like 12d would not align with common building practices, where the use of 10d nails has been widely accepted for this specific application.

SAMPLE

3. What is the minimum thickness required for concrete slabs directly on ground in an industrial park?

A. 3 inches with an approved vapor barrier

B. 4 inches without an approved vapor barrier

C. 3½ inches with or without an approved vapor barrier

D. 5 inches on a stone base without an approved vapor barrier

The minimum thickness for concrete slabs placed directly on the ground in an industrial park is generally determined by structural integrity, load-bearing capacity, and potential moisture issues. A thickness of 3½ inches provides a balanced approach for various applications, offering sufficient strength to support typical industrial loads while also addressing concerns like cracking, settling, and the effects of frost heave. The dimensions of 3½ inches allow for the concrete to be thick enough to withstand the stresses encountered in industrial environments without over-engineering the slab, thus maintaining cost-effectiveness. Additionally, this thickness can work well with or without a vapor barrier, which plays an essential role in controlling moisture transmission from the soil below but is not a strict requirement for the structural integrity of the slab. Therefore, the choice of 3½ inches caters to flexibility in construction while adhering to standard practices in the industry. In comparison, the other options either suggest a thickness that may not meet practical load-bearing needs or impose unnecessary constraints regarding the use of vapor barriers. Understanding the engineering principles and building codes in concrete construction is critical for making informed decisions about slab specifications in different settings.

4. What is the minimum clearance required between combustibles and an interior masonry chimney?

A. Zero clearance

B. 1 inch

C. 2 inches

D. 4 inches

The minimum clearance required between combustibles and an interior masonry chimney is crucial for ensuring safety and preventing fire hazards. A clearance of 2 inches is generally established based on building codes and fire safety regulations. This distance is meant to allow for adequate ventilation and to prevent heat buildup that could ignite nearby combustible materials. Having this specified clearance minimizes the risk of combustion through direct contact or excessive heat transfer. It is important that construction supervisors and those involved in building practices adhere to these regulations to maintain not only compliance but also a safe environment for the occupants. Maintaining a clearance of 2 inches provides a balance between safety and practical construction guidelines, preventing any undue strain on space limitations while still focusing on fire safety. This understanding is integral for those preparing for a Construction Supervisor License, emphasizing the importance of fire safety standards in construction practices.

SAMPLE

5. What is the minimum pitch roof onto which metal roof shingles may be installed?

A. 1

B. 4

C. 2

D. 3

The required minimum pitch for installing metal roof shingles is typically 3:12. This specification is grounded in both performance and code considerations. A roof with a pitch of 3:12 means that for every 12 horizontal inches, the roof rises 3 inches vertically. This pitch helps ensure proper drainage and allows for the effective shedding of water, which is vital to prevent moisture buildup and potential leaks over time. Installing metal shingles on a roof with a pitch lower than this minimum can lead to problems such as water pooling and increased susceptibility to wind-driven rain, which can compromise the roof's integrity. Therefore, adhering to a minimum pitch of 3:12 is a standard safety practice that promotes durability and effectiveness in roof design, making this the correct answer.

6. What is the required width for a residential driveway?

A. 10 feet

B. 12 feet

C. 8 feet

D. 6 feet

The correct width for a residential driveway is typically considered to be 12 feet. This width allows for comfortable entry and exit of vehicles, accommodating larger vehicles such as SUVs and trucks while ensuring enough space for vehicles to navigate without causing disruption to landscaping or surrounding structures. A 12-foot width also aids in providing adequate space for two vehicles to pass each other, which is increasingly important in residential areas where on-street parking may not be available. While narrower driveways such as 10 feet or 8 feet might be acceptable in certain situations, they can restrict access and make maneuvering more challenging. A 6-foot width would be insufficient for most standard vehicles, resulting in difficulties during parking or driving. Therefore, adhering to the standard of 12 feet helps promote safety and convenience in residential settings.

7. Where a slab is below grade, how thick is the sand base course to be?

A. 2 "

B. 3 "

C. 4 "

D. 6 "

When installing a sand base course for a slab below grade, it is typically recommended to use a thickness of around 4 inches. This thickness provides adequate support for the concrete slab above, contributing to proper drainage and reducing the risk of moisture-related issues. A 4-inch sand base helps to distribute the load of the slab evenly over the subgrade, minimizing settling and cracking. Additionally, this thickness is effective for allowing for proper compaction and creating a stable layer that promotes good performance of the slab. The sand also acts as a capillary break, which is crucial to prevent water from seeping into the concrete from the underlying soil, thus ensuring the longevity and durability of the slab. Thinner layers, such as 2 inches or 3 inches, may not provide sufficient support or drainage capabilities, potentially leading to structural issues. A thicker layer, such as 6 inches, may be unnecessary and can lead to additional costs and labor without significant benefits. Therefore, a 4-inch sand base is both a practical and effective choice for a slab that is below grade.

SAMPLE

8. How many square feet of shingles are in a bundle of architectural shingles, assuming that there are three bundles to a square?

A. 33 1/3

B. 25

C. 100

D. 50

In roofing terminology, a "square" refers to an area of 100 square feet. Architectural shingles, commonly used in roofing due to their durability and aesthetic appeal, are typically sold in bundles. When it comes to architectural shingles, it is standard for there to be three bundles required to cover one square. To determine how many square feet are in one bundle of architectural shingles, you can divide the total square footage covered by a square (100 square feet) by the number of bundles per square (which is three). Calculating this gives: 100 square feet / 3 bundles = approximately 33 1/3 square feet per bundle. This calculation supports the assertion that each bundle of architectural shingles effectively covers about 33 1/3 square feet. Understanding this concept is critical, as it directly impacts ordering materials, budgeting for roofing projects, and ensuring adequate coverage on existing structures.

9. For assembly use groups, what is the maximum floor area allowed per occupant for standing room in an exhibition hall?

A. One person per 5 ft.^{2}

B. One person per 7 ft.^{2}

C. One person per 15 ft.^{2}

D. One person per 20 ft.^{2}

The maximum floor area allowed per occupant for standing room in an exhibition hall is established to ensure safety and comfort during events. Focusing on the correct choice, the guideline of one person per 5 square feet in assembly use groups reflects the need for adequate space to allow for movement, emergency egress, and overall safety within densely populated areas such as exhibition halls where attendees may be gathered closely together. This density allows for a more manageable influx of people while also ensuring that there is sufficient room for individuals to navigate through the space, which is critical during emergencies. Factors such as crowd dynamics, visibility, and the necessary clearance for both attendees and emergency personnel play into the rationale behind this specification. The other choices reflect larger space allowances per occupant, which might be applicable in different scenarios or types of gatherings but do not fit the standards for standing room in an assembly context like an exhibition hall where maximized capacity and interaction are expected.

SAMPLE

10. What is the required height range for manual fire alarm boxes to the activating handle above the finished floor?

A. 36", 48"

B. 36", 54"

C. 42", 48"

D. 42", 54"

The required height range for manual fire alarm boxes to the activating handle above the finished floor is typically specified to ensure accessibility for all individuals, including those with disabilities. The range of 42 inches to 48 inches is designed to allow easy reach for most people while also adhering to safety regulations. This height range is commonly referenced in the National Fire Protection Association (NFPA) standards as well as the Americans with Disabilities Act (ADA) requirements for accessibility. Selecting a height between 42 inches and 48 inches accommodates both average height individuals and those in wheelchairs, ensuring that everyone can operate the manual fire alarm if necessary. This standard helps promote safety by ensuring that fire alarms are not only accessible but also functional in an emergency situation. Thus, this height range maximizes the effectiveness of fire alarm systems in buildings, enhancing overall safety protocols.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://constructionsupervisor.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE