# ET ASNT LEVEL I PRACTICE EXAM (SAMPLE)

## STUDY GUIDE



## SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

**VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE**

https://etasntlevel1.examzify.com

**Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.**

**ALL RIGHTS RESERVED.**

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

# Table of Contents


Copyright ..... 1

Table of Contents ..... 2

Introduction ..... 3

How to Use This Guide ..... 4

Questions ..... 5

Answers ..... 8

Explanations ..... 10

Next Steps ..... 16


SAMPLE

# Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

# How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

### 1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

### 2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

### 3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

### 4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

### 5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

### 6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

# Questions

SAMPLE

**1. One principal advantage of spinning probe eddy current instruments is:**

A. The ability to locate the circumferential position of defects

B. Relative insensitivity to vibration

C. A variety of internal and surface defects that may be detected

D. All of the above

**2. Which test method would be suitable for non-damaging evaluation of a material's properties?**

A. Destructive testing

B. Nondestructive testing

C. Impact testing

D. Load testing

**3. Why is understanding magnetic permeability crucial in Eddy Current Testing?**

A. It determines the required voltage for testing

B. It helps in evaluating the material's response to the eddy currents being induced

C. It affects the testing speed

D. It is only relevant for ferromagnetic materials

**4. Which of the following is not a primary purpose for using an eddy current standard?**

A. Determine if the eddy current test system is capable of performing the test properly

B. Determine if a discontinuity is cause for rejection

C. Determine the instrument control settings needed to pass the highest percentage of test specimens run

D. Determine if the sensitivity of a test system has drifted with time

**5. What are "probe coil designs" in the context of Eddy Current Testing?**

A. The specific voltage requirements for the testing equipment

B. The arrangement of the coils in the probe, affecting sensitivity and application

C. The choice of materials used for the probes

D. The length of time required for the test

SAMPLE

**6. What aspect of nonmagnetic materials is crucial for eddy current testing effectiveness?**

A. Thickness

B. Surface condition

C. Conductivity

D. Color

**7. The magnitude of the indication caused by a discontinuity during an eddy current test on tubing depends on which of the following?**

A. The depth of the discontinuity

B. The width of the discontinuity

C. The length of the discontinuity

D. All of the above

**8. Which unit defines flux density?**

A. A maxwell

B. A gauss

C. An ohm

D. A mho

**9. In Eddy Current Testing, what defines the expected patterns during a coherency check?**

A. Industry-specific calibration standards

B. The known characteristics of the testing material

C. The historical data from previous tests

D. The specifications of the equipment used

**10. Which of the following cannot be tested by the eddy current testing method?**

A. A 102 mm (4 in.) thick plate for small discontinuities

B. Tubing for surface cracks

C. Rod for laps and seams

D. Tubing for variations in outside diameter

SAMPLE

# Answers

SAMPLE

1. A
2. B
3. B
4. C
5. B
6. C
7. D
8. B
9. B
10. A

SAMPLE

# Explanations

SAMPLE

## 1. One principal advantage of spinning probe eddy current instruments is:

A. The ability to locate the circumferential position of defects

B. Relative insensitivity to vibration

C. A variety of internal and surface defects that may be detected

D. All of the above

*The principal advantage of spinning probe eddy current instruments lies in their ability to locate the circumferential position of defects within the material being tested. This capability is particularly important in applications where defects may exist along the circumference of a component, such as pipes or tubing. The spinning action of the probe allows for a more comprehensive scan of the surface, enabling the operator to identify and map the position of defects accurately. While other options may describe beneficial features of eddy current testing, the unique ability to determine the circumferential location is what sets spinning probe eddy current instruments apart. It is this precise defect positioning that enhances the effectiveness of inspections, especially in industries where structural integrity is critical.*

## 2. Which test method would be suitable for non-damaging evaluation of a material's properties?

A. Destructive testing

B. Nondestructive testing

C. Impact testing

D. Load testing

*The suitable choice for non-damaging evaluation of a material's properties is nondestructive testing. Unlike destructive methods, which compromise the integrity of the material being tested, nondestructive testing allows for the examination and analysis of a material without causing any damage. This means that the material can still be utilized after testing, making nondestructive testing an essential practice in many industries where maintaining the usability of materials is crucial. Nondestructive testing encompasses various techniques, such as ultrasonic testing, radiographic testing, magnetic particle testing, and dye penetrant testing, all of which provide valuable insights into a material's properties, including defects, composition, and condition. This flexibility and low risk of damaging the material make nondestructive testing an ideal choice for ensuring quality and safety in areas like construction, manufacturing, and aerospace. In contrast, methods like destructive testing inherently damage the sample, impacting its future usefulness. Impact testing and load testing are typically aimed at understanding specific behavior under stress or impact, but these methods can also compromise the specimen being assessed. Thus, they do not align with the concept of non-damaging evaluation.*

SAMPLE

## 3. Why is understanding magnetic permeability crucial in Eddy Current Testing?

A. It determines the required voltage for testing

B. It helps in evaluating the material's response to the eddy currents being induced

C. It affects the testing speed

D. It is only relevant for ferromagnetic materials

*Understanding magnetic permeability is crucial in Eddy Current Testing because it helps in evaluating how a material responds to the eddy currents being induced. Magnetic permeability is a property that indicates how easily a material can become magnetized or how well it can conduct magnetic fields. In the context of eddy current testing, which relies on the interaction between induced eddy currents and the material characteristics, magnetic permeability directly affects the way these currents flow through the material. When eddy currents are induced in a conductive material, the distribution and density of these currents will vary based on the material's permeability. A higher permeability generally allows eddy currents to circulate more freely, while lower permeability can hinder their flow. This understanding allows technicians to better interpret test results, including identifying flaws or discriminating between different materials. For instance, if a material has high permeability, it may exhibit a different attenuation of the eddy currents compared to a material with low permeability. This relationship between permeability and eddy currents is pivotal for accurate testing and analysis, ensuring that the testing effectively highlights any anomalies or variations within the material.*

## 4. Which of the following is not a primary purpose for using an eddy current standard?

A. Determine if the eddy current test system is capable of performing the test properly

B. Determine if a discontinuity is cause for rejection

C. Determine the instrument control settings needed to pass the highest percentage of test specimens run

D. Determine if the sensitivity of a test system has drifted with time

*The determination of instrument control settings to optimize the performance of the eddy current test system on test specimens is not considered a primary purpose of using an eddy current standard. Instead, the primary purposes revolve around establishing criteria for testing and ensuring the system's reliability and sensitivity. Utilizing an eddy current standard primarily focuses on validating the system's capabilities, such as confirming that it can effectively detect discontinuities (which relates to the first purpose), determining whether identified discontinuities warrant rejection based on industry standards (the second purpose), and checking if the sensitivity of the test system maintains its required performance over time (the fourth purpose). In contrast, setting instrument control settings to maximize passing rates on test specimens is more about operational optimization, rather than a foundational purpose of standards. While control settings are important for effective testing, they do not directly relate to establishing or validating the fundamental capabilities of the eddy current test system. Thus, it diverges from the essential functions that the use of standards is intended to fulfill.*

SAMPLE

## 5. What are "probe coil designs" in the context of Eddy Current Testing?

A. The specific voltage requirements for the testing equipment

B. The arrangement of the coils in the probe, affecting sensitivity and application

C. The choice of materials used for the probes

D. The length of time required for the test

*Probe coil designs refer to the specific arrangement and configuration of coils within the probe used in Eddy Current Testing (ECT). This design is crucial because it significantly affects the sensitivity of the probe and its ability to detect various types of flaws or defects in the material being examined. The arrangement can include factors like the number of turns in the coil, the spacing between coils, coil diameter, and the orientation of the coils, all of which influence how effectively the probe can interact with the eddy currents induced in the conductive material. Properly designed probe coils can enhance the resolution of the measurements and improve the probe's performance in specific applications, such as detecting surface cracks or measuring material thickness. Therefore, understanding and optimizing probe coil designs is key to achieving accurate and reliable results in Eddy Current Testing.*

## 6. What aspect of nonmagnetic materials is crucial for eddy current testing effectiveness?

A. Thickness

B. Surface condition

C. Conductivity

D. Color

*For eddy current testing, the conductivity of nonmagnetic materials is a crucial aspect as it directly influences the generation and response of eddy currents during inspection. Eddy current testing relies on electromagnetic induction, where alternating currents create magnetic fields that induce circulating currents (eddy currents) in conductive materials. Materials with higher conductivity allow for the generation of stronger eddy currents that can more effectively reveal flaws or changes in the material's properties. The interaction between the induced currents and the material's defects creates measurable impedance changes that can be analyzed to assess quality and integrity. In contrast, factors such as thickness and surface condition can affect the depth of penetration of the eddy currents and the effectiveness of the inspection, but they do not fundamentally determine the ability to generate the currents themselves. Color has no relevance in the context of eddy current testing since it does not influence the electromagnetic properties of the material. Thus, conductivity stands out as the critical parameter for ensuring effective eddy current testing.*

SAMPLE

## 7. The magnitude of the indication caused by a discontinuity during an eddy current test on tubing depends on which of the following?

A. The depth of the discontinuity

B. The width of the discontinuity

C. The length of the discontinuity

D. All of the above

*In eddy current testing, the magnitude of the indication caused by a discontinuity is influenced by several factors related to the characteristics of the discontinuity itself. Each of these factors plays a role in how the eddy currents behave when they encounter a discontinuity within the material. The depth of the discontinuity affects how much of the eddy current is disrupted. Shallower defects might only slightly alter the path of the currents, while deeper defects can cause more significant disruptions, leading to stronger indications. The width of the discontinuity is also crucial. A wider defect will interact with more of the eddy currents, resulting in a more pronounced change in the current flow and, consequently, a larger indication on the testing equipment. Similarly, the length of the discontinuity affects how long the eddy current must travel through the disrupted area. A longer defect can create a more significant alteration in the eddy current pattern, which translates to higher signal amplitudes that are easier to detect. Since all these dimensions—depth, width, and length—impact the interaction between the eddy currents and the discontinuity in the material, the overall magnitude of the indication during an eddy current test is dependent on all of the above attributes. This comprehensive understanding emphasizes the*

## 8. Which unit defines flux density?

A. A maxwell

B. A gauss

C. An ohm

D. A mho

*Flux density is defined as the strength of a magnetic field per unit area, which is commonly described in terms of the unit "gauss." The gauss is a cgs (centimeter-gram-second) unit of measurement that specifically quantifies magnetic flux density. One gauss is equal to one maxwell per square centimeter. This makes it the appropriate unit for measuring the magnetic field density in various applications, particularly in electromagnetism and magnetics. Other options represent different physical concepts. For instance, the maxwell measures magnetic flux rather than flux density. An ohm is the unit of electrical resistance, and a mho (the inverse of ohm) is a unit of electrical conductance. None of these concepts directly relates to measuring magnetic flux density. Therefore, the gauss is clearly the correct answer for defining flux density.*

SAMPLE

## 9. In Eddy Current Testing, what defines the expected patterns during a coherency check?

A. Industry-specific calibration standards

B. The known characteristics of the testing material

C. The historical data from previous tests

D. The specifications of the equipment used

*In Eddy Current Testing (ECT), the expected patterns during a coherency check are primarily defined by the known characteristics of the testing material. This includes factors such as the material's conductivity, permeability, geometry, and any known flaws or features within the material. Understanding these attributes allows technicians to establish a baseline for the expected signals during testing. During a coherency check, if the observed patterns match the anticipated signals based on these material characteristics, it indicates that the testing setup is functioning correctly and is capable of detecting variations within the material that may suggest flaws or areas of concern. This process is crucial for verifying the accuracy and reliability of the tests being performed, as it ensures that the test is sensitive to the specific properties of the material being examined. While calibration standards, historical data, and equipment specifications are indeed important in different contexts, they do not directly define the expected patterns as specifically as the material characteristics do. Calibration standards can help ensure that equipment readings are correct, historical data can provide context for expectations, and equipment specifications provide limits on performance; however, the fundamental relationship between the eddy currents and the material properties is what determines the expected signal patterns in this context.*

## 10. Which of the following cannot be tested by the eddy current testing method?

A. A 102 mm (4 in.) thick plate for small discontinuities

B. Tubing for surface cracks

C. Rod for laps and seams

D. Tubing for variations in outside diameter

*Eddy current testing is an effective non-destructive testing method primarily used for detecting surface and near-surface discontinuities in conductive materials. The technique relies on inducing eddy currents in the material and measuring the change in these currents as they encounter flaws. When considering the thickness of materials, the capability of eddy current testing diminishes with increased thickness. A 102 mm (4 in.) thick plate is too thick for this method to effectively detect small discontinuities. The penetration depth of eddy currents is limited, often being a fraction of a millimeter to a few millimeters, but can be significantly less in very thick materials. This makes it impractical for identifying small flaws deep within such a substantial thickness. In contrast, eddy current testing is highly suitable for detecting surface cracks in tubing, assessing laps and seams in rods, and evaluating variations in outside diameter of tubing, as these conditions primarily involve surface and near-surface anomalies which are within the accessible range of this testing technique.*

SAMPLE

# Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://etasntlevel1.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE