FIA AIRCRAFT PERFORMANCE PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://fiaaircraftperformance.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. **What is the approximate crosswind component for landing on Rwy 30 with a wind from 020° at 15 kts?**

   A. 5 knots

   B. 10 knots

   C. 15 knots

   D. 20 knots

2. **What is the approximate total distance required to clear a 50-foot obstacle with a temperature of 20°C and a pressure altitude of 1,000 ft?**

   A. 1,400 feet

   B. 1,724 feet

   C. 2,023 feet

   D. 1,850 feet

3. **How do you compute endurance and range from usable fuel and throttle settings?**

   A. Endurance = usable fuel × consumption rate; Range = TAS + endurance

   B. Endurance = consumption rate / usable fuel; Range = TAS × endurance

   C. Endurance = usable fuel − consumption rate; Range = TAS − endurance

   D. Endurance = usable fuel / consumption rate (hours); Range ≈ TAS × endurance, adjusted for headwind/tailwind

4. **What is the purpose of crosswind correction factors in landing distance estimates?**

   A. Crosswind corrections apply only to climb performance.

   B. Crosswind correction factors are applied to takeoff distance estimates.

   C. Crosswind has no effect on landing distance.

   D. Apply crosswind correction factors to landing distance estimates.

5. **Which statement about wind direction and takeoff distance is correct?**

   A. Headwinds reduce the takeoff distance required to clear an obstacle

   B. Headwinds increase the takeoff distance required

   C. Crosswinds are the only factor affecting takeoff distance

   D. Wind has no effect on takeoff distance

SAMPLE

6. Which input is explicitly included when calculating the takeoff distance to clear an obstacle?

A. Obstacle height and geometry

B. Aircraft color

C. Cabin pressure

D. Passenger count

7. What conclusion can be drawn if the maximum demonstrated crosswind component is exceeded during landing?

A. Landing will be successful

B. Maximum demonstrated crosswind component is not exceeded

C. Landing may be attempted but is risky

D. The maximum demonstrated crosswind component is exceeded

8. Along which axis is the center of gravity of an aircraft computed?

A. Vertical axis

B. Transverse axis

C. Longitudinal axis

D. Horizontal axis

9. Which statement about wind effects on landing distance is correct?

A. Headwind increases landing distance

B. Tailwind decreases landing distance

C. Surface condition does not affect landing distance

D. Tailwind increases landing distance

10. How does deploying flaps influence takeoff distance and initial climb performance in light aircraft?

A. Flaps typically reduce takeoff speed and distance and may improve initial climb angle, but increase drag and reduce maximum climb rate and cruise speed

B. Flaps increase takeoff speed and distance

C. Flaps have no effect on takeoff performance

D. Flaps only affect landing

SAMPLE

Answers

SAMPLE

1. C
2. B
3. D
4. D
5. A
6. A
7. D
8. C
9. D
10. A

SAMPLE

Explanations

SAMPLE

1. What is the approximate crosswind component for landing on Rwy 30 with a wind from 020° at 15 kts?

A. 5 knots

B. 10 knots

C. 15 knots

D. 20 knots

To determine the approximate crosswind component for landing on Runway 30 with a wind from 020° at 15 knots, it is essential to understand the concept of wind components relative to the runway direction. Runway 30 is aligned at a magnetic heading of 300°, which means that the crosswind component can be calculated by finding the angle between the runway heading and the wind direction. In this case, the wind is coming from 020°. To find the angle between the wind direction and the runway, you take the difference between 300° and 20°, yielding an angle of 280° or simply 80° when considering crosswind calculations. The sine of this angle will give you the crosswind component. The crosswind component is calculated using the formula: Crosswind Component = Wind Speed × sin(angle). Substituting the values: - Wind Speed = 15 knots, - Angle = 80° (the angle relative to the runway). Calculating the sine of 80° yields approximately 0.98: Crosswind Component = 15 knots × sin(80°) ≈ 15 knots × 0.98 ≈ 14.7 knots. This result rounds to about 15 knots.

2. What is the approximate total distance required to clear a 50-foot obstacle with a temperature of 20°C and a pressure altitude of 1,000 ft?

A. 1,400 feet

B. 1,724 feet

C. 2,023 feet

D. 1,850 feet

To determine the approximate total distance required to clear a 50-foot obstacle at a temperature of 20°C and a pressure altitude of 1,000 ft, one must consider a few factors related to aircraft performance, including the aircraft's takeoff distance and climb performance. At a temperature of 20°C and a pressure altitude of 1,000 ft, the performance of the aircraft will be fairly standard, enabling pilots to utilize established charts and performance data. In typical conditions, the required distance to clear a 50-foot obstacle can be computed using performance data from the aircraft's flight manual, which provide the necessary calculations for various altitudes and temperatures. The correct answer indicates that the total distance required to clear the obstacle is approximately 1,724 feet. This figure reflects the combined distances of the takeoff run and the initial climb. It accounts for the need for additional distance to ensure that the aircraft can gain sufficient altitude safely above the obstacle while considering the aircraft's performance capabilities at the specific temperature and altitude. Consistently, pilots rely on these performance calculations to ensure safety and compliance with regulatory standards, taking into consideration that most scenarios including a 50-foot obstacle will require detailed knowledge of the aircraft's capabilities along with specific environmental conditions. The

SAMPLE

3. How do you compute endurance and range from usable fuel and throttle settings?

A. Endurance = usable fuel × consumption rate; Range = TAS + endurance

B. Endurance = consumption rate / usable fuel; Range = TAS × endurance

C. Endurance = usable fuel − consumption rate; Range = TAS − endurance

D. Endurance = usable fuel / consumption rate (hours); Range ≈ TAS × endurance, adjusted for headwind/tailwind

Endurance measures how long the airplane can stay in the air on the usable fuel at the current throttle setting, so the fuel burn rate (how much fuel is used per hour) and the amount of usable fuel are the key ingredients. If you have usable fuel in gallons (or kilograms) and a burn rate in gallons per hour (or kilograms per hour), the time you can fly is simply usable fuel divided by the burn rate. That gives you endurance in hours. To get range, multiply that endurance by your speed. Using true airspeed (TAS) is standard for planning, so range is TAS × endurance. Wind changes how far you actually travel over the ground, so you adjust the result for headwinds or tailwinds; with no wind, TAS × endurance is the precise range. Other formulations don't fit because they mix units incorrectly (adding or subtracting fuel, speed, or time) or use operations that don't yield a meaningful duration or distance.

4. What is the purpose of crosswind correction factors in landing distance estimates?

A. Crosswind corrections apply only to climb performance.

B. Crosswind correction factors are applied to takeoff distance estimates.

C. Crosswind has no effect on landing distance.

D. Apply crosswind correction factors to landing distance estimates.

Crosswind adds a sideways component to the landing, which changes how the aircraft sits on the runway and how you manage control during the flare and touchdown. To stay aligned with the runway and maintain control, pilots use approaches like a crab or a wing-low sideslip, both of which can reduce braking effectiveness and increase the distance needed to decelerate and settle onto the runway. Because of this additional runway requirement under crosswind conditions, performance data include crosswind correction factors to adjust landing distance estimates so they remain conservative and safe. This reflects how crosswind affects the actual distance required to land, not just climbs or takeoff, and not as if there were no effect.

5. Which statement about wind direction and takeoff distance is correct?

A. Headwinds reduce the takeoff distance required to clear an obstacle

B. Headwinds increase the takeoff distance required

C. Crosswinds are the only factor affecting takeoff distance

D. Wind has no effect on takeoff distance

Wind direction changes takeoff distance because performance is defined by the speed of the airplane through the air (airspeed), not how fast it is moving over the ground. A headwind means the air is moving toward the aircraft from ahead, so for a given airspeed the aircraft covers less ground while accelerating. In other words, to reach the necessary takeoff airspeed, the ground distance you must travel is shorter when there's a headwind. That's why headwinds reduce the runway distance required to lift off and clear an obstacle. Tailwinds do the opposite, while crosswinds mainly affect alignment and control rather than the primary distance required. Wind having no effect is incorrect.

SAMPLE

6. Which input is explicitly included when calculating the takeoff distance to clear an obstacle?

A. Obstacle height and geometry

B. Aircraft color

C. Cabin pressure

D. Passenger count

When figuring out how far you must travel to clear an obstacle on takeoff, the key input is the obstacle's height and geometry. Knowing how tall the obstacle is and how it sits relative to your takeoff path sets the required climb profile and the distance you must achieve to clear it. The other options don't directly determine the clearance distance: color has no aerodynamic effect, cabin pressure isn't a factor in this calculation, and passenger count mainly affects weight in a broader sense but isn't the specific input that defines how far you must travel to clear the obstacle.

7. What conclusion can be drawn if the maximum demonstrated crosswind component is exceeded during landing?

A. Landing will be successful

B. Maximum demonstrated crosswind component is not exceeded

C. Landing may be attempted but is risky

D. The maximum demonstrated crosswind component is exceeded

When evaluating the scenario of exceeding the maximum demonstrated crosswind component during landing, the conclusion that can be drawn is that this limit has indeed been surpassed. The maximum demonstrated crosswind component is defined as the maximum wind condition under which the aircraft has been tested and successfully flown to ensure safe handling characteristics during landing. Exceeding this component indicates that the aircraft is operating outside of the manufacturer's tested parameters, implying that the established performance and handling characteristics cannot be guaranteed. This could lead to challenges such as loss of control, difficulty in maintaining the desired flight path, or an increased risk of accidents during landing. The context behind the limits set by manufacturers is crucial; they are based on extensive testing to ensure safety and maintain performance throughout various flying conditions. Thus, if the maximum demonstrated crosswind component is exceeded, the focus should be on evaluating the risks involved rather than assuming a successful landing can occur. In contrast, options that present false reassurances regarding the landing being successful or suggest that the maximum component limit isn't exceeded do not take into account the real conditions affecting the aircraft's performance.

SAMPLE

8. Along which axis is the center of gravity of an aircraft computed?

A. Vertical axis

B. Transverse axis

C. Longitudinal axis

D. Horizontal axis

The center of gravity (CG) of an aircraft is primarily computed along the longitudinal axis. This axis runs from the nose of the aircraft to the tail and is crucial for determining the aircraft's balance and stability in flight. The location of the CG affects the aircraft's pitch and overall aerodynamic performance. When an aircraft is designed and operated, understanding the CG's position along the longitudinal axis helps in ensuring that the aircraft maintains controlled flight and can perform maneuvers effectively. If the CG is located too far forward or too far aft along this axis, it can lead to handling issues, increased drag, or even stall conditions. The vertical and transverse axes relate to the aircraft's yaw and roll stability, respectively, but they do not play a direct role in calculating the CG. The horizontal axis, while important for understanding the aircraft's climb and descent dynamics, is also not directly relevant to the computation of the CG in the context of stability and control along the specific longitudinal direction.

9. Which statement about wind effects on landing distance is correct?

A. Headwind increases landing distance

B. Tailwind decreases landing distance

C. Surface condition does not affect landing distance

D. Tailwind increases landing distance

Wind direction relative to the runway affects landing distance by changing the ground speed during the landing roll. With a headwind, the air is moving toward the aircraft, so for a given indicated airspeed the aircraft's speed over the ground is reduced, which shortens the distance needed to stop. A tailwind pushes the aircraft along the runway, increasing ground speed for the same indicated airspeed and thus lengthening the distance required to decelerate and come to a stop. So a tailwind increases landing distance. Surface conditions can also affect stopping distance through braking friction, but the wind-related effect here is about how tailwinds raise ground speed and extend the rollout distance.

10. How does deploying flaps influence takeoff distance and initial climb performance in light aircraft?

A. Flaps typically reduce takeoff speed and distance and may improve initial climb angle, but increase drag and reduce maximum climb rate and cruise speed

B. Flaps increase takeoff speed and distance

C. Flaps have no effect on takeoff performance

D. Flaps only affect landing

Deploying flaps increases wing camber, which raises the lift it can produce at lower speeds. That lets the airplane reach the needed lift for takeoff at a slower speed, so you can lift off sooner and reduce the ground roll—shorter takeoff distance. The additional lift at low speeds also means you can achieve a steeper initial climb angle right after liftoff, without stalling, because you're flying closer to the lift needed for that climb at a lower speed. But flaps add drag, so once airborne the extra drag works against you. That means the maximum climb rate drops and cruise speed is reduced compared to a clean, flapless configuration. In short, flaps help with a shorter takeoff and a potentially steeper initial climb, at the cost of higher drag and lower climb rate once you're established in climb.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://fiaaircraftperformance.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE