HSC-3 PLANE CAPTAIN PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://hsc3planecaptain.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. What is the first action to take when approaching an overheated tire?

A. Approach from the side of the aircraft

B. Approach from above the tire

C. Approach from fore or aft of the aircraft

D. Approach from behind the aircraft

2. What is the minimum size at which viscous dampers are considered ineffective?

A. 1 inch

B. 2 inches

C. Greater than 2 inches

D. 3 inches

3. What type of towbar is commonly used for aircraft movement?

A. 20 Albar

B. 22 Albar

C. 24 Albar

D. 26 Albar

4. Where are the electrical servos found on the aircraft?

A. At the cockpit

B. Tip of the dog house

C. Center fuselage

D. Under the main wings

5. What is the effect of exceeding the moderate wind restriction on tie down chains?

A. Chains may not hold properly

B. Chains will break

C. Aircraft can be moved

D. Chains will remain secure

SAMPLE

6. What is the maximum capacity for the MGB?

A. 5.5 Gallons

B. 6.5 Gallons

C. 7.5 Gallons

D. 8.5 Gallons

7. What should be immediately done when there is a wheel brake failure?

A. Notify the flight crew only

B. Evacuate the area of unnecessary personnel

C. Begin the cooling procedure

D. Initiate the maintenance check

8. Which crew member is responsible for the braking during aircraft movement?

A. Tow tractor driver

B. Brake rider

C. Safety observer

D. Wing walker

9. What is the main mount tire pressure limit for the H60S?

A. 100-110 PSI

B. 120-130 PSI

C. 130-140 PSI

D. 140-150 PSI

10. What is the wind restriction for tie down chains rated as moderate on the H60H?

A. 12 knots

B. 14 knots

C. 16 knots

D. 18 knots

SAMPLE

Answers

SAMPLE

1. C
2. C
3. C
4. B
5. A
6. C
7. B
8. B
9. C
10. B

SAMPLE

Explanations

SAMPLE

1. What is the first action to take when approaching an overheated tire?

A. Approach from the side of the aircraft

B. Approach from above the tire

C. Approach from fore or aft of the aircraft

D. Approach from behind the aircraft

When approaching an overheated tire, the best practice is to approach from fore or aft of the aircraft. This method is crucial for safety because it keeps you out of the potential line of failure if the tire were to blow out or rupture. By positioning yourself at the front or back of the aircraft, you reduce the risk of injury from any debris that might be expelled. This approach is also grounded in understanding the dynamics of tire failure; overheated tires can fail violently, and the safest angles to observe and manage that risk are from the ends of the aircraft rather than the sides or directly above. Approaching from the side, above, or directly behind may place you in a more dangerous position where a tire failure could be more directly harmful to your safety. Thus, approaching from fore or aft is the most responsible and precautionary measure when dealing with overheated tires.

2. What is the minimum size at which viscous dampers are considered ineffective?

A. 1 inch

B. 2 inches

C. Greater than 2 inches

D. 3 inches

Viscous dampers are typically used in engineering applications to absorb and dissipate energy, particularly in structures subjected to dynamic loads such as vibrations or seismic activities. The sizing of these dampers is crucial for their effectiveness. It is generally understood that when the size of the viscous dampers is less than or equal to 2 inches, their performance tends to diminish significantly. Once the size exceeds 2 inches, dampers become more effective because they can accommodate greater fluid flow, which enhances their ability to absorb energy and reduce vibrations. This threshold is based on principles of fluid dynamics and the physical characteristics of the damper's operation, which includes factors like the cross-sectional area through which the viscous fluid must flow. Thus, stating that viscous dampers become ineffective at sizes less than or equal to 2 inches provides a clear understanding of why the cutoff point is established at this size, leading to the conclusion that "greater than 2 inches" represents the effective threshold for damper design and application.

3. What type of towbar is commonly used for aircraft movement?

A. 20 Albar

B. 22 Albar

C. 24 Albar

D. 26 Albar

The commonly used towbar for aircraft movement in the context of HSC-3 operations is the 24 Albar. This specific type of towbar is designed to connect with various aircraft types, providing the rigidity and strength necessary for safe towing. Its dimensions and design allow for compatibility with a range of military and naval aircraft, making it versatile for field operations. The 24 Albar's robust construction ensures that it can withstand the stresses involved in moving aircraft on the ground, which is crucial for maintaining operational readiness and safety. Additionally, using the correct towbar is essential for preventing damage to both the aircraft and the towing vehicle. In contrast, the other types of albars mentioned may not meet the specific requirements or compatibility needed for the aircraft typically handled by HSC-3, thus making the 24 Albar the preferred choice in this scenario.

SAMPLE

4. Where are the electrical servos found on the aircraft?

A. At the cockpit

B. Tip of the dog house

C. Center fuselage

D. Under the main wings

The electrical servos are found at the tip of the dog house, which is an essential area for various flight control systems. The dog house typically refers to the structural and mechanical components that support the tail section of the aircraft. Placement at this location allows for optimal connection and control over the aircraft's aerodynamic surfaces, such as the ailerons, elevators, and rudder. This positioning is critical for the electrical servos as it helps them efficiently manage the flight control inputs and maintain the aircraft's stability and maneuverability during operations. In this context, accessing the servos at the dog house facilitates maintenance and troubleshooting, which is crucial for aircraft safety and performance. Other options do not accurately reflect the location of the electrical servos. The cockpit is primarily for pilot controls and flight instrumentation. The center fuselage usually houses other systems, and the area under the main wings is more concerned with structural supports and fuel systems rather than the electronic servos necessary for flight control. Thus, the correct identification of the electrical servos at the tip of the dog house ensures a proper understanding of aircraft systems and their locations.

5. What is the effect of exceeding the moderate wind restriction on tie down chains?

A. Chains may not hold properly

B. Chains will break

C. Aircraft can be moved

D. Chains will remain secure

Exceeding the moderate wind restriction can lead to the chains not holding properly. In windy conditions, the forces exerted on tie down chains can increase significantly, which may exceed the design capability of the chains and their connections to the aircraft. This improper holding can result from either the chains slipping or the aircraft moving against the restraints, leading to an inadequate hold on the aircraft. Understanding the limitations of tie down systems in relation to wind conditions is important for maintaining aircraft safety. Inadequate tie-down can create risks of damage not only to the aircraft itself but also to other items and personnel in the vicinity. The other choices do not accurately represent the safety concerns and mechanics involved in the failure of tie-down chains under excessive wind, as they either imply complete failure or incorrect conditions regarding aircraft movement.

6. What is the maximum capacity for the MGB?

A. 5.5 Gallons

B. 6.5 Gallons

C. 7.5 Gallons

D. 8.5 Gallons

The maximum capacity for the MGB, or Main Gearbox, is 7.5 gallons. This figure is essential for proper maintenance and operation of the aircraft, as it ensures that the gearbox is adequately lubricated and functioning efficiently. Keeping the gearbox filled to its maximum capacity can help prevent issues such as overheating and wear of internal components. In this context, knowing the correct capacity helps ensure that aircraft maintenance routines are adhered to, which is vital for safety and operational readiness. Therefore, understanding the importance of this capacity reinforces the critical nature of maintaining proper fluid levels in aircraft components.

SAMPLE

7. What should be immediately done when there is a wheel brake failure?

A. Notify the flight crew only

B. Evacuate the area of unnecessary personnel

C. Begin the cooling procedure

D. Initiate the maintenance check

When there is a wheel brake failure, the immediate action of evacuating the area of unnecessary personnel is crucial for ensuring safety. This response helps mitigate risks associated with any potential hazards that may arise from a malfunctioning braking system, such as the possibility of the aircraft rolling uncontrollably or even experiencing a fire if there are hot brakes involved. By clearing the area of non-essential personnel, you help protect individuals who might otherwise be at risk from the malfunctioning aircraft. This preventive measure establishes a safer environment and allows maintenance crew or emergency response teams to work effectively without distractions or additional risks to personnel safety. Taking such immediate steps ensures that the situation is managed effectively while enabling the necessary procedures to be executed without further complications. Other actions such as notifying the flight crew or initiating checks might be part of the overall response but are secondary to ensuring the immediate safety of those in the vicinity.

8. Which crew member is responsible for the braking during aircraft movement?

A. Tow tractor driver

B. Brake rider

C. Safety observer

D. Wing walker

The braking during aircraft movement is primarily the responsibility of the brake rider. The brake rider is a crew member who is positioned in the cockpit or in the vicinity of the aircraft, and their main duty is to monitor and control the brakes during taxiing or towing operations. This role is critical for ensuring that the aircraft can be stopped safely, which helps prevent accidents and maintain operational safety while the aircraft is being moved on the ground. The brake rider communicates with the tow tractor driver (if applicable) and other personnel involved in the movement to coordinate actions and ensure safe operations. Their awareness and quick response to any situation can be vital, especially in crowded or high-traffic areas of the flight line where precise control is needed. Other roles, such as the tow tractor driver, safety observer, and wing walker, have different responsibilities. The tow tractor driver operates the vehicle used for moving the aircraft, while the safety observer monitors the area for obstacles and hazards. The wing walker aids in guiding the aircraft, particularly during turns or tight spaces. However, the actual braking of the aircraft during movement falls to the brake rider, making them the key person responsible for controlling the aircraft's speed and stopping.

SAMPLE

9. What is the main mount tire pressure limit for the H60S?

A. 100-110 PSI

B. 120-130 PSI

C. 130-140 PSI

D. 140-150 PSI

The main mount tire pressure limit for the H60S is in the range of 130-140 PSI. This pressure range is crucial for maintaining the optimal performance and safety of the helicopter's landing gear. Proper tire pressure ensures that the tires can adequately support the weight of the aircraft during takeoff, landing, and taxiing operations. Having the correct tire pressure also helps prevent tire blowouts and enhances the overall handling characteristics of the helicopter, especially when maneuvering on the ground. It is important for the plane captain to regularly check and maintain tire pressure within this specified limit to ensure operational readiness and safety. The other ranges of tire pressure mentioned do not correspond to the H60S specifications, which could lead to unsafe operational conditions if adhered to.

10. What is the wind restriction for tie down chains rated as moderate on the H60H?

A. 12 knots

B. 14 knots

C. 16 knots

D. 18 knots

The wind restriction for tie down chains rated as moderate on the H60 helicopter is indeed 14 knots. This specification is important as it indicates the maximum wind speed at which the aircraft can be safely secured using tie down chains designated for moderate conditions. Exceeding this wind speed can compromise the effectiveness of the tie downs and pose a risk of the aircraft being moved or damaged by strong winds. The rating of tie down chains, including those classified as moderate, is critical for operational safety. It reflects the conditions under which the aircraft can remain securely grounded without the risk of structural or mechanical failure of the securing system. In practical terms, knowing this limit helps ground crews, plane captains, and maintenance personnel take necessary precautions during adverse weather conditions. When the wind speed approaches or exceeds this restriction, alternative securing methods or additional precautions may be warranted to ensure the aircraft remains safely tied down.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://hsc3planecaptain.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE