INSTRUMENT RATING – AEROPLANE (INRAT) PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://inrataeroplane.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. Which wings generally catch more ice per square inch?

A. Thicker wings

B. Thin wings

C. Both types catch the same

D. Wings with de-icing systems only

2. What is an initial step a pilot must take if they encounter fluctuating altitude indications during their approach?

A. Notify ATC immediately

B. Revert to standard weather minimums

C. Fly the approach to minimums

D. Engage autopilot if available

3. How many satellites are needed for a 3D position fix?

A. 3 Satellites

B. 4 Satellites

C. 5 Satellites

D. 6 Satellites

4. What effect does static blockage have during a descent?

A. Under-reads altitude

B. Over-reads altitude

C. No effect on altitude

D. Unpredictable altitude

5. What is the interception angle when established outbound on a 265-degree heading and intercepting a 240-degree radial?

A. 15 degrees

B. 20 degrees

C. 25 degrees

D. 30 degrees

SAMPLE

6. How can GPS Overlays be identified on a chart?

A. By the presence of the word CNAV

B. By the addition of GNSS after the NDB identifier

C. Through a different color coding system

D. By a unique symbol for GPS approaches

7. What is the speed limit below 3,000 feet AGL within 10 nautical miles of a controlled airport?

A. 150 KTS IAS

B. 200 KTS IAS

C. 250 KTS IAS

D. 300 KTS IAS

8. What is the valid ILS localizer coverage area within 10 nautical miles from the transmitter?

A. 25* either side

B. 30* either side

C. 35* either side

D. 40* either side

9. What is required for a pilot to report visual sighting during an approach?

A. Sighting the airport includes clouds

B. Identifying ground landmarks is sufficient

C. Confirming traffic sighting only

D. The pilot must see the airport or traffic as instructed

10. What are the types of charts issued for one GFA?

A. Clouds and Wx only

B. Clouds, Wx, and Turbulence only

C. Clouds, Wx, Icing, Turbulence, and FZLVL

D. Clouds and Icing only

SAMPLE

Answers

SAMPLE

1. B
2. A
3. B
4. B
5. D
6. B
7. B
8. C
9. D
10. C

SAMPLE

Explanations

SAMPLE

1. Which wings generally catch more ice per square inch?

A. Thicker wings

B. Thin wings

C. Both types catch the same

D. Wings with de-icing systems only

Thin wings generally catch more ice per square inch due to their design and aerodynamic properties. When ice accumulates on a wing's surface, it has a greater effect on thinner wings because they have less surface area and structure to redistribute the impact of the ice. The airflow around a thinner wing can also be more sensitive to changes in shape caused by ice accumulation, which can significantly affect lift and control. In addition, thin wings often operate at higher angles of attack relative to their thicker counterparts, which can exacerbate the effects of ice accumulation. As a result, weight distribution and aerodynamic resistance are more affected, making thin wings particularly susceptible to the adverse effects of ice, including stall characteristics and reduced performance. While thicker wings may accumulate ice as well, their architecture allows them to manage the aerodynamic impacts better, providing more lift even when ice is present. Thus, the design of thinner wings plays a crucial role in their susceptibility to ice accumulation per square inch, making them the correct choice in this context.

2. What is an initial step a pilot must take if they encounter fluctuating altitude indications during their approach?

A. Notify ATC immediately

B. Revert to standard weather minimums

C. Fly the approach to minimums

D. Engage autopilot if available

When a pilot encounters fluctuating altitude indications during an approach, the priority is to ensure safety and maintain situational awareness. Notifying Air Traffic Control (ATC) immediately is crucial because they can provide assistance, including radar guidance and alerting other aircraft in the vicinity. Effective communication with ATC allows for a coordinated and responsive approach, which is particularly important in fluctuating altitude scenarios where the pilot's own instruments may be unreliable. Reverting to standard weather minimums or flying the approach to minimums can be dangerous if the altitude readings are not accurate, as these actions depend on the pilot's understanding of reliable altitude measurements. Engaging the autopilot may not be advisable if the pilot doubts the accuracy of the altitude indications, as autopilot systems might also react to erroneous data. Thus, notifying ATC is a fundamental step in managing the situation safely and effectively. It helps ensure that the pilot is supported and can make informed decisions based on updated information from air traffic services.

SAMPLE

3. How many satellites are needed for a 3D position fix?

A. 3 Satellites

B. 4 Satellites

C. 5 Satellites

D. 6 Satellites

For a 3D position fix in Global Navigation Satellite System (GNSS) technology, a minimum of four satellites is required. This is essential for determining an exact position in three dimensions: latitude, longitude, and altitude. When signals are received from three satellites, the system can calculate a 2D fix (latitude and longitude) based on the intersection of their signals. However, to accurately establish the altitude (which gives you the third dimension), a fourth satellite is necessary. The reason for this is that GNSS systems operate based on trilateration, and having an additional satellite allows the system to resolve the position in space while also accounting for variations in signal travel times caused by factors such as atmospheric conditions and clock offsets in the satellite signals. Thus, utilizing four satellites enables the receiver to solve for both the three-dimensional coordinates and to synchronize the time effectively, which is crucial for accurate positioning.

4. What effect does static blockage have during a descent?

A. Under-reads altitude

B. Over-reads altitude

C. No effect on altitude

D. Unpredictable altitude

Static blockage occurs when the static port of an aircraft becomes obstructed, preventing accurate readings from altimeters and other pressure-driven instruments. When a static blockage happens during a descent, the static pressure is higher (as the external air pressure decreases with altitude) than what the aircraft's instruments are reading. This means that the altimeter, which measures altitude based on static pressure, will interpret this higher pressure incorrectly and indicate a higher altitude than the actual altitude. As the aircraft descends, the air pressure outside decreases more rapidly than the blocked static source can accurately reflect. As a result, the altimeter will show an altitude that is higher than the true altitude of the aircraft, causing an over-read of altitude. This incorrect indication can lead to dangerous situations, particularly during key phases of flight such as approaches and landings where precise altitude readings are critical for safe operation. Understanding this effect is crucial for pilots to recognize and mitigate the risks associated with static port malfunctions during flight.

SAMPLE

5. What is the interception angle when established outbound on a 265-degree heading and intercepting a 240-degree radial?

A. 15 degrees

B. 20 degrees

C. 25 degrees

D. 30 degrees

The interception angle is determined by the difference between the aircraft's outbound heading and the radial being intercepted. In this scenario, the aircraft is established outbound on a heading of 265 degrees while trying to intercept the 240-degree radial. To calculate the interception angle, you can find the difference between the two bearings. Since the aircraft is heading outbound on a 265-degree heading and the radial to be intercepted is at 240 degrees, the calculation is: 1. Determine the angle difference: 265 degrees (outbound heading) - 240 degrees (radial). 2. This gives a difference of 25 degrees. However, to ensure a proper interception, the angle needs to be adjusted based on whether the crossover point is to the right or left of the outbound heading. Since 240 degrees is to the left of 265 degrees on a conventional compass, you need to adjust further to find the appropriate interception angle, leading to a total angle calculation of 30 degrees when taking into account the right-hand turn and correction needed to intercept effectively. Therefore, a 30-degree intercept angle allows the aircraft to effectively turn towards the radial and establish a course correction to successfully intercept the 240-degree radial. This makes the final interception angle 30 degrees,

6. How can GPS Overlays be identified on a chart?

A. By the presence of the word CNAV

B. By the addition of GNSS after the NDB identifier

C. Through a different color coding system

D. By a unique symbol for GPS approaches

GPS Overlays on an approach chart are specifically identified by the addition of the GNSS designation after the NDB (Non-Directional Beacon) identifier. This notation indicates that the approach incorporates Global Navigation Satellite System (GNSS) technology, enabling pilots to use satellite-based navigation in conjunction with traditional navigation aids like NDBs. This is important for pilots as it denotes the capability to perform approach procedures with GPS guidance, emphasizing the integration of modern navigation systems into existing frameworks. While the other choices may include concepts related to navigation, they do not accurately represent how GPS Overlays are identified on charts. For example, the presence of the word CNAV typically refers to a type of route or air navigation but does not specifically relate to overlay identification. Similarly, different color coding systems might be used in navigation charts for various purposes, but they are not a definitive method for identifying GPS Overlays. Lastly, unique symbols for GPS approaches might exist, but the standardized GNSS indication following the NDB identifier is the specific convention used for clarity in recognizing GPS Overlays.

SAMPLE

7. What is the speed limit below 3,000 feet AGL within 10 nautical miles of a controlled airport?

A. 150 KTS IAS

B. 200 KTS IAS

C. 250 KTS IAS

D. 300 KTS IAS

The correct answer is based on the regulatory framework that governs airspace and vehicles operating in proximity to controlled airports. Under the Federal Aviation Regulations (FAR), the speed limit below 3,000 feet above ground level (AGL) within 10 nautical miles of a controlled airport is set at 200 knots indicated airspeed (IAS). This regulation is in place to ensure safe and orderly operations in high-traffic areas around airports. These limits help to maintain a manageable flow of incoming and outgoing aircraft, reducing the risk of mid-air collisions and enhancing the safety of both IFR and VFR operations in congested environments. The choice of 200 knots IAS is a specific measure taken by aviation authorities to balance operational needs with safety concerns. Understanding these regulations is crucial for pilots, as adherence not only promotes safety but also compliance with national and international aviation standards.

8. What is the valid ILS localizer coverage area within 10 nautical miles from the transmitter?

A. 25* either side

B. 30* either side

C. 35* either side

D. 40* either side

The valid Instrument Landing System (ILS) localizer coverage area is significant for ensuring that pilots can effectively utilize this system for precision approaches. The correct answer indicates that the localizer has a coverage area of 35 degrees either side of the runway centerline within a distance of 10 nautical miles from the transmitter. The ILS localizer operates by providing lateral guidance to pilots during the approach phase of flight, and the specified coverage angle ensures that aircraft can achieve the required lateral alignment with the runway. This 35-degree coverage on each side provides the necessary operational margin for pilots to intercept and track the localizer signal effectively, which is critical for safe landings in low visibility conditions. The degrees specified represent the angular width of the localizer signal that pilots will need to fly to remain on course. This allows for some deviation from the centerline while still ensuring that the aircraft is within the effective range to receive guidance. The reason why it's essential to have this specific angle defined is to standardize procedures across airports and ensure a uniform level of safety and reliability for approaches using ILS. A critical point to consider is the reason for the other angles not being correct. Coverage beyond 35 degrees, such as 40 degrees, could lead to increased confusion

SAMPLE

9. What is required for a pilot to report visual sighting during an approach?

A. Sighting the airport includes clouds

B. Identifying ground landmarks is sufficient

C. Confirming traffic sighting only

D. The pilot must see the airport or traffic as instructed

For a pilot to report a visual sighting during an approach, it is essential that the pilot sees the airport or traffic as specifically instructed by air traffic control or standard operating procedures. The primary purpose of requiring visual sightings is to ensure that the pilot is adequately situating themselves in relation to the airport environment, which is essential for a safe landing. This includes having a clear visual reference to the runway and other critical navigational aids, allowing the pilot to make informed decisions about the approach and landing. Simply identifying ground landmarks, confirming traffic sighting, or having a view that includes clouds does not meet the criteria necessary for a visual approach. Instead, having an explicit view of the airport or the relevant traffic is crucial for maintaining safety and situational awareness during the landing phase.

10. What are the types of charts issued for one GFA?

A. Clouds and Wx only

B. Clouds, Wx, and Turbulence only

C. Clouds, Wx, Icing, Turbulence, and FZLVL

D. Clouds and Icing only

The correct choice encompasses a comprehensive range of atmospheric conditions depicted on the Graphical Area Forecast (GFA). The GFA is designed to provide pilots with vital information on various weather phenomena that can impact flights. By including clouds, weather systems (Wx), icing potential, turbulence, and the freezing level (FZLVL), it offers a complete overview of the conditions that may affect aerodynamically significant parameters during flight operations. Clouds play a critical role in flight safety and operational planning, affecting visibility and the likelihood of turbulence or icing. Weather information indicates the presence of significant meteorological phenomena such as fronts, storms, and precipitation that could influence route selection and operational safety. Icing forecasts inform pilots of potential ice accumulation on aircraft surfaces, which can drastically impair performance and handling. Turbulence information helps pilots anticipate and prepare for potentially uncomfortable or hazardous flight conditions. The freezing level is crucial for understanding where temperatures drop to the freezing point, which directly relates to icing conditions. Therefore, the inclusion of all these elements in a single GFA ensures that pilots have access to consolidated, pertinent data to make informed decisions during their flights, making it the most comprehensive and useful option presented.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://inrataeroplane.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE