MACHINE DESIGN ELEMENTS BOARD PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://machinedesignelements.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. **What type of load commonly leads to the phenomenon of creep in materials?**

   A. Static load

   B. Cyclic load

   C. Dynamic load

   D. Fatigue load

2. **Which cam mechanism allows for acceleration during movement?**

   A. Uniform motion cam

   B. Decelerated cam

   C. Gravity cam

   D. Accelerated cam

3. **What tools are typically used in wood pattern making in a foundry shop?**

   A. Saws and chisels

   B. Band saw

   C. Knives and drills

   D. Drill machine

4. **What property does a material exhibit if it returns to its original shape after the load is removed?**

   A. It has high modulus of elasticity

   B. It does not follow Hooke's law

   C. It is plastic

   D. It is elastic

5. **In gear design, the angle often associated with the pressure angle is also known as?**

   A. Helix angle

   B. Angle of recess

   C. Angle of obliquity

   D. Arc of action

SAMPLE

6. The height of a tooth above the pitch circle is referred to as what?

A. Top root

B. Addendum

C. Land

D. Hunting tooth

7. In terms of cutting fluids, what is the relation between water and oil in a 4 to 80 ratio?

A. Four parts water to eighty parts oil

B. Four parts oil to eighty parts water

C. Four parts water to eighty parts emulsifier

D. Four parts emulsifier to eighty parts oil

8. What does the term "endurance limit" describe?

A. The maximum stress a material can withstand without failure

B. The stress level under which a material can endure cyclic loading indefinitely

C. The measure of a material's resilience to deformation

D. The limit of stress during elastic deformation

9. What is the term for the surface of the gear located between the fillets of adjacent teeth?

A. Bottom land

B. Flank

C. Topland

D. Flank of tooth

10. What is the minimum catwalk standard required for cleaning an engine in a power plant?

A. 24 in

B. 22 in

C. 23 in

D. 25 in

SAMPLE

Answers

SAMPLE

1. A
2. D
3. A
4. D
5. C
6. B
7. A
8. B
9. A
10. B

SAMPLE

Explanations

SAMPLE

1. What type of load commonly leads to the phenomenon of creep in materials?

A. Static load

B. Cyclic load

C. Dynamic load

D. Fatigue load

Creep is a time-dependent deformation that occurs in materials subjected to constant stress, typically at elevated temperatures. This phenomenon is particularly significant in materials that experience a static load, where the load remains consistent over a long period. Under static loading conditions, a material is subject to a continuous stress that can cause it to slowly deform while under load. The mechanisms behind creep involve the movement of dislocations (defects in the crystal structure) and the rearrangement of the material's microstructure, which can lead to permanent deformation over time. Creep is generally not associated with cyclic loads, dynamic loads, or fatigue loads, as these types of loads involve varying stress conditions and their effects are typically more related to fatigue failure or dynamic response behaviors rather than slow deformation over time. Therefore, when evaluating the options, static load is the type that is most directly linked to the onset of creep in materials.

2. Which cam mechanism allows for acceleration during movement?

A. Uniform motion cam

B. Decelerated cam

C. Gravity cam

D. Accelerated cam

The cam mechanism that allows for acceleration during movement is the accelerated cam. This type of cam is designed to facilitate a change in velocity as the follower moves along the contour of the cam profile. It enables the follower to gain speed progressively as it travels, which is particularly useful in applications where quick, smooth movements are desired, such as in automated machinery or timing mechanisms. The key characteristic of accelerated cams is their ability to vary the motion of the follower, providing both acceleration and deceleration. This is achieved through specific designs of the cam profile, which can create varying radii or slopes that dictate how quickly the follower moves in relation to the cam's rotation. This feature is essential for applications that require precise control over the timing and speed of movements. The other cam mechanisms have more limited functionalities. Uniform motion cams provide a constant speed of movement, resulting in no acceleration or deceleration. Decelerated cams may slow down the motion at certain points, which is the opposite of acceleration. Gravity cams depend primarily on gravitational force to dictate motion, rather than actively controlling the acceleration profile. Hence, the accelerated cam is the best option when acceleration during movement is required.

SAMPLE

3. What tools are typically used in wood pattern making in a foundry shop?

A. Saws and chisels

B. Band saw

C. Knives and drills

D. Drill machine

In wood pattern making for foundries, the primary tools needed are generally saws and chisels. Saws are essential for cutting the wood to the desired shape and size, allowing the creator to make rough cuts and develop the basic form of the pattern. Chisels are equally important as they enable finer shaping and detailing of the pattern, which can significantly enhance the quality of the mold created from the pattern. These tools together provide the versatility required in wood pattern making, allowing for both rough shaping and precise detailing. The combined use of saws for larger cuts and chisels for intricate work ensures that the pattern is accurate and meets the specifications for the casting process. Other options like band saws or drill machines can be helpful in certain contexts but are not the primary tools in traditional wood pattern making, which emphasizes manual skill and craftsmanship using saws and chisels.

4. What property does a material exhibit if it returns to its original shape after the load is removed?

A. It has high modulus of elasticity

B. It does not follow Hooke's law

C. It is plastic

D. It is elastic

The property that allows a material to return to its original shape after the load is removed is known as elasticity. When a material is elastic, it deforms under an applied load but returns to its original dimensions once that load is taken away. This behavior is typically described by Hooke's law, which states that the deformation (strain) of an elastic material is directly proportional to the applied load (stress) within the limits of proportionality. In contrast, materials that exhibit plastic behavior would undergo permanent deformation and would not return to their original shape after the load is removed. High modulus of elasticity relates to the stiffness of a material but does not explicitly define the ability to return to the original shape after loading. Similarly, stating that a material does not follow Hooke's law implies that it behaves in a non-elastic manner, further distancing it from returning to its original shape. Therefore, the definition of elasticity is key to understanding the answer, which highlights that the correct choice clearly identifies the material's ability to restore its original shape upon unloading.

SAMPLE

5. In gear design, the angle often associated with the pressure angle is also known as?

A. Helix angle

B. Angle of recess

C. Angle of obliquity

D. Arc of action

The pressure angle in gear design is an important parameter that describes the angle between the line of action (the line along which the forces between meshing gears are transmitted) and a line tangent to the pitch circles of the gears. This angle is critical as it directly affects the shape of the gear teeth, the amount of tooth contact, and the efficiency of power transmission. The term "angle of obliquity" refers specifically to this relationship in gear design. It indicates how the forces are transmitted between gears and can influence factors such as load capacity and wear. When gears are designed with a specific pressure angle, it also plays a role in determining the geometry of the teeth, including their thickness and the profile shape. While the other options refer to different aspects of gear design, they do not directly relate to the concept of the pressure angle. The helix angle pertains to helical gears and their tooth orientation; the angle of recess is not a standard term in this context; and the arc of action relates to the distance over which the teeth interact but does not describe the angle of force application like the angle of obliquity does. Therefore, associating the pressure angle with the angle of obliquity is crucial for understanding how gear systems

6. The height of a tooth above the pitch circle is referred to as what?

A. Top root

B. Addendum

C. Land

D. Hunting tooth

The height of a tooth above the pitch circle in gear design is termed the addendum. This is a critical parameter in the geometry of gears. The addendum is the radial distance from the pitch circle to the top of the tooth, providing insight into how much material is above the pitch circle that helps in transferring motion between meshing gears. Understanding the addendum is essential for calculating various aspects of gear performance, including tooth strength and load distribution. It plays a crucial role in defining the overall size and shape of the gear teeth, as well as ensuring that the teeth engage properly with the teeth of another gear without interference. In contrast, other terms related to gear teeth serve different purposes; for instance, the top root and land do not refer to the height above the pitch circle, and the hunting tooth concept is used in specialized contexts related to gear profile or design specifics and is not relevant to tooth height above the pitch circle.

SAMPLE

7. In terms of cutting fluids, what is the relation between water and oil in a 4 to 80 ratio?

A. Four parts water to eighty parts oil

B. Four parts oil to eighty parts water

C. Four parts water to eighty parts emulsifier

D. Four parts emulsifier to eighty parts oil

The statement that presents a ratio of 4 to 80 for water and oil indicates a composition where the first number represents parts of one fluid and the second number represents parts of another. In the context of cutting fluids, a 4 to 80 ratio specifically means that for every four parts of water, there are eighty parts of oil. This ratio is significant because it describes the concentration of water in the mixture, which can affect the cooling and lubricating properties of the cutting fluid used in machining operations. When water is mixed with oil in this way, it's common to create an emulsion, which helps to lubricate the cutting tool, reduce friction, and dissipate heat generated during cutting processes. The importance of the correct ratio is critical to ensure that the cutting fluid performs effectively and protects both the workpiece and the tool from damage. In this particular case, the other answer choices do not correctly reflect the specified ratio. Recognizing the precise proportions is essential in machine design and machining operations, as they influence not only the efficiency of the cutting process but also the longevity of tools and the quality of the finished product.

8. What does the term "endurance limit" describe?

A. The maximum stress a material can withstand without failure

B. The stress level under which a material can endure cyclic loading indefinitely

C. The measure of a material's resilience to deformation

D. The limit of stress during elastic deformation

The term "endurance limit" specifically refers to the stress level below which a material can theoretically endure an infinite number of loading cycles without failing. This concept is crucial in applications where materials are subjected to repeated or fluctuating stresses, such as in rotating shafts, beams, or structural components that experience cyclic loading. Understanding the endurance limit is important in fatigue analysis, where materials may not fail due to a single overload but can instead fail after many cycles at lower stress levels. The endurance limit offers engineers a guideline to design components that can withstand fatigue over their intended lifespan, promoting reliability and safety. While other options describe important material properties, they do not capture the specific definition of endurance limit related to cyclic loading. The maximum stress without failure and the limits during elastic deformation pertain more to different mechanisms of material failure rather than cyclic loading endurance. Resilience to deformation touches on material properties but doesn't directly address the endurance limit in the context of fatigue.

SAMPLE

9. What is the term for the surface of the gear located between the fillets of adjacent teeth?

A. Bottom land

B. Flank

C. Topland

D. Flank of tooth

The correct term for the surface of the gear located between the fillets of adjacent teeth is known as the flank. The flank of a gear tooth is the surface that makes contact with the mating gear tooth during operation, and it plays a crucial role in the transmission of torque and motion. The design of the flank influences the efficiency and performance of the gear system, as it affects the contact between teeth, the load distribution, and the wear characteristics. While options like bottom land, topland, and flank of tooth have specific definitions in gear design, they do not accurately describe the surface located between the fillets of adjacent teeth in the same manner as flank does. Understanding these terms is essential as they relate to the geometry and function of gears in machine design, and recognizing their differences helps in applying the right terminology during analysis and discussions.

10. What is the minimum catwalk standard required for cleaning an engine in a power plant?

A. 24 in

B. 22 in

C. 23 in

D. 25 in

The minimum catwalk standard of 22 inches is established for safe access and maintenance operations, including cleaning engines in power plants. This width ensures that personnel have adequate space to move freely while performing essential tasks, thus minimizing the risk of accidents or injuries. The requirement is based on ergonomic considerations as well as safety regulations that prioritize the welfare of workers handling potentially hazardous equipment. In power plants, workers often need to maneuver around engines and other machinery while carrying tools or cleaning equipment. The 22-inch width allows enough clearance for efficient movement without compromising safety or stability. This design can accommodate personal protective equipment, which may add bulk and restrict movement, making this standard particularly important. Choosing a width greater than this might not necessarily improve safety or functionality but could lead to unnecessary material costs and space constraints. Therefore, 22 inches is a well-justified minimum for ensuring that operational safety standards are met while enabling efficient maintenance practices.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://machinedesignelements.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE