MASSACHUSETTS PLUMBERS JOURNEYMAN PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://massachusettsplumbers.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1
Table of Contents 2
Introduction 3
How to Use This Guide 4
Questions 5
Answers 8
Explanations 10
Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. **According to the Massachusetts Plumbers Code, where should the fixture wastes be connected when installing two lavatories on a two inch horizontal waste branch?**

   A. The top of the branch

   B. At the end of the branch

   C. Into the center of the branch

   D. Into the side center of the branch

2. **When conducting a deflection test on hubless cast iron soil pipe, what is the minimum required deflection per lineal foot?**

   A. 1/2"

   B. 3/4"

   C. 1"

   D. 1 1/4"

3. **According to sizing requirements, what should be the cross-sectional area at the valve seat of vacuum relief valves?**

   A. Equal to the cold water supply size

   B. Two pipe sizes smaller than the cold water supply

   C. One pipe size smaller than the cold water supply

   D. Half the cold water supply size

4. **What is defined as discharge from any fixture, appliance, area, or appurtenance that does not contain human or animal waste matter suspended in a solution?**

   A. Air

   B. Liquid Waste

   C. Developed Length

   D. Trap Seal

5. **When the water service source to a building exceeds 80 P.S.I.G., what should be installed in the water main pipe?**

   A. A pressure release valve

   B. A pressure increasing valve

   C. A pressure gauge

   D. A pressure reducing valve

SAMPLE

6. How should all sumps and ejectors be protected against backflow and backpressure?

A. Backwater valve

B. Check valve

C. Pressure valve

D. Float valve

7. For vent terminal flashing, what is the minimum thickness of Sheet Lead required?

A. 2 pounds per square foot

B. 3 pounds per square foot

C. 4 pounds per square foot

D. 5 pounds per square foot

8. If there is reason to believe that a plumbing system has become defective, what action should be taken based on regulations?

A. Notify the building owner

B. Continue regular use

C. Subject it to test and inspection

D. Ignore the issue

9. In case of possible frost closure, what is the minimum diameter required for each vent extension through a roof?

A. One inch

B. Two inches

C. Three inches

D. Four inches

10. How much larger should every drainage pipe in a combination waste-and-vent system be compared to the size required?

A. Same size as required

B. One size larger

C. Two sizes larger

D. Three sizes larger

SAMPLE

Answers

SAMPLE

1. D
2. C
3. C
4. B
5. D
6. B
7. B
8. C
9. C
10. C

SAMPLE

Explanations

SAMPLE

1. According to the Massachusetts Plumbers Code, where should the fixture wastes be connected when installing two lavatories on a two inch horizontal waste branch?

A. The top of the branch

B. At the end of the branch

C. Into the center of the branch

D. Into the side center of the branch

The correct approach for connecting the fixture wastes when installing two lavatories on a two-inch horizontal waste branch is to connect them into the side center of the branch. This method ensures that the waste from both fixtures is appropriately directed into the waste line, allowing for effective drainage while minimizing the risk of clogs or backflow. By connecting into the side center of the branch, you also allow for better alignment with the flow of waste and ventilation, which is crucial for maintaining proper drainage. This positioning aids in ensuring that both lavatories can operate concurrently without causing a negative impact on the drainage system's overall performance. Additionally, this configuration adheres to the principles outlined in the Massachusetts Plumbers Code, which emphasizes effective waste management and plumbing system efficiency.

2. When conducting a deflection test on hubless cast iron soil pipe, what is the minimum required deflection per lineal foot?

A. 1/2"

B. 3/4"

C. 1"

D. 1 1/4"

The correct deflection amount for hubless cast iron soil pipe during a deflection test is indeed measured at a minimum of 1 inch per lineal foot. This standard is crucial to ensure the pipe can accommodate typical loads and stresses that it may encounter during its lifespan without significant deformation or compromise to the plumbing system's integrity. Deflection testing is an important quality control measure that helps to ensure that the installed pipe remains functional under pressure and during environmental changes. A minimum of 1 inch of deflection indicates that the pipe has sufficient flexibility to handle both thermal expansion and contraction as well as potential ground movement without risk of failure or leakages. Other options reflect lesser amounts of deflection, which would not meet the necessary performance criteria for this type of plumbing installation. Proper adherence to these standards ensures longevity and reliability in plumbing systems.

SAMPLE

3. According to sizing requirements, what should be the cross-sectional area at the valve seat of vacuum relief valves?

A. Equal to the cold water supply size

B. Two pipe sizes smaller than the cold water supply

C. One pipe size smaller than the cold water supply

D. Half the cold water supply size

The correct answer is that the cross-sectional area at the valve seat of vacuum relief valves should be one pipe size smaller than the cold water supply. This sizing is critical because it allows for adequate airflow while maintaining enough pressure differential to function effectively. This configuration helps prevent potential damage due to vacuum conditions that can occur within piping systems, especially in heated water applications or when cooling occurs rapidly. Having the valve seat sized appropriately—not exceeding one pipe size smaller than the cold water supply—ensures that the valve can act rapidly to relieve any vacuum conditions without being excessively restrictive. This contributes to overall system efficiency and safety. Other choices suggest sizing that might be too small or too large for effective operation, which could compromise the functionality of the vacuum relief valve. Ensuring a proper size is essential to both the operational efficiency and the safety of plumbing systems.

4. What is defined as discharge from any fixture, appliance, area, or appurtenance that does not contain human or animal waste matter suspended in a solution?

A. Air

B. Liquid Waste

C. Developed Length

D. Trap Seal

The correct answer is liquid waste. Liquid waste refers to any discharge coming from fixtures, appliances, or areas that does not include human or animal waste. This encompasses a wide range of non-hazardous discharges such as water from sinks, showers, or appliances that handle wash water, making it a significant category in plumbing definitions and practices. Other options do not fit this definition. Air represents a gas, while developed length pertains to the physical layout of piping in a system. Trap seal refers to the body of water maintained in a trap to prevent sewer gases from entering the building, which is unrelated to the discharge characteristics defined in the question. Thus, focusing on the nature of liquid waste provides a clear understanding of what qualifies as discharge without harmful waste.

SAMPLE

5. When the water service source to a building exceeds 80 P.S.I.G., what should be installed in the water main pipe?

A. A pressure release valve

B. A pressure increasing valve

C. A pressure gauge

D. A pressure reducing valve

When the water service source to a building exceeds 80 P.S.I.G., a pressure reducing valve should be installed in the water main pipe. This is because a pressure reducing valve is designed to reduce the high water pressure to a safer and more manageable level within the building's plumbing system. Without a pressure reducing valve in place, excessively high water pressure can potentially damage fixtures, pipes, and appliances, leading to costly repairs and water wastage. Options A, B, and C are incorrect: A. A pressure release valve is not typically used to address high water pressure concerns. Its primary function is to release excess pressure in a system to prevent damage or failure. B. A pressure increasing valve is used to boost water pressure when it is too low, not to reduce high water pressure. C. While a pressure gauge is important for monitoring water pressure, simply installing a pressure gauge will not address the issue of excessively high water pressure; a pressure reducing valve is needed for that purpose.

6. How should all sumps and ejectors be protected against backflow and backpressure?

A. Backwater valve

B. Check valve

C. Pressure valve

D. Float valve

The correct choice is a check valve, which plays a crucial role in preventing backflow and backpressure in systems that include sump pumps and ejectors. A check valve allows fluid to flow in one direction only, ensuring that when the pump is not active, wastewater or water does not flow back into the sump or ejector pit. This is particularly important in drainage systems where the risk of backflow can lead to flooding or contamination, thereby protecting the integrity of the plumbing system and maintaining health and safety standards. Other options such as a backwater valve can also control backflow but are primarily designed for use in sewer systems to prevent sewage from entering a building. Pressure valves serve different functions typically related to regulating system pressure rather than preventing backflow, while float valves are commonly used for maintaining water levels in tanks rather than being a mechanism for backflow prevention. Therefore, the check valve is the most appropriate and effective choice for protecting sumps and ejectors against backflow and backpressure.

SAMPLE

7. For vent terminal flashing, what is the minimum thickness of Sheet Lead required?

A. 2 pounds per square foot

B. 3 pounds per square foot

C. 4 pounds per square foot

D. 5 pounds per square foot

The minimum thickness of sheet lead required for vent terminal flashing is indeed 3 pounds per square foot. This specification is set to ensure that the material is durable enough to withstand environmental stressors such as wind, rain, and snow while providing a reliable barrier to prevent water intrusion around vent terminals. Using lead flashing of this specified thickness helps maintain the integrity of the vent system and contributes to the longevity of both the vent and the surrounding structure. Thicker variations might offer additional robustness but are not the minimum requirement as per building codes and industry standards. Therefore, choosing 3 pounds per square foot strikes the right balance between performance and compliance with safety regulations.

8. If there is reason to believe that a plumbing system has become defective, what action should be taken based on regulations?

A. Notify the building owner

B. Continue regular use

C. Subject it to test and inspection

D. Ignore the issue

When there is suspicion that a plumbing system has become defective, the regulations emphasize the importance of subjecting the system to testing and inspection. This action is crucial because it allows for an accurate assessment of the plumbing system's condition to determine the extent of the defect and the necessary remedial steps. Testing and inspection can uncover hidden issues such as leaks, obstructions, or code violations that could lead to further complications if not addressed promptly. Taking proactive measures to test and inspect helps ensure the safety, functionality, and compliance of the plumbing system with local codes and regulations. This practice not only protects the building occupants but also mitigates potential damage to property and health risks associated with defective plumbing. Regular assessment is a key component in maintaining the integrity of plumbing systems.

9. In case of possible frost closure, what is the minimum diameter required for each vent extension through a roof?

A. One inch

B. Two inches

C. Three inches

D. Four inches

The correct minimum diameter for each vent extension through a roof, in the context of preventing frost closure, is indeed three inches. This specification is essential for ensuring that the vent has adequate airflow and is less susceptible to blockages caused by ice or snow accumulation, which are common issues in colder climates like Massachusetts. While smaller diameters may technically function as vents, they can lead to increased risks during freezing weather conditions. A three-inch diameter provides a greater volume for air to pass through, which helps to maintain proper ventilation and prevents pressure buildup in the plumbing system. This is crucial for the safe and effective operation of the plumbing system, as it allows gases and odors to exit the home without obstruction. In contrast, smaller diameters can drastically diminish the venting capability and increase the likelihood of causing frost closure. Hence, choosing a minimum diameter of three inches aligns with best practices for plumbing venting in environments prone to freezing temperatures.

SAMPLE

10. How much larger should every drainage pipe in a combination waste-and-vent system be compared to the size required?

A. Same size as required

B. One size larger

C. Two sizes larger

D. Three sizes larger

In a combination waste-and-vent system, every drainage pipe should be sized larger than what is typically required to ensure proper function and to mitigate potential issues such as clogs or insufficient drainage. The correct approach is to make those pipes two sizes larger than the standard requirement. This is necessary because the combination of drainage and venting functions can lead to increased flow and pressure conditions that need to be accommodated. A larger pipe size allows for improved flow capacity, reduces friction losses, and enhances overall system efficiency and reliability. The importance of this practice is particularly relevant in systems where fixtures are connected to a single drainage line, as this can create unique challenges in maintaining adequate drainage while also providing adequate venting. Thus, ensuring the pipes are sized appropriately is crucial for the system's performance.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://massachusettsplumbers.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE