MASSACHUSETTS STATE ELEVATOR PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://mastateelevator.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. What is the required illumination in the elevator pit?

A. 10 foot candles

B. 5 foot candles

C. 15 foot candles

D. 1 foot candle

2. What color and size is the lettering for "Fire" on a fire sign?

A. 1/8" in red

B. 1/4" in red

C. 3/8" in red

D. 1/2" in red

3. When is firefighter service required for elevators?

A. Only for elevators installed after July 24, 1987

B. For all elevators having a travel of 50 feet or more

C. If installed before July 24, 1987, on all elevators with 70 or more feet of travel

D. Only for freight elevators

4. How long should oil buffers take to return to their fully extended position after being released?

A. 60 seconds

B. 75 seconds

C. 90 seconds

D. 120 seconds

5. What is the minimum stroke for spring buffers for elevators running at speeds of 151 to 200 FPM?

A. 1 inch

B. 1.5 inches

C. 2.5 inches

D. 4 inches

SAMPLE

6. What is the minimum headroom requirement for an elevator hoisting machine?

A. 6 feet

B. 7 feet

C. 8 feet

D. 9 feet

7. What is the size of lettering required for freight elevators?

A. 1/2"

B. 1"

C. 2"

D. 4"

8. How high should the top of the counterweight guard be above the floor of the pit?

A. 10 inches

B. 12 inches

C. 7 feet

D. 5 inches

9. What happens to the elevator when it is set to recall mode?

A. The elevator goes to the loading dock

B. The elevator returns to a specific floor based on programmed settings

C. The elevator shuts down completely

D. The elevator can only be operated manually

10. How frequently should hydraulic hoses be changed?

A. Every 3 years

B. Every 6 years

C. Every 10 years

D. Every 12 years

SAMPLE

Answers

SAMPLE

1. B
2. C
3. C
4. C
5. D
6. B
7. B
8. B
9. B
10. B

SAMPLE

Explanations

SAMPLE

1. What is the required illumination in the elevator pit?

A. 10 foot candles

B. 5 foot candles

C. 15 foot candles

D. 1 foot candle

The required illumination in the elevator pit is 5 foot candles. This standard is established to ensure safety and functionality during maintenance or emergencies. Adequate lighting is crucial in these areas to allow personnel to clearly see and perform their duties without the risk of accidents or overlooking potential hazards. Illuminating an elevator pit to this level improves visibility of equipment, maintenance tools, and any warning signs that might be present in the pit, thus enhancing the overall safety of the work environment. Lower levels of illumination, such as 1 foot candle, would be insufficient for safe operation and inspection, while higher levels like 10 or 15 foot candles may not be necessary and could lead to glare or other visibility issues in an already confined space.

2. What color and size is the lettering for "Fire" on a fire sign?

A. 1/8" in red

B. 1/4" in red

C. 3/8" in red

D. 1/2" in red

The correct specification for the lettering of "Fire" on a fire sign is 3/8 inches in red. This size and color are mandated to ensure clear visibility and strong emphasis, which are crucial for safety in emergency situations. The red color is universally associated with fire or danger, making it immediately recognizable to individuals needing guidance in urgent scenarios. Using a 3/8 inch size ensures that the sign can be seen from a reasonable distance, allowing people to quickly identify the location of fire-related equipment or exits. This specific attention to detail plays a vital role in fire safety protocols, where clear signage can be the difference in emergency response efficacy. While other options propose different sizes, only the 3/8 inch standard strikes the ideal balance between visibility and compliance with safety regulations.

3. When is firefighter service required for elevators?

A. Only for elevators installed after July 24, 1987

B. For all elevators having a travel of 50 feet or more

C. If installed before July 24, 1987, on all elevators with 70 or more feet of travel

D. Only for freight elevators

Firefighter service is an important feature for elevators in buildings to enhance safety during emergencies, particularly regarding fire situations. The requirement for firefighter service is based on the elevator's travel distance and the date of installation, which is crucial for complying with safety regulations. When considering elevators that were installed before July 24, 1987, the requirement is that those with a travel distance of 70 feet or more must have firefighter service. This service allows firefighters to take control of the elevator system during an emergency, ensuring that they can safely transport individuals and equipment without interference or risks associated with normal operation. Elevators installed after the specified date have different regulations that may vary, illustrating that the laws have evolved to enhance safety features over time. However, the specific regulation that dictates the necessity of firefighter service for older installations directly relates to their travel height, making the answer centered on the requirement for those specific conditions. This focus on the combination of installation date and travel distance is how the correct answer is determined, ensuring compliance with the relevant fire safety protocols.

SAMPLE

4. How long should oil buffers take to return to their fully extended position after being released?

A. 60 seconds

B. 75 seconds

C. 90 seconds

D. 120 seconds

Oil buffers are critical components in elevator systems, designed to absorb the impact when the elevator car reaches the end of its travel. The specified time for these buffers to return to their fully extended position is indicative of their performance and operational safety. The standard time for oil buffers to return to their fully extended position after being compressed is typically 90 seconds. This duration allows for the controlled retraction of the buffer to ensure smooth operation and prevent mechanical failure. It also accounts for the viscosity of the oil used in the buffers, ensuring it has adequate time to flow back into the buffer chamber and return to a ready state for the next impact scenario. In contrast, shorter or longer durations could suggest malfunctioning components or improper conditions that could compromise the safety and reliability of the elevator system. Therefore, the 90-second requirement aligns with safety standards and operational guidelines vital for the effective functioning of elevators.

5. What is the minimum stroke for spring buffers for elevators running at speeds of 151 to 200 FPM?

A. 1 inch

B. 1.5 inches

C. 2.5 inches

D. 4 inches

The minimum stroke for spring buffers for elevators operating at speeds of 151 to 200 feet per minute is specifically stipulated by industry standards and regulations to ensure sufficient deceleration and safety during operation. At these higher speeds, there is a greater potential for impact forces, and the buffers need to be effective in absorbing the energy generated during a downward landing or in case of an emergency stop. A stroke of 4 inches for spring buffers provides the necessary cushioning and absorption required to adequately protect the elevator car, its occupants, and the machinery from damage in the event of a malfunction or other issues. This stroke length is designed to allow sufficient compression of the buffer spring to effectively mitigate impact forces, ensuring safe operation. In practice, carefully following these guidelines is crucial for maintaining safety standards within elevator systems, particularly as speeds increase and the forces at play become more significant. This regulation is based on extensive safety testing and engineering principles, making it a critical aspect of elevator design and maintenance.

SAMPLE

6. What is the minimum headroom requirement for an elevator hoisting machine?

A. 6 feet

B. 7 feet

C. 8 feet

D. 9 feet

The minimum headroom requirement for an elevator hoisting machine is set to ensure both safety and operational efficiency. A requirement of 7 feet is established to provide enough vertical space for maintenance personnel to work safely without the risk of injury from overhead equipment. This height allows technicians to perform necessary inspections, repairs, and emergency operations without the hazard of head injury, which could occur if the space is too low. In many building codes and standards, requirements for headroom serve to maintain an industry-standard that includes considerations for both the equipment and the people who maintain it. The 7-foot requirement strikes a balance between functional usage of space in machinery rooms and ensuring sufficient safety margins. This height also accommodates various types of hoisting machinery and related components commonly used in elevator systems. Considering this context, the alternative options do not align with the established standards for headroom. Lower height options would increase the risk of safety hazards during maintenance or emergency situations, while higher requirements, although potentially safer, may not be necessary and could lead to inefficient use of space in elevator machinery installations.

7. What is the size of lettering required for freight elevators?

A. 1/2"

B. 1"

C. 2"

D. 4"

The size of lettering required for freight elevators is specified as 1 inch. This standard ensures that the markings are easily visible and readable, which is crucial for safety and operational efficiency. In freight elevators, clear signage helps operators and users identify controls, capacities, and safety warnings from a distance, particularly in busy environments where visibility may be compromised. Using 1-inch lettering strikes a balance between clarity and practicality. Larger sizes, such as 2 inches or 4 inches, may be excessive for typical operational needs and can clutter the design, while smaller sizes, like 1/2 inch, may not provide sufficient visibility, especially in low-light or busy conditions. Ensuring that the lettering is adequately sized is a key component of safety regulations, thereby facilitating prompt recognition and compliance with operational protocols in freight elevator usage.

SAMPLE

8. How high should the top of the counterweight guard be above the floor of the pit?

A. 10 inches

B. 12 inches

C. 7 feet

D. 5 inches

The height of the counterweight guard above the floor of the pit is specified to be 12 inches for safety and compliance reasons. This height is critical in providing a proper barrier that prevents any potential contact with the counterweights and ensures that personnel working in or around the elevator pit are safeguarded from injury. In elevator systems, the counterweights help balance the weight of the elevator car, contributing to the smooth operation of the system. If the guard were to be any lower than 12 inches, it could allow objects, tools, or even personnel's limbs to inadvertently come too close to the counterweight mechanism, which operates under tension and can pose a significant risk. Therefore, maintaining this specific height is essential for adhering to safety regulations and standards established for elevator systems. Understanding safety regulations is crucial for elevator practitioners, as they are designed to protect both the maintenance personnel and the users of the elevator system, and this particular measurement is a clear example of those safety standards in action.

9. What happens to the elevator when it is set to recall mode?

A. The elevator goes to the loading dock

B. The elevator returns to a specific floor based on programmed settings

C. The elevator shuts down completely

D. The elevator can only be operated manually

When an elevator is set to recall mode, it is programmed to return to a specific floor, such as a designated landing for emergencies or maintenance. This floor is typically predetermined and is often the main entry level or a supervised area to ensure safety during non-operational hours or emergency situations. The recall function is essential for facilitating the safe and efficient management of elevator traffic, especially in commercial buildings where control over elevator placement can enhance safety protocols. The other scenarios outlined do not accurately represent the function of recall mode. For instance, sending the elevator to the loading dock is not a standard function associated with recall mode, as it focuses on returning to an assigned floor instead. Additionally, shutting down completely or requiring manual operation are not intrinsic to recall mode, which is designed for automated return rather than complete cessation of function.

10. How frequently should hydraulic hoses be changed?

A. Every 3 years

B. Every 6 years

C. Every 10 years

D. Every 12 years

Hydraulic hoses should typically be changed every 6 years as part of a routine maintenance schedule. This timeframe helps to ensure that the hoses maintain their integrity, efficiency, and safety within the hydraulic system. Over time, hydraulic hoses can experience wear and tear from exposure to heat, pressure, and the hydraulic fluid itself, which can lead to degradation. Changing them every 6 years helps to prevent potential failures that could result in hydraulic leaks or system malfunctions, ensuring that the elevator operates safely and reliably. While some other schedules for changing hoses may exist, they often do not take into account the specific conditions and demands that hydraulic systems may face in various environments, which is why the 6-year recommendation stands out as a balanced approach to maintenance. This timeframe aligns with best practices in the industry and is supported by manufacturers' guidelines, ensuring compliance with safety regulations and performance standards.

EXAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://mastateelevator.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE