
NATIONAL COMMISSION FOR THE CERTIFICATION OF CRANE OPERATORS (NCCCO) CORE PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://ncccocore.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. When the boom angle falls between the capacities listed in the load chart, which capacity should be used?

A. Higher boom angle gross capacity

B. Lower boom angle gross capacity

C. Average of the capacities

D. Maximum rated capacity

2. When the load radius falls between capacities listed in the load chart, which capacity should be used?

A. Gross capacity for the shorter radius

B. Gross capacity for the longer radius

C. Net capacity based on safety factors

D. Averages of the capacities listed

3. An audible outrigger/stabilizer alarm indicates

A. The outriggers/stabilizers are in motion

B. The crane is lifting a load

C. The hydraulic system is malfunctioning

D. The boom is fully extended

4. What does the D/d ratio represent in rigging?

A. The total load weight divided by the body diameter of the sling

B. The diameter of the load divided by the body diameter of the sling

C. The angle of the sling divided by the total weight

D. The length of the sling relative to the lifting height

5. The lifting capacities listed in the load chart are based on what assumption?

A. High wind conditions

B. Under ideal conditions

C. Dynamic loading

D. Variable conditions

SAMPLE

6. A properly set up crane should have what feature regarding its tires?

A. The tires should be on the supporting surface

B. The tires should be partially on the supporting surface

C. The tires should be off the supporting surface

D. The tires should be completely submerged

7. Who is allowed to give a crane operator the stop signal?

A. Only the lift director

B. Anyone

C. Only certified operators

D. Only site supervisors

8. Which type of hook is prohibited when personnel are present in the fall zone?

A. Swivel hook

B. Sorting hook

C. Safety hook

D. Clevis hook

9. Which unsafe condition could result when a wedge socket is attached directly to a load hook, using 6x19?

A. Increased weight capacity

B. Spinning load

C. Stability

D. Improved load distribution

10. Which of the following is a temporary alternative measure when a boom length indicator malfunctions?

A. Mark the boom with measured marks to calculate boom length

B. Use a secondary boom length indicator

C. Secure the boom and stop operation

D. Adjust the boom according to the load weight

SAMPLE

Answers

SAMPLE

1. B
2. B
3. A
4. B
5. B
6. C
7. B
8. B
9. B
10. A

SAMPLE

Explanations

SAMPLE

1. When the boom angle falls between the capacities listed in the load chart, which capacity should be used?

A. Higher boom angle gross capacity

B. Lower boom angle gross capacity

C. Average of the capacities

D. Maximum rated capacity

When determining the appropriate capacity to use when the boom angle falls between those listed in the load chart, it is essential to prioritize safety by selecting a conservative approach. Choosing the lower boom angle gross capacity is the correct method, as it ensures that the load remains safely within the limits of the crane's stability and operational capability. Using the lower capacity takes into account the fact that as the boom angle increases, the lifting capacity typically decreases due to the changes in leverage and the center of gravity. By opting for this more conservative figure, operators can minimize the risk of overloading the crane, which could lead to potential accidents or mechanical failures. This method aligns with safety protocols and best practices in crane operation, emphasizing the importance of erring on the side of caution to protect both personnel and equipment.

2. When the load radius falls between capacities listed in the load chart, which capacity should be used?

A. Gross capacity for the shorter radius

B. Gross capacity for the longer radius

C. Net capacity based on safety factors

D. Averages of the capacities listed

When determining the capacity of a crane when the load radius falls between the capacities listed in the load chart, it is essential to use the gross capacity for the longer radius. This approach is based on the principle that as the load radius increases, the crane's lifting capacity typically decreases. The load chart reflects this relationship, indicating that for any given crane configuration, the capacity at a shorter radius will always be higher than that at a longer radius. Using the gross capacity for the longer radius ensures that the crane operates within safe limits, prevents possible overloads, and complies with performance specifications outlined in the load chart. This practice helps protect both the integrity of the crane and the safety of personnel working on site. By selecting the capacity corresponding to the longer radius, operators minimize risks associated with lifting loads at a distance that could jeopardize the crane's stability or performance. It is vital for crane operators to adhere strictly to these guidelines to maintain operational safety and efficiency.

SAMPLE

3. An audible outrigger/stabilizer alarm indicates

A. The outriggers/stabilizers are in motion

B. The crane is lifting a load

C. The hydraulic system is malfunctioning

D. The boom is fully extended

An audible outrigger/stabilizer alarm serves a critical safety function by alerting personnel that the outriggers or stabilizers are in motion. This warning system is essential because it informs operators and nearby workers that the crane's stabilizing mechanisms are being adjusted, which may pose a risk if individuals are not aware and do not maintain a safe distance. When the alarm sounds, it ensures those in proximity understand the crane is undergoing changes in its stance or stability, which is crucial for safe operation. This is particularly important in busy work environments where visibility might be limited or where multiple operations are occurring simultaneously. The other options do not accurately represent the primary function of the audible alarm. The alarm specifically pertains to the movement of the outriggers or stabilizers and does not indicate lifting operations, hydraulic issues, or the boom's position. Understanding this function reinforces the importance of safety protocols and maintaining awareness of equipment operations on site.

4. What does the D/d ratio represent in rigging?

A. The total load weight divided by the body diameter of the sling

B. The diameter of the load divided by the body diameter of the sling

C. The angle of the sling divided by the total weight

D. The length of the sling relative to the lifting height

The D/d ratio is a critical concept in rigging that represents the relationship between the diameter of the load (D) and the body diameter of the sling (d). This ratio is essential in determining the appropriate use of slings, as it helps evaluate how the geometry of the load and the sling's design affects the sling's strength and potential for wear and damage. When the diameter of the load increases relative to the body diameter of the sling, it can lead to a situation where greater forces are exerted on the sling due to the bending and contact stresses. A higher D/d ratio indicates that the load is proportionally larger compared to the sling's diameter, which can increase the risk of failure or excessive wear on the sling over time. Understanding the D/d ratio allows rigging professionals to make informed decisions about equipment selection and the safe limits for lifting operations, enhancing overall safety on the job site.

5. The lifting capacities listed in the load chart are based on what assumption?

A. High wind conditions

B. Under ideal conditions

C. Dynamic loading

D. Variable conditions

The lifting capacities listed in the load chart are based on the assumption of ideal conditions. This means that the weights and load placements are calculated without external influences such as wind, slope of the ground, or other factors that could affect the crane's performance. Ideal conditions assume a crane is operating on stable ground, with no additional forces acting on the load being lifted, and the crane is properly setup without any load moment indicators engaged. This provides a baseline for operators to understand the maximum capacities the crane can safely manage under perfect circumstances. It's essential for operators to assess real-time conditions and adjustments may be necessary when actual conditions deviate from these ideal assumptions in order to maintain safety and prevent accidents.

SAMPLE

6. A properly set up crane should have what feature regarding its tires?

A. The tires should be on the supporting surface

B. The tires should be partially on the supporting surface

C. The tires should be off the supporting surface

D. The tires should be completely submerged

A properly set up crane requires that its tires be off the supporting surface, as this is essential for ensuring stability and safety during operation. When the tires are off the ground, it indicates that the crane is likely properly positioned, on outriggers or pads, which helps distribute the weight of the crane and its load more evenly. This setup minimizes the risk of tipping or instability, allowing for a safer work environment. Ensuring that the crane is on a firm and stable ground without reliance on tires for support is crucial in preventing accidents or equipment failure. It reinforces the proper functioning of the crane's hydraulic system and ensures that the center of gravity remains low, further enhancing safety. In contrast, other options suggest either partial support by tires, which could lead to instability, or complete submersion, which could cause improper handling of the crane and potential hazards. Understanding these principles is vital for safe crane operation and compliance with safety regulations.

7. Who is allowed to give a crane operator the stop signal?

A. Only the lift director

B. Anyone

C. Only certified operators

D. Only site supervisors

The correct answer is that anyone is allowed to give a crane operator the stop signal. This principle is rooted in the fundamental importance of safety on construction sites. In emergency situations, it is critical for the operation of cranes to be halted immediately to prevent accidents, injuries, or potential fatalities. Therefore, allowing anyone on site to issue a stop signal ensures that all personnel, regardless of their specific role or certification, can intervene if they perceive a dangerous situation. While the other roles listed, such as lift directors, certified operators, and site supervisors, often have designated responsibilities and authority regarding crane operations, the ability to stop operations is given to all individuals. This approach fosters a safer environment by empowering all workers to participate in the safety protocols of crane operation and to act without delay if they observe unsafe conditions. The collective responsibility for safety ensures that the operators are not solely dependent on a specific person for critical signals, thus enhancing the overall safety culture on the job site.

SAMPLE

8. Which type of hook is prohibited when personnel are present in the fall zone?

A. Swivel hook

B. Sorting hook

C. Safety hook

D. Clevis hook

The type of hook that is prohibited when personnel are present in the fall zone is the sorting hook. This prohibition is based on safety considerations, as sorting hooks can allow for uncontrolled load movement and position shifting, which poses significant risks to personnel in close proximity to the lifting operation. Sorting hooks often have a design that does not provide a secure capturing mechanism for a load, which may result in the load being dropped or swinging unexpectedly. When personnel are in the fall zone, any falling objects or shifting loads can lead to serious injuries or fatalities. As a result, adherence to stringent safety practices includes avoiding the use of hooks that lack sufficient safety features in areas where personnel may be located. In contrast, swivel hooks, safety hooks, and clevis hooks may have designs that incorporate features to prevent load disengagement or to allow for more controlled handling of loads, thus making them safer options in contexts where personnel are present. These hooks tend to provide more reliability in terms of securement and load management, decreasing the likelihood of accidents in the fall zone.

9. Which unsafe condition could result when a wedge socket is attached directly to a load hook, using 6x19?

A. Increased weight capacity

B. Spinning load

C. Stability

D. Improved load distribution

When a wedge socket is attached directly to a load hook, using a 6x19 construction wire rope, it can create an unsafe condition known as a spinning load. This occurs because the connection may not provide a stable configuration for the load, leading to an imbalance during the lift. When a load spins, it poses two significant risks: first, it can cause the load to swing unpredictably, increasing the potential for accidents and injuries; second, spinning loads complicate the control over the load's movement, making it difficult for the operator to maintain visibility and situational awareness. Proper rigging techniques and connections are essential for ensuring the stability and safety of the load during operation, and using a wedge socket directly with a load hook does not help in achieving this stability.

SAMPLE

10. Which of the following is a temporary alternative measure when a boom length indicator malfunctions?

A. Mark the boom with measured marks to calculate boom length

B. Use a secondary boom length indicator

C. Secure the boom and stop operation

D. Adjust the boom according to the load weight

When dealing with a malfunctioning boom length indicator, marking the boom with measured marks to calculate the boom length serves as a practical temporary workaround. This method allows the operator to have a reference for the boom's lengths based on predetermined measurements, thereby enabling them to still operate the crane while adhering to safety protocols that involve understanding the boom's extent. This approach is particularly useful because it allows for continued operation without compromising safety, assuming the operator is proficient in the crane's capacities and can accurately use the markings to avoid exceeding limits. It ensures that the operator can visually reference the boom's position concerning safe operation parameters. While other solutions may seem viable, they generally involve either stopping operation, which is not as flexible as marking the boom, or relying on alternative systems that may not be available or tested to be reliable under the current circumstances. Marking the boom provides an immediate and effective solution to assess the boom length for the tasks at hand, facilitating the ongoing work process while addressing the malfunction.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://ncccocore.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE