

NATIONAL HIGHWAY INSTITUTE (NHI) SAFETY INSPECTION OF IN- SERVICE BRIDGES FINAL ASSESSMENT PRACTICE EXAM (SAMPLE) STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

**VISIT US ONLINE FOR
THE FULL VERSION STUDY GUIDE**

<https://nhi-buildings.examzify.com>



Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright	1
Table of Contents	2
Introduction	3
How to Use This Guide	4
Questions	5
Answers	8
Explanations	10
Next Steps	15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

Questions

SAMPLE

- 1. Which method uses magnetic fields and iron particles to reveal surface flaws?**
 - A. Dye Penetrant
 - B. Magnetic Particle Testing
 - C. Ultrasonic
 - D. Eddy Current

- 2. A moisture meter determines what in timber members?**
 - A. Determines moisture content in timber members
 - B. Determines internal cracking in concrete
 - C. Measures thickness of asphalt
 - D. Detects decay in timber

- 3. What is the purpose of the approach guardrail ends?**
 - A. Traffic-friendly systems that minimize barrier end threat as hazardous object within roadside area
 - B. They are not used
 - C. They are decorative
 - D. They limit access to the roadway

- 4. Roller and rocker bearings are characterized by:**
 - A. A curved bearing surface allows for longitudinal movement and rotation.
 - B. They require constant lubrication.
 - C. They provide a fixed, non-movable joint.
 - D. They are composed of sliding metal plates.

- 5. Solid shaft pier is used when:**
 - A. When a very large mass is needed and a limited number of load points are required.
 - B. When there is ample clearance and many load points.
 - C. For light loads only.
 - D. When large mass is needed and a limited number of load points are required.

- 6. The impact echo test is primarily used for which purpose in concrete structures?**
- A. Detecting delaminations in asphalt
 - B. Detecting moisture content in timber
 - C. Flaw detection in concrete
 - D. Assessing surface roughness of concrete
- 7. Clacking refers to which sound?**
- A. The sound of delaminated concrete
 - B. The sound of cracking concrete
 - C. The sound of pings
 - D. The sound of water intrusion
- 8. Which statement about steel box-girder or box-beam bridges is true?**
- A. they lack any stiffeners
 - B. they rely solely on external frames
 - C. a floor system between girders
 - D. internal stiffeners are present
- 9. In arch bridges, what does the spandrel refer to?**
- A. Area between the arch and the deck
 - B. The decorative element above the arch
 - C. The abutment housing
 - D. The reinforcement in arch ribs
- 10. In adjacent box beam layouts, which statement is true regarding their arrangement?**
- A. Placed side by side, no space between
 - B. Span 400 to 600 feet
 - C. Top flange may serve as deck
 - D. Always uses shear keys

Answers

SAMPLE

1. B
2. A
3. A
4. A
5. D
6. C
7. A
8. D
9. D
10. A

SAMPLE

Explanations

SAMPLE

1. Which method uses magnetic fields and iron particles to reveal surface flaws?

- A. Dye Penetrant
- B. Magnetic Particle Testing**
- C. Ultrasonic
- D. Eddy Current

This method relies on magnetic fields to reveal surface flaws by drawing iron particles to discontinuities. In Magnetic Particle Testing, the part is magnetized, and fine iron particles are applied (dry or in a liquid). If there is a flaw near or at the surface, the magnetic field leaks at that defect, attracting the particles and forming a visible indication that marks the flaw's location and shape. This makes it particularly effective for ferromagnetic materials like steel and iron, where cracks that intersect the surface produce clear, inspectable patterns. Surface preparation matters: the surface should be clean and properly oriented for magnetization (longitudinal, transverse, or circumferential) to maximize leakage at flaws. This method is distinct from dye penetrant testing (which uses a dye that seeps into surface cracks), ultrasonic testing (which uses high-frequency sound waves to detect internal flaws), and eddy current testing (which detects flaws via induced currents and magnetic fields without iron particles).

2. A moisture meter determines what in timber members?

- A. Determines moisture content in timber members**
- B. Determines internal cracking in concrete
- C. Measures thickness of asphalt
- D. Detects decay in timber

Moisture content in timber is the amount of water contained in the wood, usually expressed as a percentage of the dry weight. A moisture meter is used to measure this value in timber members. Knowing the moisture content is crucial because wood properties depend on moisture: higher moisture generally reduces strength and stiffness, causes swelling and dimensional changes, and can influence the likelihood of decay. The meter works by sensing how the wood's electrical properties change with water content—some meters rely on electrical resistance, others on capacitance or impedance—and then converts that signal to a moisture percentage based on calibration for wood species. This reading helps inspectors determine if the timber is within acceptable moisture limits for service and whether conditions are favorable for degradation processes. It doesn't measure internal cracking in concrete, which requires different nondestructive tests or visual/repair assessments; it doesn't measure the thickness of asphalt, which is done with other tools; and while high moisture can indicate potential decay risk, the meter's job is to read moisture content, not to detect decay itself.

3. What is the purpose of the approach guardrail ends?

- A. Traffic-friendly systems that minimize barrier end threat as hazardous object within roadside area
- B. They are not used
- C. They are decorative
- D. They limit access to the roadway

Guardrail ends can become a serious hazard if they terminate abruptly or are sharp to a passing vehicle. The purpose of the approach end treatment is to make the end of the barrier behave in a safer, more forgiving way for traffic. By shaping or energy absorbing the end, and often tapering it, the end is less likely to snag, penetrate, or impart a sudden, high severity impact to a vehicle that hits it. This keeps the barrier's protective role while reducing the risk of the end becoming a hazardous object in the roadside area. So the best choice describes a system that is traffic-friendly and minimizes the barrier end threat. It isn't decorative, it's used, and it isn't about merely limiting access to the roadway.

4. Roller and rocker bearings are characterized by:

- A. A curved bearing surface allows for longitudinal movement and rotation.
- B. They require constant lubrication.
- C. They provide a fixed, non-movable joint.
- D. They are composed of sliding metal plates.

The main idea is how these bearings handle movement at the bridge support. Roller and rocker bearings are designed with curved contact surfaces or rolling elements so the joint can accommodate movement along the span while still allowing some rotation. As the bridge expands, contracts, or shifts under load, the weight rolls or slides along that curved surface, letting the girder move longitudinally and rotate a bit without binding. This reduces friction and keeps the structure stable through temperature changes and other loads. Constant lubrication is important for maintenance, but it isn't what defines roller and rocker bearings. They aren't fixed, non-movable joints, which would prevent necessary movement. And they aren't simply sliding metal plates—the curved/rolling interface is the key characteristic that enables both longitudinal movement and rotation.

5. Solid shaft pier is used when:

- A. When a very large mass is needed and a limited number of load points are required.
- B. When there is ample clearance and many load points.
- C. For light loads only.
- D. When large mass is needed and a limited number of load points are required.

Solid shaft piers are chosen when the structure must carry a large mass through a small number of load transfer points. The dense, solid cross-section provides maximum strength and stiffness, so the pier can resist high compressive forces with minimal deflection and bending at the bearing points. This makes it the most reliable option when loads are heavy and you don't have the flexibility to distribute them across many supports. If there's plenty of clearance and many load points, or if the loads are light, other configurations that use less material or distribute loads differently are more appropriate, so a solid shaft isn't needed in those cases.

6. The impact echo test is primarily used for which purpose in concrete structures?

- A. Detecting delaminations in asphalt
- B. Detecting moisture content in timber
- C. Flaw detection in concrete
- D. Assessing surface roughness of concrete

Impact echo is a nondestructive way to probe the interior of concrete by sending a short mechanical pulse into the member and listening for echoes that come back from internal boundaries. The time it takes for these reflections to return tells you how deep the reflecting surface is, so you can locate and estimate the size of flaws like delaminations, voids, or other discontinuities within the concrete. This makes it especially useful for assessing the integrity of concrete elements such as bridge decks where hidden flaws could affect performance. It's not intended for detecting moisture in timber, moisture or delaminations in asphalt, or measuring surface roughness of concrete.

7. Clacking refers to which sound?

- A. The sound of delaminated concrete
- B. The sound of cracking concrete
- C. The sound of pings
- D. The sound of water intrusion

Clacking is the sharp, hollow sound produced when concrete has delaminated and the separated layers move or strike against each other under traffic. When the deck loses bonding between layers, a vehicle load can cause the upper and lower portions to rub or separate, creating that distinctive clack. This sound signals bond failure and potential deterioration beneath the surface, which is important to flag for further inspection. It's different from a cracking noise (which is a crack forming), a ping (a metallic ring or tinkle), or sounds from water intrusion (dripping or hissing).

8. Which statement about steel box-girder or box-beam bridges is true?

- A. they lack any stiffeners
- B. they rely solely on external frames
- C. a floor system between girders
- D. internal stiffeners are present

In a steel box-girder or box-beam bridge, the main load-carrying member is a hollow box made from thin walls. Those thin webs are prone to buckling under compression, so internal stiffeners are placed inside the box at intervals to keep the webs from buckling, to transfer shear between the top and bottom flanges, and to maintain the overall shape and rigidity of the cross-section as the bridge bends and twists. This internal reinforcement is a key feature that enables the box girder to carry bending and shear loads effectively over long spans. External frames alone don't provide all the stiffness, and a floor system between girders is part of the deck support rather than evidence of no stiffeners. Hence, internal stiffeners being present is the correct description.

9. In arch bridges, what does the spandrel refer to?

- A. Area between the arch and the deck
- B. The decorative element above the arch
- C. The abutment housing
- D. The reinforcement in arch ribs**

In arch bridges, the spandrel is the space between the curve of the arch and the deck. That area is typically a wall or panel (spandrel wall) that carries the deck's load down to the arch ribs, helping transfer forces from the deck to the arch. It's not a decorative piece, nor the abutment housing, nor the reinforcement within the arch ribs. Its role is to connect the deck to the arch and distribute vertical loads into the arch structure.

10. In adjacent box beam layouts, which statement is true regarding their arrangement?

- A. Placed side by side, no space between**
- B. Span 400 to 600 feet
- C. Top flange may serve as deck
- D. Always uses shear keys

Adjacent box beam layouts are built by placing multiple box girders directly next to each other with no gap between them. This butt-jointed arrangement makes the group behave as a single, wider cross-section, improving stiffness and distributing loads more evenly across the deck. With no space separating the girders, the top flanges align to present a continuous bearing surface, which can simplify deck construction and create a uniformly supported deck over the entire width. The other statements aren't universal features of adjacent box beam layouts: spans can vary by project, the deck may or may not be formed by the top flange depending on the design, and shear keys at joints are not a mandatory requirement in every case.

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

<https://nhi-buildings.examzify.com>

We wish you the very best on your exam journey. You've got this!

SAMPLE