NATIONAL HOME INSPECTOR EXAMINATION (NHIE) PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://natlhomeinspector.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. What is a common cause of water hammer in plumbing systems?

A. A lack of air chambers

B. Faulty shutoff valves

C. Loose piping

D. Low static water pressure

2. What types of soil conditions can affect a home's foundation?

A. Clay, loam, and sandy soil

B. Expansive clay, sandy soil, and poorly drained soils

C. Silty soil, gravel, and compacted earth

D. Rocks, clay, and peat soil

3. What is a common issue associated with older plumbing systems?

A. High-pressure water output

B. Corrosion and build-up in pipes, leading to reduced water flow

C. Excessive water waste

D. Modern fixture compatibility

4. What is required of an inspector when examining the structural system?

A. Inspect only the visible components in the attic and crawl space

B. Specify method of structural repairs to the system

C. Report all structural deficiencies observed

D. Determine the cause and origin of the damage

5. How can a home inspector evaluate the condition of an air conditioning system?

A. By checking landscaping proximity to the unit

B. By examining the unit's operation and airflow

C. By reviewing the owner's recent utility bills

D. By measuring indoor humidity levels

6. What are the key components of roof inspection?

A. Roof covering, flashing, drainage, and ventilation

B. Gutters, shingles, insulation, and trim

C. Decking, support beams, and ridge boards

D. Surface materials, aesthetic appeal, and color

SAMPLE

7. What is the most common contributing factor to masonry retaining wall movement?

A. Corbelled construction.

B. Hydrostatic pressure.

C. Poorly mortared joints.

D. Too many tiebacks.

8. What types of heating systems might be found in a home?

A. Geothermal, solar panels, and air conditioning

B. Forced air, radiators, electric baseboard, and heat pumps

C. Wood stoves, fireplaces, and gas heaters

D. Central air, electric ovens, and heat strips

9. In the context of dryer exhaust and gas-fired water heater vent termination, what should a home inspector recommend?

A. the dryer exhaust should be at least 5 feet from the gas vent termination.

B. the dryer exhaust backdraft damper should be repaired or replaced.

C. the gas vent is improperly terminated and should be relocated.

D. the client monitor the gas vent for indications of deterioration.

10. What is an example of a safety hazard that a home inspector should identify?

A. Exposed electrical wires or ungrounded outlets

B. Old appliances that are still operational

C. Decorative lighting arrangements

D. Well-maintained landscaping

SAMPLE

Answers

SAMPLE

1. A
2. B
3. B
4. C
5. B
6. A
7. B
8. B
9. C
10. A

SAMPLE

Explanations

SAMPLE

1. What is a common cause of water hammer in plumbing systems?

A. A lack of air chambers

B. Faulty shutoff valves

C. Loose piping

D. Low static water pressure

Water hammer is a phenomenon that occurs when a fluid in motion is suddenly stopped or forced to change direction, causing a pressure surge in the plumbing system. A common cause of this issue is the lack of air chambers in the plumbing. Air chambers serve as a cushion or buffer that absorbs the shock of the sudden stop, significantly reducing the pressure surges that can lead to water hammer. In the absence of these air chambers, there's no mechanism to absorb the kinetic energy of the moving water when a valve is abruptly closed. As a result, the pressure can spike, leading to the characteristic banging noise associated with water hammer. The other options may contribute to plumbing issues but do not directly address the cause of water hammer in the same way that the absence of air chambers does. For instance, while faulty shutoff valves or low static water pressure can create other complications within a plumbing system, they do not specifically relate to the sudden pressure changes that characterize water hammer. Loose piping may create rattling sounds, but it's not the fundamental reason for the pressure surge inherent in water hammer scenarios.

2. What types of soil conditions can affect a home's foundation?

A. Clay, loam, and sandy soil

B. Expansive clay, sandy soil, and poorly drained soils

C. Silty soil, gravel, and compacted earth

D. Rocks, clay, and peat soil

The impact of soil conditions on a home's foundation is critical for assessing stability and longevity. Expansive clay is particularly known for its ability to swell when wet and shrink when dry, which can lead to significant changes in volume and pressure on a foundation. Sandy soil, while generally allowing for good drainage, can also cause issues if it is poorly compacted; it can shift and settle over time, leading to foundation movement. Poorly drained soils hold water, increasing hydrostatic pressure against foundation walls, which can also lead to structural damage. Other soil types, while they may play a role in certain contexts, do not have the same level of direct impact on foundation stability as expansive clay and poorly drained soils do. Silty soils can retain moisture but do not exhibit the same expansive properties, while sandy soils, depending on drainage and compaction, might not exert enough pressure to be significantly harmful. Therefore, the combination of expansive clay, sandy soil, and poorly drained soils clearly outlines the key types that can create problematic conditions for a foundation.

SAMPLE

3. What is a common issue associated with older plumbing systems?

A. High-pressure water output

B. Corrosion and build-up in pipes, leading to reduced water flow

C. Excessive water waste

D. Modern fixture compatibility

Corrosion and build-up in pipes is a prevalent issue in older plumbing systems. Over time, the materials used in older pipes, such as galvanized steel or iron, can deteriorate due to chemical reactions with water, leading to rust formation and mineral deposits. This corrosion not only weakens the structural integrity of the pipes but also results in reduced water flow rates. The accumulation of build-up can create blockages, which may further exacerbate the issue and lead to increased pressure on the plumbing system. As a result, homeowners with older plumbing systems often experience variable water pressure and diminished performance in fixtures. In contrast, high-pressure water output is typically a characteristic of newer plumbing systems that are designed to handle the demands of modern households. Excessive water waste may arise due to leaks, but this is not inherently a problem tied to the age of the plumbing system alone. Lastly, modern fixture compatibility may be an issue with older systems that don't meet current standards, but it is not a common physical issue affecting the plumbing's performance like corrosion and build-up.

4. What is required of an inspector when examining the structural system?

A. Inspect only the visible components in the attic and crawl space

B. Specify method of structural repairs to the system

C. Report all structural deficiencies observed

D. Determine the cause and origin of the damage

When examining the structural system, an inspector must report all structural deficiencies observed. This requirement is crucial for maintaining safety and ensuring that potential issues are documented so that appropriate actions can be taken for repairs or further evaluation. The focus on reporting deficiencies allows homeowners, buyers, and other stakeholders to understand the condition of the structure and make informed decisions based on the inspector's findings. The other choices involve actions that go beyond the scope of a typical home inspection. For instance, inspecting only the visible components limits the thoroughness of the evaluation, as hiding places in attics or crawl spaces can conceal significant issues. Specifying the method of structural repairs requires expertise in construction that may not fall within the inspector's responsibilities, as the inspector's role is to identify issues rather than prescribe specific solutions. Determining the cause and origin of damage generally necessitates a more detailed analysis and may involve the expertise of specialists, making it outside the typical duties of a home inspector. The primary duty remains to identify and report any deficiencies that are visible and relevant to the structural integrity of the building.

SAMPLE

5. How can a home inspector evaluate the condition of an air conditioning system?

A. By checking landscaping proximity to the unit

B. By examining the unit's operation and airflow

C. By reviewing the owner's recent utility bills

D. By measuring indoor humidity levels

Evaluating the condition of an air conditioning system primarily involves examining the unit's operation and airflow. This process includes checking whether the unit powers on, runs smoothly, and effectively cools the air being circulated throughout the home. Inspectors assess the unit's cooling performance by measuring the temperature differential between the air entering and exiting the system to ensure it is functioning within industry standards. Additionally, inspecting for proper airflow direction and any obstructions can help identify potential issues affecting efficiency, such as blocked ducts or filters. While other choices may provide some related information, they do not directly assess the operational effectiveness of the air conditioning system itself. For instance, checking landscaping proximity to the unit can be relevant for maintenance considerations but doesn't evaluate functionality. Reviewing utility bills offers insight into energy consumption which may indicate performance issues but does not provide a direct evaluation of the system's working condition. Measuring indoor humidity levels can give clues about system performance in terms of dehumidification but does not specifically evaluate the air conditioning unit's operational state. Therefore, the most comprehensive and practical method to evaluate an air conditioning system is through a thorough examination of its operation and airflow.

6. What are the key components of roof inspection?

A. Roof covering, flashing, drainage, and ventilation

B. Gutters, shingles, insulation, and trim

C. Decking, support beams, and ridge boards

D. Surface materials, aesthetic appeal, and color

The key components of a roof inspection primarily include roof covering, flashing, drainage, and ventilation. Roof covering refers to the material that protects the structure from weather, such as shingles, tiles, or metal. Flashing is essential as it prevents water from penetrating the roof at joints and transitions, which is critical for maintaining the integrity of the roof. Drainage involves the assessment of the roof's ability to direct water away from the building, often involving the inspection of gutters and downspouts. Lastly, ventilation is important to regulate temperature and moisture levels in the attic, preventing problems like mold growth and structural damage. These components work together to ensure that the roof functions effectively and remains in good condition. In contrast, other options contain components that are either less relevant to the roof inspection process, such as aesthetic aspects and trim work or do not encompass critical roof functionality in the same way. While gutters are important, they are part of the drainage system rather than a standalone component. Similarly, shingles fit under roof covering but do not encompass the complete scope of what needs to be inspected.

SAMPLE

7. What is the most common contributing factor to masonry retaining wall movement?

A. Corbelled construction.

B. Hydrostatic pressure.

C. Poorly mortared joints.

D. Too many tiebacks.

Hydrostatic pressure is considered the most common contributing factor to masonry retaining wall movement. This pressure builds up in the soil behind the wall, especially in areas where there is poor drainage or heavy rainfall. When water saturates the soil, it increases the weight of the retained material, leading to increased lateral forces on the wall. If the wall is not designed to withstand these forces or if proper drainage systems are not in place to alleviate the pressure, it can cause the wall to move, bow, tilt, or even fail entirely. Inadequate drainage can exacerbate the problem, as water pooling behind the wall increases hydrostatic pressure significantly. This principle is crucial in the design and maintenance of retaining walls, as engineers must consider soil saturation and proper drainage solutions to prevent movement. While the other factors mentioned may contribute to wall stability in certain contexts, hydrostatic pressure is the primary reason for movement in masonry retaining walls.

8. What types of heating systems might be found in a home?

A. Geothermal, solar panels, and air conditioning

B. Forced air, radiators, electric baseboard, and heat pumps

C. Wood stoves, fireplaces, and gas heaters

D. Central air, electric ovens, and heat strips

The correct answer identifies various types of heating systems typically found in homes, providing a comprehensive overview of conventional and effective heating methods. Forced air systems are among the most prevalent in residential heating; they use a network of ducts to distribute warmed air throughout the home. Radiators, which can be part of either a hot water or steam-heating system, effectively utilize heated water to warm spaces. Electric baseboard heaters offer localized heating through electric resistance, making them ideal for individual rooms. Heat pumps are versatile, functioning both as heating and cooling systems by transferring heat between the house and the outside environment, proving efficient year-round. The other responses include options that either do not primarily function as heating systems or are not typically classified as heating systems in a residential context. For instance, while geothermal and solar panels can contribute to a home's heating, they are generally part of broader energy systems rather than standalone heating systems. Wood stoves and fireplaces are indeed heat sources, but they lack the systematic and widespread application seen in central heating systems. Lastly, central air and electric ovens are not classified as heating systems; central air provides cooling, while electric ovens are intended solely for cooking. This distinction underscores the emphasis on the heating function of each system listed in the correct choice

SAMPLE

9. In the context of dryer exhaust and gas-fired water heater vent termination, what should a home inspector recommend?

A. the dryer exhaust should be at least 5 feet from the gas vent termination.

B. the dryer exhaust backdraft damper should be repaired or replaced.

C. the gas vent is improperly terminated and should be relocated.

D. the client monitor the gas vent for indications of deterioration.

When evaluating venting, the safety issue is keeping combustion appliance venting separate from other exhaust paths so gases don't backdraft into living areas. A gas-fired water heater vents combustion products outdoors, while a dryer exhaust pushes lint-laden air outward. If the gas vent termination is improperly placed relative to the dryer exhaust, wind or pressure differences can cause backdrafting or cross-drafting, potentially sending combustion gases into the home or causing the dryer to affect the gas vent's performance. Relocating the gas vent termination to a location with appropriate clearance from the dryer exhaust ensures each vent operates independently and reduces the risk of backdrafting, entry of combustion gases, and lint/moisture issues near the vent. This directly addresses the hazardous condition shown. The other options don't tackle that risk as directly: a fixed distance requirement may not apply universally or address the immediate termination placement; repairing a dryer backdraft damper? That might help in some cases but doesn't fix the improper gas vent termination; monitoring deterioration is reactive and unrelated to the current safety concern.

10. What is an example of a safety hazard that a home inspector should identify?

A. Exposed electrical wires or ungrounded outlets

B. Old appliances that are still operational

C. Decorative lighting arrangements

D. Well-maintained landscaping

Exposed electrical wires or ungrounded outlets represent a significant safety hazard that a home inspector should identify during their inspection. These conditions can create a risk of electric shock or fire hazards, making them critical issues for both the safety of the occupants and the integrity of the home. Identifying such hazards is vital for ensuring that the electrical system in the home complies with safety standards, which ultimately protects the health and well-being of the residents. In contrast, old appliances that are still operational do not necessarily pose an immediate safety hazard, as their functionality can vary widely based on maintenance and condition. Decorative lighting arrangements may contribute to aesthetic appeal but are not inherently dangerous unless improperly installed. Well-maintained landscaping is generally not a safety hazard and is instead considered a positive aspect of a home's exterior. Thus, recognizing exposed electrical wires or ungrounded outlets as hazards is crucial for a home inspector's role in safeguarding homeowners.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://natlhomeinspector.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE