NCCR BOILERMAKER PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://nccrboilermaker.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1
Table of Contents 2
Introduction 3
How to Use This Guide 4
Questions 5
Answers 8
Explanations 10
Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. What is the most commonly used light lifting device in boiler shop operations?

A. Hydraulic jack

B. Chain pulley

C. Come-along

D. Chain hoist

2. Who is responsible for rigging when a big control valve is pulled?

A. Crane operator and rigger

B. Maintenance supervisor

C. Ground crew

D. Project engineer

3. What type of valve is used on a hydro test tree to maintain test pressure after the hydro has reached its required pressure?

A. Gate

B. Ball

C. Check

D. Globe

4. Where is the convection section of a heater located?

A. Below the radiant tubes

B. Above the radiant tubes

C. Adjacent to the feed

D. Inside the combustion chamber

5. A worker is installing a blind in a flange for blanking off the gas line to the burners. The appropriate gasket cannot be found. What should the worker do?

A. Proceed with the blind anyway

B. Use a substitute gasket

C. Do not continue installing the blind until the proper gasket can be found

D. Delay but continue with other work

SAMPLE

6. How many people can tie off to a vertical line?

A. One

B. Two

C. Three

D. Four

7. All of the following would be reasons for rejecting a synthetic sling for rigging except?

A. An identification tag on the wrong side of the sling

B. Visible damage in the fiber

C. Knots or broken stitches

D. Excessive loads beyond rating

8. The maximum fillet size on a tube-to-drum seal weld should be?

A. 1/2 Inch

B. 3/4 Inch

C. 3/8 Inch

D. 1/4 Inch

9. What are the most commonly used fasteners?

A. Threaded bolts

B. Pins

C. Screws

D. Staples

10. What size generating tube stock is permitted inside the steam and mud drum of a boiler?

A. 1 1/2 inch to 2 inch

B. 1/4 inch to 1/2 inch

C. 2 1/2 inch to 3 inch

D. 3/4 inch to 1 inch

SAMPLE

Answers

SAMPLE

1. D
2. A
3. C
4. B
5. C
6. B
7. A
8. C
9. A
10. A

SAMPLE

Explanations

SAMPLE

1. What is the most commonly used light lifting device in boiler shop operations?

A. Hydraulic jack

B. Chain pulley

C. Come-along

D. Chain hoist

In boiler shop work, overhead lifting needs to be controllable, safe, and versatile for positioning heavy parts. A chain hoist fits that role best because it offers smooth, controlled lifting and lowering, solid braking to hold a load in place, and easy attachment to overhead beams or trolleys for moving components around the shop. It provides good load capacity with straightforward operation, and it can be used in tight or confined spaces typical of boiler fabrication and maintenance. Compared with a hydraulic jack, which is great for lifting a single object but isn't ideal for continual, precise vertical positioning or for traveling along a beam, the chain hoist gives better control and portability. A come-along is lighter and useful for shorter pulls, but it requires more effort and offers less precise control under heavier loads. A chain pulley system increases mechanical advantage but isn't as practical for frequent overhead lifting and precise positioning as a dedicated chain hoist. For these reasons, the chain hoist is the most commonly used light lifting device in boiler shop operations.

2. Who is responsible for rigging when a big control valve is pulled?

A. Crane operator and rigger

B. Maintenance supervisor

C. Ground crew

D. Project engineer

The key idea is that lifting heavy equipment requires a clear division of on-site roles: the person who sets up the lift and the person who operator-controls the lift work together to make it safe. The rigger takes responsibility for the rigging plan—selecting the right slings, hooks, chains, and attachments; inspecting gear for wear; choosing the proper configuration based on the valve's weight and center of gravity; and securing the load so it won't shift or slip. The crane operator then uses that plan to lift and maneuver the valve, maintaining balance, watching the load path, and following the signal commands. Both roles are essential for a safe lift. Maintenance supervisors are focused on keeping equipment in good working condition rather than performing rigging tasks. Ground crew may assist with setup and staging but don't determine rigging methods. Project engineers design and specify requirements, but they don't perform the on-site rigging during the lift.

3. What type of valve is used on a hydro test tree to maintain test pressure after the hydro has reached its required pressure?

A. Gate

B. Ball

C. Check

D. Globe

The essential idea is one-way flow control to keep the test pressure from dropping once the target hydro pressure is reached. A check valve does exactly that: it allows fluid to flow into the test line to build pressure, then automatically closes to stop flow in the reverse direction. That prevents the test fluid from leaking back through the hydro test tree, so the system can hold the required pressure with minimal leakage. Gate valves and globe valves are better for isolating or throttling flow, but they don't inherently prevent backflow, which is why they're not used to maintain the pressure in this scenario. A ball valve provides quick shut-off but isn't designed to maintain a pressurized condition over time.

SAMPLE

4. Where is the convection section of a heater located?

A. Below the radiant tubes

B. Above the radiant tubes

C. Adjacent to the feed

D. Inside the combustion chamber

Heat is transferred in two stages inside a heater: first, radiant heat from the flame warms the tubes directly in the lower part of the furnace, and then hot combustion gases move through a convection section where the remaining heat is transferred to the water as the gases flow past more tubes. The convection section sits above the radiant tubes because the hot gases naturally rise after delivering radiant heat, allowing them to pass over the convection tubes and transfer heat efficiently by convection. Placing this section higher also keeps the hottest, most radiant zone separate from the convection area, making the overall heat transfer more efficient and the tubes less exposed to direct flame exposure. If the convection section were placed below the radiant tubes or inside the combustion chamber, heat transfer would be less efficient or would interfere with the combustion zone.

5. A worker is installing a blind in a flange for blanking off the gas line to the burners. The appropriate gasket cannot be found. What should the worker do?

A. Proceed with the blind anyway

B. Use a substitute gasket

C. Do not continue installing the blind until the proper gasket can be found

D. Delay but continue with other work

The situation tests safe practice when dealing with a critical gas-sealing component. A gasket in a flange for blanking off a gas line is there to create a reliable seal and prevent leaks. If the proper gasket isn't available, you must not proceed with installing the blind. Using an improvised or substitute gasket can fail under pressure, be incompatible with the flange materials, or not provide the correct compression, all of which can lead to a gas leak, a fire, or an explosion. The safest course is to halt the installation, obtain the approved gasket, and complete the work only when the correct part is in place and properly torqued and leak-tested. Delaying only part of the task while continuing other work doesn't resolve the hazard, since the unsealed gas line still poses a risk. If necessary, escalate to obtain the proper gasket and, once it's on hand, proceed with the installation and a proper leak check.

6. How many people can tie off to a vertical line?

A. One

B. Two

C. Three

D. Four

Vertical lifelines are fixed lines installed along a vertical surface to keep a worker attached while moving. The line has a rated capacity for the number of people who can be attached at once. In typical setups, a vertical lifeline can support two workers at the same time, each with their own harness and lanyard attached at separate points along the line. This keeps loads within what the line and anchors are designed to handle and helps prevent collisions or overloads. Exceeding that, with more than two people tied off simultaneously, risks overloading the system and creating a fall hazard. So two is the safe, intended maximum for a single vertical lifeline.

SAMPLE

7. All of the following would be reasons for rejecting a synthetic sling for rigging except?

A. An identification tag on the wrong side of the sling

B. Visible damage in the fiber

C. Knots or broken stitches

D. Excessive loads beyond rating

The situation is about recognizing what makes a synthetic sling unsafe and when it should be taken out of service. Synthetic slings must be free from damage and used within their rated capacity. When you inspect, you reject a sling if you find signs that weaken it or exceed its limits: visible damage to the fiber means the core or sheath has been compromised and could fail under load; knots or broken stitches create weak points where the load is not carried evenly by the seam, reducing strength; and applying loads beyond the sling's rating can cause sudden failure. Having the identification tag on the wrong side does not inherently weaken the sling. The tag provides important information about the sling, and as long as the tag is still legible and readable, its exact orientation doesn't compromise safety. If the tag were unreadable or missing, that would be a reason to reject it, but simply being on the opposite side isn't a fault that requires discarding the sling.

8. The maximum fillet size on a tube-to-drum seal weld should be?

A. 1/2 Inch

B. 3/4 Inch

C. 3/8 Inch

D. 1/4 Inch

In a tube-to-drum seal weld, the fillet size controls how much heat and filler metal you put into a joint that is already thin-walled and need to seal rather than bear heavy loads. You want enough weld to create a reliable seal, but not so much heat input that the tube or drum walls distort, warp, or burn through. A fillet size of 3/8 inch hits that balance: it's large enough to seal effectively but small enough to keep heat input and distortion under control. Larger sizes would introduce more heat and potential distortion, while a smaller size might not provide a dependable seal. So the maximum practical fillet for this type of seal weld is 3/8 inch.

9. What are the most commonly used fasteners?

A. Threaded bolts

B. Pins

C. Screws

D. Staples

Threaded bolts are the most commonly used fasteners because they deliver strong, adjustable clamping across a wide range of materials and applications. They pass through holes in two parts and are secured with nuts (often with washers) to spread the load and prevent loosening. The clamping force can be set precisely by tightening to a specified torque, and different bolt grades match strength to the job. They're removable and reusable, which makes maintenance and disassembly straightforward. In many industrial settings, including boilerwork and structural assemblies, this versatility and reliability keep bolts as the go-to choice for holding components firmly together. Pins, by contrast, mainly locate parts or provide simple shear connections rather than strong, clamped joints; screws rely on engaging tapped holes and may not handle the same high-load, disassembly-friendly requirements; staples are light-duty and not suitable for structural or heavy-duty connections.

SAMPLE

10. What size generating tube stock is permitted inside the steam and mud drum of a boiler?

A. 1 1/2 inch to 2 inch

B. 1/4 inch to 1/2 inch

C. 2 1/2 inch to 3 inch

D. 3/4 inch to 1 inch

Inside the steam and mud drum, generating tubes must be a size that provides enough mechanical strength, clearance for proper steam–water separation, and room for cleaning and inspection. The permitted range of 1 1/2 inch to 2 inches strikes that balance: it yields tubes sturdy enough to withstand boiler pressures, while leaving adequate space in the drum for sludge removal and for the flow paths that separate steam from water. Smaller tubes would be harder to inspect, prone to clogging, and more difficult to clean, increasing maintenance issues and flow resistance. Larger tubes would crowd the interior and reduce the drum's ability to separate steam effectively and would complicate fabrication and support. So, 1 1/2 to 2 inches is the standard size range that fits practical maintenance, safe operation, and efficient steam generation.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://nccrboilermaker.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE