NFPA LIQUEFIED PETROLEUM GAS CODE (NFPA 58) PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://nfpa-58liquefiedpetroleumgascode.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. **What must ASME LP gas motor/mobile fuel containers comply with according to the "Rules for Construction of Unfired Pressure Vessels"?**

   A. Only testing standards

   B. Design, fabrication, testing, and marking

   C. Environmental regulations

   D. Transportation requirements only

2. **What should be done if a Grade 1 leak is detected?**

   A. Inform the customers

   B. Take no action

   C. Install additional equipment

   D. Prompt action to mitigate the hazard

3. **For an applicant, what does paying applicable fees in a reciprocal examination agreement signify?**

   A. Commitment to further education

   B. Eligibility for exemption

   C. Financial capability

   D. Intent to relocate

4. **Which valve on a cargo tank is permitted to remain open during transportation?**

   A. Pressure relief valve

   B. Engine fuel line valve

   C. Emergency shutoff valve

   D. Liquid withdrawal valve

5. **Which portion of a cargo tank must be painted a reflecting color?**

   A. Lower one-third

   B. Upper two-thirds

   C. Every section equally

   D. Entire tank

SAMPLE

6. Where may a flexible connector NOT be used to connect a portable appliance?

A. In open areas

B. On rooftops

C. Concealed area between one room or another

D. Near an outdoor grill

7. What weight calculation method involves the water capacity to determine cylinder filling weight?

A. Water capacity x 0.6

B. Water capacity x 0.5

C. Water capacity x 0.42

D. Water capacity x 0.75

8. What is an acceptable method for protecting engine fuel container valves and connections?

A. Using a thick layer of insulation

B. Location of container and fitted guard

C. Covering with cloth material

D. Embedding in concrete

9. Plastic pipe, tubing, and fittings used to supply fuel gas must conform to which standard?

A. ASTM D 2513

B. ASTM D 3200

C. ISO 9001

D. ANSI 61

10. What is the minimum clearance on all sides and the rear of an unlisted water heater?

A. 6 inches

B. 12 inches

C. 18 inches

D. 24 inches

SAMPLE

Answers

SAMPLE

1. B
2. D
3. B
4. B
5. B
6. C
7. C
8. B
9. A
10. B

SAMPLE

Explanations

SAMPLE

1. What must ASME LP gas motor/mobile fuel containers comply with according to the "Rules for Construction of Unfired Pressure Vessels"?

A. Only testing standards

B. Design, fabrication, testing, and marking

C. Environmental regulations

D. Transportation requirements only

The correct answer is that ASME LP gas motor/mobile fuel containers must comply with design, fabrication, testing, and marking requirements according to the "Rules for Construction of Unfired Pressure Vessels." This is essential because the ASME (American Society of Mechanical Engineers) standards are established to ensure the safety, reliability, and performance of pressure vessels, which includes LP gas containers. Compliance with design requirements ensures that the containers are built to withstand the pressures they will encounter. Fabrication standards govern the methods used to construct the vessels, ensuring that high-quality materials and techniques are employed. Testing requirements involve various assessments to ascertain the integrity and performance of the containers before they are put into use, helping to prevent failures that could lead to accidents or leaks. Marking is important for certification and traceability purposes, providing vital information about the vessel's specifications and compliance with safety standards. Options related to testing standards only, environmental regulations, and transportation requirements do not encompass the full scope of compliance needed for these containers, which requires a comprehensive approach to ensure safety throughout the entire lifecycle of the vessel.

2. What should be done if a Grade 1 leak is detected?

A. Inform the customers

B. Take no action

C. Install additional equipment

D. Prompt action to mitigate the hazard

A Grade 1 leak is classified as an immediate hazard that requires prompt action. When such a leak is detected, the priority is to ensure safety and mitigate the risks associated with the leak. This can involve actions such as shutting off the gas supply, evacuating the area, and implementing emergency response procedures to prevent any potential accidents or injuries. Timely action is essential in these situations to prevent escalation, as Grade 1 leaks pose a significant danger of fire or explosion. Therefore, immediate measures must be taken to control the leak and protect both people and property. This understanding illustrates why the focus is on proactive measures in response to Grade 1 leaks, which helps to ensure the utmost safety in situations where hazardous conditions are present.

SAMPLE

3. For an applicant, what does paying applicable fees in a reciprocal examination agreement signify?

A. Commitment to further education

B. Eligibility for exemption

C. Financial capability

D. Intent to relocate

Paying applicable fees in a reciprocal examination agreement signifies eligibility for exemption. This process is established to acknowledge and streamline the qualifications of professionals who have already demonstrated their competence in one jurisdiction, potentially allowing for recognition or exemption from certain testing requirements in another jurisdiction. By fulfilling the fee requirement, the applicant indicates that they have met the prerequisites laid out in the reciprocal agreement, thus qualifying for an exemption from redundant examinations. This facilitates mobility for professionals and supports harmonization of standards across different regions, enhancing workforce efficiency without compromising safety or regulatory compliance.

4. Which valve on a cargo tank is permitted to remain open during transportation?

A. Pressure relief valve

B. Engine fuel line valve

C. Emergency shutoff valve

D. Liquid withdrawal valve

The engine fuel line valve is the only valve that is permitted to remain open during transportation of liquefied petroleum gas (LPG) in a cargo tank. This is because the fuel line valve is associated with the engine's operation and is necessary for providing fuel to the engine for it to run during transit. In contrast, the other valves are designed for safety and containment purposes. The pressure relief valve is crucial for releasing excess pressure and preventing tank rupture, and it must remain in a closed position to maintain the integrity of the system under normal transport conditions. The emergency shutoff valve is designed to stop the flow of gas in case of an emergency, and having it open during transportation could lead to risks if an emergency arose. The liquid withdrawal valve, which allows for the withdrawal of liquid LPG from the tank, should also remain closed to prevent accidental discharge or leaks during transport, as this poses significant safety and environmental hazards. Understanding the role of each valve helps ensure safe transportation practices in compliance with NFPA 58 regulations, emphasizing the importance of only keeping certain valves open while ensuring the others are safely secured.

SAMPLE

5. Which portion of a cargo tank must be painted a reflecting color?

A. Lower one-third

B. Upper two-thirds

C. Every section equally

D. Entire tank

The correct portion of a cargo tank that must be painted a reflecting color is the upper two-thirds. This requirement is primarily aimed at enhancing the safety and visibility of the cargo tank, particularly in conditions where it may be exposed to direct sunlight. By painting the upper two-thirds with a reflective color, heat absorption by the tank is minimized, which helps to prevent pressure buildup within the tank due to rising temperatures. The reflective color serves to deflect sunlight, thereby maintaining the integrity of the liquefied petroleum gas stored within. This is crucial in preventing potential hazards such as vaporization of the LPG, which can lead to overpressure and increase the risk of explosions or leaks. Other options, such as painting only the lower one-third or every section equally, do not adequately address the need to manage heat absorption effectively. Painting the entire tank would also not conform to the specific regulation, as it doesn't focus on the critical upper portion that is most affected by sunlight and heat. Therefore, the requirement highlights the importance of targeting the specific area that balances safety and regulatory compliance.

6. Where may a flexible connector NOT be used to connect a portable appliance?

A. In open areas

B. On rooftops

C. Concealed area between one room or another

D. Near an outdoor grill

A flexible connector is designed to provide a degree of flexibility for the connection between a gas appliance and the gas supply, facilitating movement or replacement of the appliance. However, certain locations are deemed unsuitable for the use of flexible connectors due to safety and regulatory concerns as outlined in NFPA 58. In concealed areas, such as spaces between rooms, a flexible connector is not permitted because these locations pose potential hazards should a gas leak occur. The ability to readily detect gas leaks is crucial for safety; thus, connectors in concealed spaces would hinder this capability. In the event of a leak, the gas could accumulate out of sight, leading to an increased risk of fire or explosion without proper ventilation. Open areas, rooftops, and near outdoor grills are typically considered acceptable for the use of flexible connectors as they provide adequate ventilation and reduce the risk of gas accumulation. If a leak were to occur in these settings, it would be more easily dispersed and detected, thereby mitigating the risks associated with gas appliances.

SAMPLE

7. What weight calculation method involves the water capacity to determine cylinder filling weight?

A. Water capacity x 0.6

B. Water capacity x 0.5

C. Water capacity x 0.42

D. Water capacity x 0.75

The correct method for calculating the filling weight of a liquefied petroleum gas (LPG) cylinder using its water capacity is based on the factor of 0.42. This factor accounts for the fact that propane and butane have specific gravities lighter than water, and this conversion allows for accurate determination of the weight of the gas contained within the cylinder. When the water capacity of a cylinder is multiplied by 0.42, it gives the weight of the liquefied gas in pounds (or kilograms) that can safely be filled into that cylinder. This method is essential for ensuring the safe and efficient filling of LPG cylinders, as it takes into consideration the properties of the gas and ensures compliance with safety standards outlined in the NFPA 58 code. By using this calculation, one can determine the appropriate fill level, avoiding overfilling and ensuring safe operation. The other methods listed don't align with the standard practices and could lead to inaccurate calculations, thereby compromising the safety and efficacy of the LPG cylinder filling process.

8. What is an acceptable method for protecting engine fuel container valves and connections?

A. Using a thick layer of insulation

B. Location of container and fitted guard

C. Covering with cloth material

D. Embedding in concrete

Choosing the location of the container and employing a fitted guard is an effective method for protecting engine fuel container valves and connections. This approach ensures that the valves and connections are shielded from potential physical damage as well as environmental conditions that could compromise their integrity. By strategically placing the container in a location that minimizes exposure to hazards—such as vehicle traffic, falling objects, or severe weather—risks are reduced. Additionally, a fitted guard serves as an additional barrier, effectively preventing accidental impacts or interference. This method is vital for maintaining operational safety and ensuring that the fuel supply is reliable and secure from both physical and environmental threats. In contrast, using a thick layer of insulation or covering with cloth material might not provide adequate protection against physical damage or weather-related issues. Embedding the container in concrete could pose challenges for maintenance access and might not be practical in many applications. Therefore, choosing the right location and employing a suitable guard represents a comprehensive strategy that balances accessibility and protection for the fuel container's valves and connections.

SAMPLE

9. Plastic pipe, tubing, and fittings used to supply fuel gas must conform to which standard?

A. ASTM D 2513

B. ASTM D 3200

C. ISO 9001

D. ANSI 61

The appropriate standard for plastic pipe, tubing, and fittings used to supply fuel gas is ASTM D 2513. This standard specifically addresses the requirements for thermoplastic gas piping systems, ensuring that they are suitable for the transportation of fuel gases. The standard covers aspects like material properties, dimensions, testing methods, and installation practices that are critical for safety and performance in the gas supply context. Other standards listed do not pertain specifically to fuel gas applications. ASTM D 3200, for instance, relates to a different set of specifications that do not apply to fuel gas piping systems. ISO 9001 is a standard for quality management systems but does not specifically cover the materials used for gas piping. ANSI 61 deals with the standards for potable water and does not encompass the criteria for gas service. Thus, ASTM D 2513 is the dedicated standard ensuring that plastic materials used for fuel gas applications meet the necessary safety and performance criteria.

10. What is the minimum clearance on all sides and the rear of an unlisted water heater?

A. 6 inches

B. 12 inches

C. 18 inches

D. 24 inches

The minimum clearance requirement for an unlisted water heater is established to ensure proper ventilation, allow for servicing, and minimize the risk of fire hazards. Specifically, the NFPA 58 code emphasizes that adequate space is necessary around appliances, particularly those that are unlisted or not subject to the same testing and certification standards as listed appliances. In this case, the 12 inches clearance is the standard measurement specified for unlisted water heaters, which helps in promoting safety and operational efficiency. This clearance allows sufficient air circulation to the appliance, reducing the risk of overheating and ensuring that any heat or combustion products can dissipate effectively without risk of ignition. Understanding this clearance is critical for installation practices, as inadequate space can lead to dangerous conditions, such as restricted airflow or increased fire risk, necessitating strict adherence to the regulated distances outlined in the code.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://nfpa-58liquefiedpetroleumgascode.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE