NICET CONSTRUCTION MATERIALS TESTING SOILS LEVEL I PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://nicetconstmatsoilslvl1.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. Which of the following is considered fine-grained soil?

A. Silty soil

B. Gravel

C. Clay soil

D. Both Silty and Clay soil

2. What does the term "maximum dry density" refer to in the context of soil compaction tests?

A. The least weight of soil that can be compacted

B. The highest weight of compacted soil at a given moisture content

C. The average weight of all soil types

D. The density of soil in its saturated state

3. What action should be taken if the rammer is adjusted or repaired in Standard/Modified Proctor tests?

A. It should be thrown away

B. It should be restandardized

C. It should be cleaned thoroughly

D. It should be recalibrated

4. When is a correction factor established in a standard proctor test?

A. When the test specimen contains more than 2% of oversize fractions

B. When the test specimen contains more than 5% of oversize fractions

C. When the test specimen contains 10% of oversize fractions

D. When the test specimen contains 15% of oversize fractions

5. What is a requirement for acceptable sand used in the sand cone?

A. Bulk density variation should not exceed 5%

B. Loose density variation should not exceed 1%

C. Bulk density variation should not be greater than 1%

D. It can have varying moisture content

SAMPLE

6. What is the purpose of using a dispersant in soil testing?

A. To increase soil density
B. To promote the separation of soil particles
C. To stabilize soil composition
D. To enhance soil cohesiveness

7. Which type of testing evaluates the load-bearing capacity of a drilled shaft?

A. Compression test
B. Load test
C. Shear test
D. Tensile strength test

8. What does the term "shrink-swell potential" refer to?

A. The tendency of soil to increase in volume when saturated
B. The potential of soil to lose moisture content
C. The capacity of soil to absorb contaminants
D. The variability in soil density with moisture changes

9. How does temperature impact soil permeability?

A. Increased temperature can decrease soil permeability
B. Temperature has no effect on permeability
C. Increased temperature can enhance the flow rate of water through soil
D. Cooled soil has better permeability than warm soil

10. What information is provided through laboratory compaction tests?

A. Percent compaction and time to achieve optimum moisture
B. Percent compaction and molding water needed for required properties
C. Soil type and density
D. Grain size distribution only

SAMPLE

Answers

SAMPLE

1. D
2. B
3. B
4. B
5. C
6. B
7. B
8. A
9. C
10. B

SAMPLE

Explanations

SAMPLE

1. Which of the following is considered fine-grained soil?

A. Silty soil

B. Gravel

C. Clay soil

D. Both Silty and Clay soil

Fine-grained soil is characterized by its small particle size, typically less than 0.075 mm in diameter. This category includes both silty and clay soils. Silty soil, which is composed of fine, smooth particles, holds moisture well but has lower plasticity than clay. Consequently, it tends to have better drainage properties compared to clay. Clay soil, on the other hand, consists of even finer particles and has a high plasticity and significant cohesion, making it very malleable when wet but often problematic due to its expansion and contraction with moisture changes. Both types contribute to the overall classification of fine-grained soils, making the selection of both silty and clay soil the most accurate choice. Other options, such as gravel, contain much larger particles and are classified as coarse-grained soil, which sets them apart from the fine-grained category. Thus, the inclusion of both silty and clay soil in this response correctly identifies the two primary types of fine-grained soils.

2. What does the term "maximum dry density" refer to in the context of soil compaction tests?

A. The least weight of soil that can be compacted

B. The highest weight of compacted soil at a given moisture content

C. The average weight of all soil types

D. The density of soil in its saturated state

The term "maximum dry density" refers specifically to the highest weight of compacted soil that can be achieved at a given moisture content. This measurement is crucial in soil compaction tests, such as the Proctor test, where the properties of soil are analyzed to determine the optimum moisture content that allows for the most efficient compaction. In this context, achieving maximum dry density indicates that the soil particles are packed as closely together as possible, which enhances the material's load-bearing capacity and minimizes settlement. The moisture content plays a significant role because it affects the cohesion and spacing between soil particles; therefore, maximizing dry density at a specific moisture level is essential for construction applications where structural integrity is critical. The other choices do not accurately reflect the definition of maximum dry density. It is not about the least weight of soil, an average of soil types, or a saturated condition, as these factors address different aspects of soil behavior and properties. Focusing on the relationship between dry density and moisture content allows engineers and technicians to optimize soil compaction for construction purposes.

SAMPLE

3. What action should be taken if the rammer is adjusted or repaired in Standard/Modified Proctor tests?

A. It should be thrown away

B. It should be restandardized

C. It should be cleaned thoroughly

D. It should be recalibrated

In the context of Standard and Modified Proctor tests, which are used to determine the optimum moisture content and maximum dry density of soils, it's essential that all equipment maintains specific performance standards throughout testing procedures. If a rammer is adjusted or repaired, it can impact the results of the tests, as the rammer's weight, fall height, and impact energy need to conform to established specifications. Rstandardizing the rammer is crucial after any adjustments or repairs because it ensures that the equipment is functioning according to the precise criteria defined by the testing standards. This process validates that the rammer will deliver consistent and reliable results during the compaction testing of soils. Without restandardization, there could be uncertainty regarding how the adjustments or repairs may have altered its performance characteristics, leading to inaccurate test results. Cleaning the rammer, while beneficial for maintenance, does not directly address issues of measurement accuracy or compliance with testing standards. Similarly, recalibrating typically refers to adjusting measuring devices; in this case, it is the need for restandardization that clearly lays the groundwork for ensuring precise testing compliance. Thus, restandardizing is the correct action to maintain the integrity of the test results.

4. When is a correction factor established in a standard proctor test?

A. When the test specimen contains more than 2% of oversize fractions

B. When the test specimen contains more than 5% of oversize fractions

C. When the test specimen contains 10% of oversize fractions

D. When the test specimen contains 15% of oversize fractions

In a standard Proctor test, a correction factor is established when the test specimen contains more than 5% of oversize fractions. This situation arises because the presence of oversize particles can significantly affect the density and moisture content measurements. The Proctor test is designed to evaluate the compaction characteristics of soil, and having a standard method for addressing oversize materials ensures that the resulting values are accurate and representative of the soil's compaction properties. When oversize particles exceed 5%, they can disrupt the uniformity of the soil matrix being tested, leading to a potential misrepresentation of the soil's density after compaction. By applying a correction factor at this threshold, engineers and technicians maintain the integrity of the test results, allowing for more reliable design and analysis of soil in construction projects. This correction is crucial in ensuring that the test results are valid for determining the optimal moisture content and maximum density for proper soil compaction.

SAMPLE

5. What is a requirement for acceptable sand used in the sand cone?

A. Bulk density variation should not exceed 5%

B. Loose density variation should not exceed 1%

C. Bulk density variation should not be greater than 1%

D. It can have varying moisture content

The requirement for acceptable sand used in the sand cone method pertaining to bulk density variation is that it should not exceed 1%. This specification is crucial because the accuracy of the sand cone test depends on the consistent properties of the sand used for determining the density of the material being tested. Using sand with a bulk density variation greater than 1% could lead to significant errors in the calculation of the in-place density of the soil or aggregate material, which is a key factor in assessing the compaction and stability of the construction site. Consistency in the density of the sand ensures that the measurements taken are reliable and valid, leading to more accurate results that are essential for quality assurance in construction practices. The other options relate to various forms of density measurement that are not as critical for this specific test. For instance, while moisture content can affect the density of the sand, it is not a requirement for the sand itself to have varying moisture content, as this could also introduce variability in the testing process.

6. What is the purpose of using a dispersant in soil testing?

A. To increase soil density

B. To promote the separation of soil particles

C. To stabilize soil composition

D. To enhance soil cohesiveness

Using a dispersant in soil testing is essential for promoting the separation of soil particles. In soil analysis, particularly in tests like sedimentation analysis or particle size distribution, soil samples often contain clumps or aggregates. These aggregates can interfere with obtaining accurate measurements of the individual particles' sizes and distribution. By adding a dispersant, the surface tension among the soil particles is reduced, which allows these particles to separate and disperse uniformly throughout a liquid medium. This uniform distribution is crucial for achieving precise and reliable results when analyzing the soil's physical properties, such as its texture, grading, or classification. The ability to effectively separate particles ensures that the testing methods yield data reflective of the true characteristics of the soil sample.

7. Which type of testing evaluates the load-bearing capacity of a drilled shaft?

A. Compression test

B. Load test

C. Shear test

D. Tensile strength test

The load test is specifically designed to evaluate the load-bearing capacity of a drilled shaft. This testing method involves applying a load to the shaft and monitoring its behavior under that load, allowing engineers to assess how much weight the shaft can support before failure. Load tests can provide critical data that informs design decisions and ensures structural safety. In contrast, other testing methods serve different purposes. The compression test measures the material's ability to withstand axial loads without failing, but it is not specific to drilled shafts. The shear test assesses the material's resistance to shear forces, which also does not directly determine the load-bearing capacity of a drilled shaft. The tensile strength test evaluates how much tension a material can withstand before breaking, but again, it does not focus on the specific performance of drilled shafts under loading conditions. Each of these methods can be important in their own contexts, but the load test directly addresses the evaluation of a drilled shaft's capacity to bear loads effectively.

SAMPLE

8. What does the term "shrink-swell potential" refer to?

A. The tendency of soil to increase in volume when saturated

B. The potential of soil to lose moisture content

C. The capacity of soil to absorb contaminants

D. The variability in soil density with moisture changes

The term "shrink-swell potential" specifically pertains to the tendency of certain types of soil, particularly clay-rich soils, to undergo significant changes in volume in response to moisture content variations. When soil is saturated with water, it can absorb moisture and swell, increasing in volume. Conversely, when the moisture content decreases, the soil can shrink, resulting in a reduction in volume. This characteristic is particularly important in construction and agricultural applications, as it can lead to ground instability, cracking, and other structural issues if not properly accounted for. The other choices refer to different properties of soil that do not align with the definition of shrink-swell potential. For instance, the potential of soil to lose moisture content is more about drying and does not capture the volume change aspect that is central to shrink-swell behavior. The capacity of soil to absorb contaminants relates to soil pollution and retention properties rather than physical dimensional changes. Finally, variability in soil density with moisture changes is a broader concept that discusses density fluctuations but does not specifically highlight the dimensional expansion or contraction associated with shrink-swell potential.

9. How does temperature impact soil permeability?

A. Increased temperature can decrease soil permeability

B. Temperature has no effect on permeability

C. Increased temperature can enhance the flow rate of water through soil

D. Cooled soil has better permeability than warm soil

Temperature plays a significant role in the behavior of water in soil, particularly in relation to soil permeability. As the temperature of water increases, its viscosity decreases, meaning that water becomes less thick and flows more easily. When water flows more readily, it can move through the interconnected pores and spaces between soil particles at a greater rate. Therefore, higher temperatures can contribute to an enhanced flow rate of water through soil, resulting in increased permeability. In contrast, lower temperatures can cause the viscosity of water to rise, making it thicker and more resistant to flow, which can lead to a decrease in permeability. Additionally, while a variety of soil types and their structures can affect permeability, temperature remains a crucial factor influencing the dynamics of water movement within those soils. The notion that temperature has no effect on permeability does not take into account this relationship between temperature, water viscosity, and flow rates. Thus, an increase in temperature generally leads to improved water flow through soil, which directly correlates to enhanced soil permeability.

SAMPLE

10. What information is provided through laboratory compaction tests?

A. Percent compaction and time to achieve optimum moisture

B. Percent compaction and molding water needed for required properties

C. Soil type and density

D. Grain size distribution only

Laboratory compaction tests primarily focus on determining the relationship between moisture content and the density of soil. The results of these tests, such as Proctor tests, yield vital information, including the optimum moisture content required to achieve maximum dry density of the soil. This information is crucial for construction and engineering applications where soil stabilization and compaction are implemented to ensure the structural integrity of the built environment. Through these tests, the percent compaction can be derived by comparing the achieved density to the maximum dry density at the optimum moisture content identified during the test. Furthermore, knowing the molding water (moisture content) needed allows engineers to select appropriate moisture levels for soil before compaction in the field. This aids in achieving the desired soil properties for construction purposes, making it critical information for ensuring the soil behaves as expected under load. Other options provide limited or incorrect information: soil type and density do not provide insight into the compaction process, and grain size distribution does focus on different soil characteristics than those assessed in compaction tests, which are centered on density and moisture content relationships.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://nicetconstmatsoilslvl1.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE