NON-DESTRUCTIVE TESTING (NDT) PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://nondestructivetesting.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. **What happens to magnetic fields when AC is applied to a ferromagnetic material?**

   A. The magnetic field strengthens uniformly

   B. The magnetic field penetrates deeper

   C. Eddy currents are created, limiting depth of penetration

   D. The material loses its magnetization

2. **What instrument adjustment must be changed to ensure accurate results when performing inspections on aluminum?**

   A. Frequency

   B. Amplitude

   C. Velocity

   D. Gain

3. **Which standard specifies the requirements for personnel performing eddy current testing?**

   A. ASTM E 1002

   B. SNT-TC-1A

   C. NDT Level II

   D. ISO 9712

4. **How do sound waves propagate within a material?**

   A. Due to heat expansion

   B. Through vibrations of the medium's particles

   C. By external force applied

   D. Through electronic signals only

5. **What does Method A refer to in NDT practices?**

   A. Surface Examination

   B. Removal Methods

   C. Ultrasonic Testing

   D. Magnetic Particle Testing

SAMPLE

6. What is a characteristic of shear waves in ultrasonic testing?

A. They travel faster than longitudinal waves

B. They cannot propagate through liquids

C. They penetrate further than longitudinal waves

D. They are used to inspect only specific materials

7. What term is used to describe the phenomenon when one circuit induces current flow in a second nearby circuit?

A. Electromagnetic induction

B. Resistance fluctuation

C. Mutual inductance

D. Conductive interaction

8. Which frequency transducer produces the least amount of penetration strength?

A. 5 MHz

B. 10 MHz

C. 15 MHz

D. 20 MHz

9. When preparing for penetrant inspection, what is a critical step that should not be overlooked?

A. Choosing the color of the penetrant

B. Cleaning the surface properly

C. Determining inspection angles

D. Ensuring part temperature compliance

10. When setting up equipment for ultrasonic testing, which factor is crucial to calibrate correctly?

A. Frequency

B. Power Supply

C. Velocity

D. Transducer size

SAMPLE

Answers

SAMPLE

1. C
2. C
3. B
4. B
5. B
6. B
7. C
8. C
9. B
10. C

SAMPLE

Explanations

SAMPLE

1. What happens to magnetic fields when AC is applied to a ferromagnetic material?

A. The magnetic field strengthens uniformly

B. The magnetic field penetrates deeper

C. Eddy currents are created, limiting depth of penetration

D. The material loses its magnetization

When alternating current (AC) is applied to a ferromagnetic material, eddy currents are induced due to the changing magnetic fields. These currents flow in closed loops within the material and generate their own magnetic fields, which counteract the applied field. This phenomenon limits the depth to which the magnetic field can penetrate into the material. The presence of eddy currents creates a barrier that effectively restricts the influence of the external magnetic field, leading to reduced magnetic field strength at greater depths in the material. This understanding elucidates why the development of eddy currents is a critical consideration in applications of non-destructive testing and magnetic inspection methods. The effect of eddy currents becomes especially significant in thicker ferromagnetic materials or at higher frequencies of AC. This relationship highlights the importance of understanding electromagnetic principles in evaluating the effectiveness and limitations of magnetic testing techniques.

2. What instrument adjustment must be changed to ensure accurate results when performing inspections on aluminum?

A. Frequency

B. Amplitude

C. Velocity

D. Gain

When performing inspections on aluminum, it's essential to adjust the velocity measurement to ensure accurate results. This is because different materials have varying acoustic properties, affecting sound wave propagation speeds. Aluminum has a specific velocity associated with sound waves traveling through it, which is crucial when interpreting inspection data. If the velocity is not properly set for aluminum, the time it takes for sound waves to return to the sensor can be miscalculated. This miscalculation can lead to incorrect depth measurements or identification of flaws, ultimately compromising the integrity and safety assessments of the aluminum structure being inspected. Ensuring that the velocity setting reflects aluminum's characteristics allows for precise readings and reliable evaluations during the inspection process.

SAMPLE

3. Which standard specifies the requirements for personnel performing eddy current testing?

A. ASTM E 1002

B. SNT-TC-1A

C. NDT Level II

D. ISO 9712

The standard that specifies the requirements for personnel performing eddy current testing is SNT-TC-1A. This standard, developed by the American Society for Nondestructive Testing (ASNT), provides guidance on the qualification and certification of personnel in various nondestructive testing (NDT) methods, including eddy current testing. It outlines the necessary education, training, and experience requirements that individuals must meet to ensure they are competent to perform inspections and evaluations using this specific NDT technique. It is crucial for personnel involved in eddy current testing to meet these established standards to ensure consistency, reliability, and safety in their work. SNT-TC-1A emphasizes the importance of having trained professionals who understand the principles of eddy currents, equipment operating procedures, and the interpretation of results, thereby ensuring high standards are maintained during inspections. Other choices may refer to specific techniques or broader qualifications but do not directly specify personnel requirements for eddy current testing itself. ASTM E 1002 is focused on the actual methods and procedures for conducting eddy current tests rather than personnel qualifications. NDT Level II typically refers to a level of proficiency in NDT methods but doesn't specify requirements for eddy current testing specifically. ISO 9712 provides a more

4. How do sound waves propagate within a material?

A. Due to heat expansion

B. Through vibrations of the medium's particles

C. By external force applied

D. Through electronic signals only

Sound waves propagate through a material primarily by the vibrations of the medium's particles. When a sound wave travels through a solid, liquid, or gas, it causes the particles within that medium to vibrate and oscillate. These vibrations create areas of compression and rarefaction, which allow the sound energy to move through the material. The efficiency of sound propagation can vary based on the material's density, elasticity, and structure, but the fundamental principle remains that it's the particle-to-particle interaction that facilitates the transmission of sound. The other options involve concepts that do not accurately describe the mechanism of sound wave propagation. For instance, heat expansion does not directly cause sound waves to travel; however, it might affect the properties of the material itself. External force can initiate vibrations, but it does not encompass the continuous propagation of sound waves once they have been generated. Electronic signals pertain to a different realm entirely, related more to data transmission and communication rather than mechanical wave propagation.

SAMPLE

5. What does Method A refer to in NDT practices?

A. Surface Examination

B. Removal Methods

C. Ultrasonic Testing

D. Magnetic Particle Testing

Method A in Non-Destructive Testing (NDT) typically refers to removal methods, which include techniques that involve the physical removal of material to assess certain properties or conditions within a test specimen. The context of removal methods is crucial in NDT applications, particularly when evaluating the integrity and structural health of materials without compromising their overall utility. Such methods can include grinding or milling away material to observe subsurface defects, which is essential in industries where safety and material performance are paramount. Surface examination, ultrasonic testing, and magnetic particle testing are distinct methodologies within NDT but do not fall under the specific designation of Method A. While they are important techniques, they focus on different aspects of material inspection and assessment rather than the removal of material itself. Understanding these distinctions helps in correctly identifying the methodologies used in various NDT situations.

6. What is a characteristic of shear waves in ultrasonic testing?

A. They travel faster than longitudinal waves

B. They cannot propagate through liquids

C. They penetrate further than longitudinal waves

D. They are used to inspect only specific materials

Shear waves, also known as S-waves, are indeed characterized by their inability to propagate through fluids, which distinguishes them from longitudinal waves. In the context of ultrasonic testing, this characteristic is crucial because shear waves move through solids by causing shear strain in the material. This type of motion is not possible in fluids, where the particles can only support longitudinal stress. Understanding this aspect of shear waves is essential, particularly in applications such as inspecting structures made of solid materials (like metals and composites) where the detection of flaws or integrity evaluation requires the shear wave's unique propagation characteristics. The fact that they are ineffective in liquids makes them particularly valuable in testing solid materials since it allows for an assessment of defects or discontinuities that may be missed by longitudinal waves, which can propagate through both solids and fluids. Other options do not align with the fundamental properties of shear waves. For example, shear waves do not travel faster than longitudinal waves; in fact, they generally have a slower velocity in solids compared to longitudinal waves. Moreover, they do not penetrate further than longitudinal waves either; longitudinal waves typically have greater penetration due to their ability to travel through liquids and solids. Lastly, while shear waves are often used for specific materials, they are not limited to just a

SAMPLE

7. What term is used to describe the phenomenon when one circuit induces current flow in a second nearby circuit?

A. Electromagnetic induction

B. Resistance fluctuation

C. Mutual inductance

D. Conductive interaction

The phenomenon when one circuit induces current flow in a second nearby circuit is best described as mutual inductance. This term specifically refers to the ability of one electrical circuit to influence another through its magnetic field. When an alternating current (AC) flows through the first circuit, it creates a changing magnetic field around it. If a second circuit is located within this magnetic field, the change can induce an electromotive force (EMF) in the second circuit, leading to current flow. Mutual inductance is a key principle in many electrical devices, such as transformers, where it enables the transfer of energy between circuits through magnetic coupling. It highlights the relationship between two coils and how the change in current in one coil can affect the other. Understanding this phenomenon is important for applications in non-destructive testing (NDT) techniques that rely on electromagnetic principles, such as eddy current testing, where the interaction between currents in conductive materials can reveal material properties and integrity.

8. Which frequency transducer produces the least amount of penetration strength?

A. 5 MHz

B. 10 MHz

C. 15 MHz

D. 20 MHz

A transducer's frequency is inversely related to its penetration capability in ultrasonic testing. Lower frequency transducers, such as those operating at 5 MHz, possess a longer wavelength, allowing them to penetrate deeper into materials. Conversely, as the frequency increases, the wavelength decreases, which improves the resolution of the images obtained but compromises the ability to penetrate deeper. In this context, a transducer operating at 15 MHz will produce even less penetration strength than one at 10 MHz, and a 20 MHz transducer will have even greater limitations. Therefore, the higher the frequency, the less penetration strength the signal will possess due to its higher absorption and scattering rate by the medium it is attempting to penetrate. This means that among the given frequencies, the 15 MHz transducer indeed would produce the least amount of penetration strength when compared to the lower frequencies, reinforcing the understanding that higher frequency correlates with reduced depth penetration capabilities.

SAMPLE

9. When preparing for penetrant inspection, what is a critical step that should not be overlooked?

A. Choosing the color of the penetrant

B. Cleaning the surface properly

C. Determining inspection angles

D. Ensuring part temperature compliance

Cleaning the surface properly is a critical step in the penetrant inspection process because it directly impacts the effectiveness and reliability of the inspection results. Penetrant testing relies on the ability of the liquid penetrant to seep into surface-breaking defects. If the surface is contaminated with dirt, grease, oil, or any other substances, these contaminants can impede the penetrant's ability to enter defects. Effective cleaning ensures that the surface is free from any materials that could obstruct the penetrant. This step is essential not only for obtaining accurate test results but also for ensuring that any flaws or discontinuities present are properly identified. While other aspects like choosing the color of the penetrant, determining inspection angles, and ensuring part temperature compliance are important, they all depend on a clean surface to function effectively. Without proper cleaning, even the best chosen penetrant or the most ideal inspection angle would not yield accurate assessments of the component's integrity.

10. When setting up equipment for ultrasonic testing, which factor is crucial to calibrate correctly?

A. Frequency

B. Power Supply

C. Velocity

D. Transducer size

In ultrasonic testing, calibrating the velocity of the sound waves in the medium being examined is crucial because it directly affects the accuracy of the measurements obtained. The speed at which sound travels through different materials varies based on their density, elasticity, and temperature, among other factors. Therefore, knowing the correct velocity allows the technician to accurately interpret the time-of-flight measurements taken during the testing process. If the velocity is set incorrectly, the resulting distance measurements could be erroneous, potentially leading to misinterpretation of flaws or discontinuities within the material. While other factors such as frequency, power supply, and transducer size are important for optimizing the testing setup and ensuring efficient operation, they do not have the same direct impact on the accuracy of spatial measurements as velocity does. The carrier frequency affects resolution and penetration but does not change the time-of-flight calculations per se. Similarly, while a stable power supply is critical for consistent equipment performance, it does not influence the calibration required for accurate distance measurements. Transducer size can affect the beam profile and sensitivity, yet it is the velocity that fundamentally governs the relationships between time and distance in ultrasonic testing.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://nondestructivetesting.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE