PE CIVIL TRANSPORTATION PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://peciviltranspo.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. What does R2 in median design represent?

A. The total width of a roadway

B. The length of a turn bay

C. The radius of a circular median opening

D. The setback distance between lanes

2. What must be true if a culvert is laid on a steep slope?

A. The culvert is outlet controlled

B. The culvert is inlet or outlet controlled

C. The culvert is inlet controlled

D. The flow in the culvert is subcritical through the entire length

3. Which of the following is a requirement for road signs?

A. High cost for installation

B. High visibility - retro-reflective

C. Low maintenance

D. Dim lighting

4. The empirical method or model described in M-E PDG is specifically referred to as which model?

A. Pavement response model

B. Performance prediction model

C. Mechanistic model

D. Design threshold model

5. Which table in the MUTCD addresses the placement of warning signs?

A. Table 2C-1

B. Table 2C-4

C. Table 6F-1

D. Table 2B-1

6. What is the minimum cross slope allowed for ramps?

A. 0.5%

B. 1.0%

C. 1.5%

D. 2.0%

SAMPLE

7. Which type of signal operation involves a fixed cycle regardless of traffic?

A. Pretimed operation
B. Semi-actuated operation
C. Full actuated operation
D. Dynamic operation

8. What does the dynamic cone penetrometer (DCP) test determine?

A. Indirect correlation between soil strength and moisture
B. Direct correlation between soil strength and resistance to penetration
C. Soil cohesion
D. Soil density

9. What factors does the coefficient of permeability (k) depend on?

A. Soil particle size, shape, structure, void ratio
B. Degree of saturation, void connectivity
C. All of the above
D. Only soil particle size and shape

10. What does a direct runoff hydrograph result from?

A. Base flow
B. Total Rainfall
C. Rainfall Excess
D. Interflow

SAMPLE

Answers

SAMPLE

1. C
2. C
3. B
4. B
5. B
6. B
7. A
8. B
9. C
10. C

SAMPLE

Explanations

SAMPLE

1. What does R2 in median design represent?

A. The total width of a roadway

B. The length of a turn bay

C. The radius of a circular median opening

D. The setback distance between lanes

In median design, R2 denotes the radius of a circular median opening. This measurement is crucial for determining how vehicles can safely navigate through or around a median. A well-designed median with an appropriate radius allows for smoother transitions and enhances safety by reducing the likelihood of overshooting the median or experiencing vehicle instability. The circular opening needs to be sufficient to accommodate turning movements without undue strain on vehicle systems, thus aiding in traffic flow and providing safe access to cross streets or pedestrian pathways. The other options, although relevant in various contexts of roadway design, do not specifically address the function of R2 in median geometry.

2. What must be true if a culvert is laid on a steep slope?

A. The culvert is outlet controlled

B. The culvert is inlet or outlet controlled

C. The culvert is inlet controlled

D. The flow in the culvert is subcritical through the entire length

For a culvert laid on a steep slope, it is important to recognize how the slope affects the flow conditions within the culvert. When a culvert is installed on a steep slope, it tends to promote higher velocities in the flow. Under these conditions, one of the dominant factors influencing the flow is the inlet control, as the flow rate may be limited by the conditions at the inlet of the culvert rather than the outlet. Inlet control occurs when the entrance conditions of the culvert restrict flow, effectively determining the maximum flow rate the culvert can carry regardless of the outlet conditions. On a steep slope, if the culvert's inlet is not designed properly or is experiencing a high head difference, it could lead to situations where the entrance geometry or flow conditions (like a submerged outlet) control the capacity and flow dynamics. Thus, for a culvert situated on a steep slope, it must be true that it is inlet controlled, indicating that the flow characteristics at the inlet dictate its performance.

3. Which of the following is a requirement for road signs?

A. High cost for installation

B. High visibility - retro-reflective

C. Low maintenance

D. Dim lighting

High visibility is a critical requirement for road signs, as they are essential for ensuring the safety of drivers, pedestrians, and cyclists. Retro-reflective materials are used in the manufacturing of these signs to enhance their visibility during both day and night conditions. This means that when headlights from vehicles shine on the sign, the retro-reflective material reflects the light back towards the source, making the signs more noticeable at night. This feature significantly aids in guiding and warning road users effectively, contributing to safer travel. The other factors mentioned, such as cost, maintenance, and lighting conditions, are not primary requirements for road signs. While low maintenance is beneficial, it does not directly influence the effectiveness of a road sign in terms of visibility and safety. Dim lighting would adversely affect visibility, and high installation costs do not pertain to the fundamental requirement of road sign functionality. Thus, high visibility using retro-reflective materials stands out as the key requirement for road signs.

SAMPLE

4. The empirical method or model described in M-E PDG is specifically referred to as which model?

A. Pavement response model

B. Performance prediction model

C. Mechanistic model

D. Design threshold model

The model referenced in the M-E PDG, known as the empirical method, is specifically characterized as a performance prediction model. This approach is fundamentally used for predicting the long-term performance of pavements based on historical data and observed outcomes, rather than solely on the underlying mechanisms or response forces acting within the pavement structure. Performance prediction models utilize historical performance data to establish relationships between design inputs (such as material properties, traffic loads, environmental conditions) and resulting pavement performance metrics (such as rutting, cracking, or overall durability). This methodology combines empirical data with a predictive framework to estimate how a pavement will react over time. By focusing on past performance, these models can effectively guide engineers in making informed decisions regarding pavement design and material selection. In contrast, the other options, while relevant to pavement design, do not accurately describe this specific empirical approach found in the M-E PDG.

5. Which table in the MUTCD addresses the placement of warning signs?

A. Table 2C-1

B. Table 2C-4

C. Table 6F-1

D. Table 2B-1

The correct choice regarding the placement of warning signs in the Manual on Uniform Traffic Control Devices (MUTCD) is indeed Table 2C-4. This table specifically provides detailed guidance on the positioning and installation of warning signs to ensure they are both visible and effective in alerting road users to potential hazards. Table 2C-4 offers criteria such as recommended distances from various types of roadways and conditions for the installation of warning signs. Understanding these guidelines is crucial for transportation engineers and planners as they design roadways and enhance safety for all users. The other tables mentioned focus on different aspects of traffic control. While Table 2C-1 deals with additional warning sign specifications and Table 2B-1 covers regulatory signs, they do not specifically address the placement criteria that are critical for warning signs. Meanwhile, Table 6F-1 pertains to guide signs and their specific use but does not connect to warning sign placement. This makes Table 2C-4 the best reference for the installation and location of warning signs.

SAMPLE

6. What is the minimum cross slope allowed for ramps?

A. 0.5%

B. 1.0%

C. 1.5%

D. 2.0%

The minimum cross slope allowed for ramps is significant for ensuring accessibility and safety for users, particularly for those with mobility impairments. A cross slope of 1.0% is often specified because it provides sufficient drainage for surface water while being gentle enough for individuals using wheelchairs or other mobility devices. This slope allows for effective water runoff without creating a hazardous condition for users who might struggle to navigate steeper slopes. If the cross slope were too steep, it could lead to difficulties in maneuvering, increasing the risk of tipping or losing control, especially in wet conditions. Furthermore, adherence to this standard helps ensure compliance with building codes and accessibility guidelines, such as the Americans with Disabilities Act (ADA), which aims to make public spaces usable for everyone. Other options either fall below this standard or exceed the maximum recommended cross slope, compromising accessibility and potentially leading to unsafe conditions.

7. Which type of signal operation involves a fixed cycle regardless of traffic?

A. Pretimed operation

B. Semi-actuated operation

C. Full actuated operation

D. Dynamic operation

The concept of pretimed signal operation is centered around the use of a fixed cycle length for traffic signals, which does not adapt to real-time traffic conditions. This means the signal phases are predetermined and remain constant, regardless of the volume of vehicles or pedestrians waiting at the intersection. Such a system is beneficial in areas with relatively steady traffic patterns, where the predictability of signal changes can help improve overall traffic flow without the need for constant adjustments. In contrast, semi-actuated and full actuated operations rely on real-time traffic conditions. Semi-actuated systems adjust the signal based on input from detectors on one or two approaches, while full actuated systems continuously monitor and manage signal timing based on traffic demand on all approaches. Dynamic operation also involves adapting signal timing based on variable traffic flows, often using advanced technologies for optimization. Therefore, pretimed operation is distinct in its fixed nature, ensuring that signals turn according to a set schedule rather than adapting to current traffic conditions.

SAMPLE

8. What does the dynamic cone penetrometer (DCP) test determine?

A. Indirect correlation between soil strength and moisture

B. Direct correlation between soil strength and resistance to penetration

C. Soil cohesion

D. Soil density

The dynamic cone penetrometer (DCP) test is a field test used to assess the strength and stiffness of soil by measuring its resistance to penetration. It involves driving a cone-shaped penetrometer into the ground using a hammer that causes the cone to penetrate the soil material. The depth of penetration and the number of blows required to reach specific depths are recorded. A direct correlation exists between the resistance to penetration—indicated by the number of blows required to drive the cone a certain distance—and soil strength. Essentially, as the soil strength increases, it becomes more resistant to penetration, and more blows are necessary to achieve a given penetration depth. This relationship allows engineers to make inferences about the load-bearing capacity of the soil, which is crucial for designing foundations, pavements, and other civil engineering structures. While the other options mention related concepts, they do not accurately capture the primary purpose of the DCP test. For instance, the DCP is not primarily designed to measure soil cohesion or density directly, nor does it focus specifically on moisture content or its indirect correlation to soil strength. The test's utility lies in its ability to provide immediate, field-based measurements of soil strength through the resistance to penetration.

9. What factors does the coefficient of permeability (k) depend on?

A. Soil particle size, shape, structure, void ratio

B. Degree of saturation, void connectivity

C. All of the above

D. Only soil particle size and shape

The coefficient of permeability (k) is a critical factor in geotechnical engineering, particularly regarding the movement of water through soil. It reflects how easily fluid can flow through the soil and is influenced by multiple factors. One primary aspect is the soil particle size, which affects the pore sizes and spaces between the particles. Larger particles generally allow for easier water flow compared to finer particles, which can create more restrictive pathways. The shape of the particles is also significant, as irregularly shaped particles can create more complex flow paths that may hinder permeability compared to more rounded particles. The structure of the soil, including how particles aggregate and the presence of clays, can influence the connectivity of voids, determining how water moves through the soil. Additionally, the void ratio—essentially the amount of void space compared to the solid material—plays a crucial role. A higher void ratio typically means more space for water to flow, impacting the overall permeability. Degree of saturation also affects the permeability, as fully saturated soils tend to have higher permeability than soils that contain air voids. The connectivity of voids—how well the voids are interconnected—further dictates the ease with which water can navigate through the material. Given that k is influenced by all these factors

SAMPLE

10. What does a direct runoff hydrograph result from?

A. Base flow

B. Total Rainfall

C. Rainfall Excess

D. Interflow

A direct runoff hydrograph represents the immediate response of a watershed to precipitation, specifically the portion of rainfall that contributes to surface runoff. It illustrates how much of the rainfall exceeds the infiltration capacity of the soil and becomes direct runoff. Rainfall excess is the key concept here, as it is the part of the total rainfall that is not absorbed into the soil or held in the form of depression storage. Instead, it is conveyed over the land surface to streams and rivers, resulting in direct runoff. This is what causes the rise in stream flow depicted in the hydrograph. In contrast, base flow refers to the groundwater contribution to stream flow, which is relatively stable and does not respond quickly to storm events. Total rainfall encompasses both the rainfall that infiltrates and the rainfall excess; hence, it does not solely pertain to the runoff aspect. Interflow involves water movement through the soil layer, contributing to groundwater rather than immediate surface runoff. Thus, rainfall excess most accurately defines the cause of a direct runoff hydrograph.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://peciviltranspo.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE