RIGGING FOR ELECTRICAL INDUSTRY 2 PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://riggingforelectricalindustry2.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. How are taglines used and how many should be used for a lift?

A. Taglines control load movement from a distance; use at least two and add more as needed for size, weight, and hazards.

B. Taglines are decorative and optional.

C. Use one tagline only.

D. Taglines should be avoided to prevent entanglement.

2. What is a primary reason for documenting assumed values when estimating lift weight?

A. To provide a rationale for the estimate and a traceable data trail for the lift plan.

B. To confuse the team with unnecessary paperwork.

C. To avoid measuring equipment.

D. To comply with unrelated regulations.

3. What is the general approach to determining safe wind limits for a lift?

A. Follow wind values from personal preference

B. Follow the crane manufacturer's wind limits and site policy; abort if wind exceeds limits or gusts create unsafe conditions

C. Wind limits are irrelevant indoors

D. Increase limits with more loads

4. How should you assess the integrity of a rope sling before use?

A. Perform a quick sniff test.

B. Inspect only for visible cuts.

C. Perform a thorough visual inspection for wear, fraying, cuts, broken fibers, or other damage; retire if in doubt.

D. Rope slings cannot be inspected.

5. Which factor is not typically considered when weather affects rigging decisions?

A. Wind affecting grip

B. Visibility

C. Temperature affecting hoist performance

D. The color of the load's paint

SAMPLE

6. OSHA requires that the proof test verification be retained by which party?

A. certified person

B. employee

C. employer

D. qualified person

7. What item is used to convey chain sling specifications from the manufacturer?

A. attached nameplate or tag

B. invoice

C. MSD sheet

D. OSHA reference sheet

8. If a load shifts unexpectedly during a lift, what is the appropriate response?

A. Stop the lift, secure the area, recheck attachments/CG, rebalance, and resume only when the load is stable and safe.

B. Ignore and finish the lift if the shift is small.

C. Increase lift rate to speed balance.

D. Remove the load immediately and start over with new gear.

9. Name two types of rigging hardware that require a stamped load rating.

A. Bolts and nuts.

B. Pulleys and turnbuckles.

C. Chains and slings.

D. Shackles and hooks.

10. Give two examples where you would not push a sling to its maximum rating.

A. When the lift is dynamic or has a high shock factor, and when edge conditions (sharp edges, proximity to power lines) increase risk; derate for angles, dynamic loads, and attachments.

B. Always push to maximum rating for efficiency.

C. When the sling shows no signs of wear or damage.

D. When working in safe weather conditions only.

SAMPLE

Answers

SAMPLE

1. C
2. A
3. B
4. C
5. D
6. C
7. A
8. A
9. D
10. A

SAMPLE

Explanations

SAMPLE

1. How are taglines used and how many should be used for a lift?

A. Taglines control load movement from a distance; use at least two and add more as needed for size, weight, and hazards.

B. Taglines are decorative and optional.

C. Use one tagline only.

D. Taglines should be avoided to prevent entanglement.

Taglines are used to guide and control a load's movement during a lift from a distance, helping to keep the load aligned and prevent sway. The safest, most straightforward approach is to use a single tagline. One line provides a clear, direct point of control, reduces the risk of tangling with other rigging or the hoist, and simplifies communication between the signaler and the operator. Using additional taglines can create crossing, snagging, or conflicting pulls and is typically only appropriate under very specific, trained-crew procedures. Taglines aren't decorative or optional, and they shouldn't be avoided; they're a safety tool, with a single line offering the simplest, most controllable setup.

2. What is a primary reason for documenting assumed values when estimating lift weight?

A. To provide a rationale for the estimate and a traceable data trail for the lift plan.

B. To confuse the team with unnecessary paperwork.

C. To avoid measuring equipment.

D. To comply with unrelated regulations.

Documenting assumed values is about creating a defensible, transparent basis for the lift plan. When exact weights or conditions aren't known, you record the assumptions you're using so everyone can understand how the estimate was derived. This traceable data trail lets the team see the rationale behind the numbers, enables review or revision if real conditions differ, and supports safety and accountability during the lift. It's not meant to confuse anyone, skip measurements, or chase unrelated regulations—the value lies in having a clear, auditable basis for the plan.

3. What is the general approach to determining safe wind limits for a lift?

A. Follow wind values from personal preference

B. Follow the crane manufacturer's wind limits and site policy; abort if wind exceeds limits or gusts create unsafe conditions

C. Wind limits are irrelevant indoors

D. Increase limits with more loads

Safe operation relies on using proven wind limits rather than personal judgment. The crane is designed to handle wind only up to the manufacturer's specified maximum, and site safety policy may add even stricter requirements. By monitoring wind speeds and gusts against those approved limits, you maintain control of the suspended load and the crane itself. If wind exceeds the allowed limits or gusts create unsafe conditions, that's a signal to abort or pause work. This disciplined approach protects against instability, excessive load swing, and potential accidents. Personal preference, indoors not always removing wind effects, or trying to push limits with heavier loads do not provide a reliable safety margin.

SAMPLE

4. How should you assess the integrity of a rope sling before use?

A. Perform a quick sniff test.

B. Inspect only for visible cuts.

C. Perform a thorough visual inspection for wear, fraying, cuts, broken fibers, or other damage; retire if in doubt.

D. Rope slings cannot be inspected.

Before using a rope sling, perform a thorough visual inspection of the entire length and the eye/termination for any signs of damage. Rope slings can hide damage inside the fibers even when the surface looks fine, so you should check for wear patterns, fraying, broken or cut fibers, flat spots from abrasion, heat or chemical damage, stiffness, glazing, or any distortion of the rope. Look at the core if possible, and inspect splices or fittings for cracks or deformation. If there's any doubt about the condition, retire the sling from service. A sniff test isn't reliable, and only checking for visible cuts can miss internal or hidden damage, which is why a comprehensive inspection is essential for safe lifting.

5. Which factor is not typically considered when weather affects rigging decisions?

A. Wind affecting grip

B. Visibility

C. Temperature affecting hoist performance

D. The color of the load's paint

Weather affects rigging decisions by changing how well you can grip and control equipment, how clearly you can see signals and hazards, and how equipment performs in the conditions. Wind can complicate securing and lifting, making grip and control harder. Visibility determines whether the crew can read signals and spot hazards in time. Temperature influencing hoist performance matters because lubrication, hydraulics, and motor cooling are affected by heat or cold, altering speed and reliability. The color of the load's paint does not impact any of these weather-driven factors, so it's not a consideration in weather-related rigging decisions.

6. OSHA requires that the proof test verification be retained by which party?

A. certified person

B. employee

C. employer

D. qualified person

OSHA requires that proof-test verification be retained by the employer because the employer is responsible for the equipment, the safety program, and maintaining records for regulatory compliance. Keeping these records centralized and accessible ensures there is a traceable history showing the equipment has been tested and meets safety requirements, which inspectors may review at any time. The person who performs the test (a qualified or certified individual) may generate the documentation, but the obligation to retain and control the records belongs to the employer to support ongoing safety and accountability in the workplace.

SAMPLE

7. What item is used to convey chain sling specifications from the manufacturer?

A. attached nameplate or tag

B. invoice

C. MSD sheet

D. OSHA reference sheet

The main idea here is that the device's official, manufacturer-provided specifications travel with the sling and are readily available at the point of use. For chain slings, that information is found on an attached nameplate or tag. This tag is the authoritative source for critical data like the rated load (working load limit), material and grade, sling length, number of legs, hook type, and identification details (manufacturer, serial number, date of manufacture). Having this tag on the sling ensures you can verify you're using the right sling for a given lift and track its inspection/maintenance status. Invoices, SDSs (MSDS), and OSHA reference sheets don't provide the device-specific capacity and usage information needed to select or inspect a sling. An invoice is just billing, an SDS covers chemical hazards, and an OSHA reference sheet gives regulatory guidelines rather than the sling's exact specifications.

8. If a load shifts unexpectedly during a lift, what is the appropriate response?

A. Stop the lift, secure the area, recheck attachments/CG, rebalance, and resume only when the load is stable and safe.

B. Ignore and finish the lift if the shift is small.

C. Increase lift rate to speed balance.

D. Remove the load immediately and start over with new gear.

When a load shifts unexpectedly, the priority is to stop and assess before continuing. Stop the lift and secure the area to keep bystanders safe. Then recheck all attachments and the center of gravity, and rebalance the setup so the load can be lifted with control. Only resume when the load is stable and everything is verified as safe. This approach prevents tipping, swinging, or rigging failure and protects people and equipment. Ignoring the shift, speeding up the lift, or removing the load and starting over with new gear without first assessing the situation can hide a real hazard or create a bigger risk.

9. Name two types of rigging hardware that require a stamped load rating.

A. Bolts and nuts.

B. Pulleys and turnbuckles.

C. Chains and slings.

D. Shackles and hooks.

A stamped load rating shows the maximum weight that a piece of rigging hardware is certified to carry safely. Shackles and hooks are direct load-bearing connection points in lifting setups, so their failure would have immediate, serious consequences. Because of that, standards require a clear stamped Working Load Limit on the body of these pieces, reflecting their size, material, and design, so you can quickly verify they're suitable for the lift and won't be overloaded. While other components may have ratings as well, shackles and hooks are the quintessential rigging hardware that must carry visible, stamped load ratings to ensure safe and compatible use.

SAMPLE

10. Give two examples where you would not push a sling to its maximum rating.

A. When the lift is dynamic or has a high shock factor, and when edge conditions (sharp edges, proximity to power lines) increase risk; derate for angles, dynamic loads, and attachments.

B. Always push to maximum rating for efficiency.

C. When the sling shows no signs of wear or damage.

D. When working in safe weather conditions only.

In rigging, the rated capacity of a sling is not a guarantee you can push it to the limit in every situation. The main idea is that real lifts can generate loads well above the static weight due to dynamics and safety hazards, so you don't operate at the maximum rating. Two common situations illustrate this. First, dynamic lifts or those with a high shock factor create peak forces as the load is accelerated or stopped, which can temporarily exceed the sling's rating. In these cases you derate the sling and use a lower working load limit or a different rigging method to account for the extra force. Second, edge conditions or hazards—such as sharp edges that can cut the sling, or being near power lines—increase the risk of damage or failure, so you must derate and protect the sling (with padding or edge rollers, for example) and maintain extra clearance. These considerations, along with how lift angles and attachment points reduce effective capacity, reinforce not pushing a sling to its maximum rating. So you would avoid max rating in dynamic lifts with potential shock and in situations with edges or hazards that raise risk.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://riggingforelectricalindustry2.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE