
SEABEE BU A SCHOOL WALL AND FLOOR TILE, TRIM, AND PEB PRACTICE TEST (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://buaschwallfloortile.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1

Table of Contents 2

Introduction 3

How to Use This Guide 4

Questions 5

Answers 8

Explanations 10

Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. What does primer do in thinset installations?

A. Improves adhesion by reducing suction and ensuring better bond between substrate and thinset.

B. Provides waterproofing

C. Colors the thinset

D. Increases curing time

2. Outline a logical sequence for erecting a PEB on site.

A. Foundation/anchor bolts, erect steel frame, install roof deck, install wall panels, seal joints, add insulation and interior finishes, run MEP services, perform final inspections.

B. Foundation/anchor bolts.

C. Erect steel frame, install interior finishes, roof deck, then foundation.

D. Install wall panels first and ignore roof deck.

3. What is buttering (back-buttering) and when is it used?

A. It is applying grout to the back of the tile.

B. It is tapping tiles to set them.

C. It is applying a sealant to the tile back.

D. It is applying a thin coat of mortar to the tile back (or both tile and substrate) to improve bond for large-format or challenging surfaces.

4. Sag rods connect to hold the Holden column and bottom of the wall panel.

A. Sag rods

B. End wall parts

C. Brace rods

D. Eave strut

5. Which backer board is described as strong and dimensionally stable?

A. Foam tile backer boards

B. Cement backer unit

C. Gypsum board

D. Fiber-cement backer board

SAMPLE

6. Sag rods are used to hold the Holden column and bottom of the wall panel.

A. Purlins and girts

B. End wall parts

C. Holden column and bottom of wall panel

D. Door jamb

7. What is the primary purpose of an uncoupling membrane in floor tile installation?

A. It decouples tile from substrate movement to prevent cracking; commonly used with plywood or gypsum substrates; example Schluter-DITRA.

B. It provides a waterproof seal for concrete slabs.

C. It is a decorative underlayment that adds texture under the tile.

D. It bonds the tile directly to the substrate without adhesive.

8. Which moisture tests are commonly performed on concrete slabs before tile installation?

A. Surface moisture test and non-destructive tests, such as relative humidity or calcium chloride test, as per procedure.

B. pH measurement of the surface.

C. Visual inspection only.

D. No testing required.

9. Which grout is used in industrial areas requiring big resistance to acids and weak alkalis?

A. Latex grout

B. Cement grout

C. Furan resin grout

D. Epoxy grout

10. The trim that provides the finish between the finished wall and the floor?

A. Baseboard

B. Crown molding

C. Cap

D. Sill

SAMPLE

Answers

SAMPLE

1. A
2. B
3. D
4. A
5. D
6. C
7. B
8. A
9. C
10. A

SAMPLE

Explanations

SAMPLE

1. What does primer do in thinset installations?

A. Improves adhesion by reducing suction and ensuring better bond between substrate and thinset.

B. Provides waterproofing

C. Colors the thinset

D. Increases curing time

Primers in thinset installations primarily boost adhesion by controlling suction at the substrate and creating a better surface for the thinset to grip. Porous substrates pull moisture from the thinset as it cures, which can cause the mixture to dry too fast or bond unevenly. A primer seals those pores and normalizes absorbency, improving surface energy so the thinset can hydrate properly and form a stronger, more uniform bond to the substrate. This is especially helpful on rough, dusty, or highly absorbent surfaces like new concrete, masonry, or cement backer boards. It isn't intended for waterproofing, and while some products may offer moisture resistance, their main role is enhancing bond, not sealing out water. It doesn't color the thinset or meaningfully alter curing time—the curing is governed by cement hydration and environmental conditions.

2. Outline a logical sequence for erecting a PEB on site.

A. Foundation/anchor bolts, erect steel frame, install roof deck, install wall panels, seal joints, add insulation and interior finishes, run MEP services, perform final inspections.

B. Foundation/anchor bolts.

C. Erect steel frame, install interior finishes, roof deck, then foundation.

D. Install wall panels first and ignore roof deck.

Starting with foundation and anchor bolts is essential because it provides the solid base and precise anchor points the entire structure relies on. The foundation transfers loads to the ground, while the anchor bolts align and secure the steel frame, giving you a stable reference for everything that comes next. Without this first step, the frame can't be accurately positioned or safely bolted, and all subsequent construction becomes unreliable. Once the foundation and anchored bolts are set, the logical flow continues with erecting the steel frame, then installing the roof deck and wall panels, sealing joints, adding insulation and interior finishes, running MEP services, and finally completing inspections. The other sequences fail because they try to place structural work or enclosure components before a proper foundation, or skip essential steps like roofing or sealing, which are necessary to create a safe, weather-tight building.

3. What is buttering (back-buttering) and when is it used?

A. It is applying grout to the back of the tile.

B. It is tapping tiles to set them.

C. It is applying a sealant to the tile back.

D. It is applying a thin coat of mortar to the tile back (or both tile and substrate) to improve bond for large-format or challenging surfaces.

Buttering (back-buttering) means applying a thin, even coat of mortar to the back of the tile, and sometimes also to the substrate, to improve adhesion for large-format or otherwise challenging tiles. The idea is to create more contact with the tile and fill any ridges or gaps on the tile back (and on an uneven substrate), so when you press the tile in, there are fewer voids and a more uniform bed. This technique is especially helpful with large-format tiles, very smooth backs (like glazed porcelain or glass), or substrates that aren't perfectly flat. It's not about grout or sealant. You'll use back-buttering when the tile size, back texture, or substrate condition could otherwise lead to bond problems or noticeable lippage.

SAMPLE

4. Sag rods connect to hold the Holden column and bottom of the wall panel.

A. Sag rods

B. End wall parts

C. Brace rods

D. Eave strut

Sag rods are used as temporary tension braces to keep the Holden column and the bottom edge of the wall panel aligned during wall erection. They are attached from the Holden column down to the bottom of the panel and tightened to pull the panel into position, preventing sag and maintaining plumb until the frame is fully secured with permanent members. Other components serve different roles—end wall parts define wall ends, brace rods provide general bracing elsewhere, and the eave strut supports the roof edge—so they don't perform this specific function of tying the bottom of the wall panel to the Holden column.

5. Which backer board is described as strong and dimensionally stable?

A. Foam tile backer boards

B. Cement backer unit

C. Gypsum board

D. Fiber-cement backer board

Fiber-cement backer board is described as strong and dimensionally stable because it combines a cementitious matrix with reinforcing fibers, giving high rigidity and resistance to moisture-related swelling. This makes the board stay flat and hold a solid, uniform bonding surface for tile, which helps prevent movement and cracking over time. Foam tile backer boards are lighter but lack the same level of rigidity and moisture resistance. Cement backer boards without the fiber reinforcement can be strong, but they're heavier and not as resistant to dimensional changes as fiber-cement boards. Gypsum boards, even the moisture-resistant types, tend to absorb moisture, warp, or deteriorate in wet areas, making them unsuitable as tile backing substrates. So the fiber-cement option best fits the description of being strong and dimensionally stable.

6. Sag rods are used to hold the Holden column and bottom of the wall panel.

A. Purlins and girts

B. End wall parts

C. Holden column and bottom of wall panel

D. Door jamb

Sag rods act as temporary braces that keep the Holden column and the bottom edge of the wall panel aligned and from sagging as the wall is erected. By pulling these points into the correct position and holding them steady, they provide the stability needed for accurate fastening and for the wall to stay plumb until the permanent members are in place. Purlins and girts are used to support roof and wall framing rather than brace the Holden column, while end wall parts and door jamb refer to other components of the structure.

SAMPLE

7. What is the primary purpose of an uncoupling membrane in floor tile installation?

A. It decouples tile from substrate movement to prevent cracking; commonly used with plywood or gypsum substrates; example Schluter-DITRA.

B. It provides a waterproof seal for concrete slabs.

C. It is a decorative underlayment that adds texture under the tile.

D. It bonds the tile directly to the substrate without adhesive.

Uncoupling membranes are designed to absorb and separate movement between the tile layer and the substrate, so the tile can move with the substrate without transferring stress that causes cracking. This flexible layer, used under tiles on substrates like plywood or gypsum, lets differential movement occur without breaking the tile or grout. While some membranes offer additional moisture management, their primary purpose is decoupling, not waterproofing. They're not decorative underlayment, and they don't bond tile directly to the substrate without adhesive.

8. Which moisture tests are commonly performed on concrete slabs before tile installation?

A. Surface moisture test and non-destructive tests, such as relative humidity or calcium chloride test, as per procedure.

B. pH measurement of the surface.

C. Visual inspection only.

D. No testing required.

Moisture in a concrete slab directly affects tile adhesion and long-term performance, so testing before installation is essential. The best practice combines a surface moisture assessment with non-destructive in-slab measurements. A surface moisture test helps identify moisture present at or near the surface and any moisture vapor coming to the surface, while non-destructive methods like relative humidity testing (in-slab RH) and the calcium chloride test (measuring moisture vapor emission rate) probe moisture levels inside the slab. Following the procedure specified by the adhesive and tile manufacturers or relevant standards ensures you know whether the slab meets the allowable moisture limits before applying thin-set or other mortars. pH measurement, while sometimes relevant to chemical compatibility, does not quantify moisture content; visual inspection alone can miss hidden moisture, and skipping moisture testing is not acceptable.

SAMPLE

9. Which grout is used in industrial areas requiring big resistance to acids and weak alkalis?

A. Latex grout

B. Cement grout

C. Furan resin grout

D. Epoxy grout

In environments where acids are present and only weak alkalis are involved, you need a grout that resists chemical attack at a high level. Cementitious and latex-based grouts rely on cement or lightweight matrices that are porous and easily degraded by acids, so they don't hold up well in harsh chemical conditions. Epoxy grout offers good chemical resistance compared to cementitious options, but furan resin grout is specifically formulated for extreme chemical exposure, especially acids and mild bases. Its resin matrix provides superior resistance to acids, reduces permeability, and preserves strength in hostile environments, which is why it's the preferred choice in industrial areas like chemical plants and facilities handling corrosive substances. Keep in mind, furan resin grout requires careful handling and installation, but in terms of acid resistance, it stands out among these options.

10. The trim that provides the finish between the finished wall and the floor?

A. Baseboard

B. Crown molding

C. Cap

D. Sill

The trim at the bottom where the finished wall meets the floor is baseboard. It covers the joint between wall and floor, hides gaps or uneven edges, and protects the wall from scuffs while providing a clean, finished transition from wall to floor. Crown molding sits along the top edge of the wall near the ceiling for decoration, not at the floor. A cap trim is used for edging in other applications, not specifically the wall-to-floor seam. A sill refers to the bottom ledge of a window or door, not the continuous trim along the base of the wall.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://buaschwallfloortile.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE