
SMOG REPAIR TECHNICIAN PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://smogrepairtech.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1
Table of Contents 2
Introduction 3
How to Use This Guide 4
Questions 5
Answers 8
Explanations 10
Next Steps 16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. What mode should be accessed to check if the ECM has saved a permanent record of a failure after clearing a trouble code?

A. Mode 8

B. Mode 9

C. Mode 10

D. Mode 11

2. If a vehicle's STFT is stable at -10% and LTFT is at -22%, what might be responsible for excessive fuel consumption?

A. Faulty throttle position sensor

B. Leaking fuel injector

C. Faulty fuel pressure regulator

D. Clogged catalytic converter

3. What is a typical indicator of a failing mass airflow sensor?

A. Steady engine performance

B. Fluctuating idle speed

C. Increased lighting efficiency

D. Lower emission levels

4. What is typically indicated by a NOx reading of 2400 ppm in a smog test?

A. Normal engine operation

B. Clogged EGR passages

C. Excessive fuel vaporization

D. Defective fuel injectors

5. Which of the following is a common symptom of a stuck-closed EGR valve?

A. High CO emissions

B. High NOx emissions

C. Rough idle

D. Increased fuel consumption

SAMPLE

6. What is indicated when a vehicle's exhaust gas analyzer shows high levels of hydrocarbons?

A. Incomplete combustion

B. Excessive fuel flow

C. Lower octane fuel usage

D. Bad fuel filter

7. If no trouble codes are present and diagnostic tests need to be reviewed for emissions control devices, which mode is essential?

A. Mode 6

B. Mode 7

C. Mode 8

D. Mode 9

8. A post-catalytic converter oxygen sensor should ideally:

A. Fluctuate between 0.1V - 0.9V

B. Remain steady at about 0.45V

C. Signal a continuous high voltage

D. Vary significantly with engine load

9. If an oxygen sensor voltage range is 0.6 - 1.0V, what does it signify?

A. Normal fuel mixture

B. Rich fuel mixture

C. Lean fuel mixture

D. Faulty oxygen sensor

10. What are typical signs that a leaking fuel injector is present in a vehicle?

A. Decreased engine temperature

B. Increased power output

C. Excessive fuel consumption

D. Negligible changes in performance

SAMPLE

Answers

SAMPLE

1. C
2. C
3. B
4. B
5. B
6. A
7. A
8. B
9. B
10. C

SAMPLE

Explanations

SAMPLE

1. What mode should be accessed to check if the ECM has saved a permanent record of a failure after clearing a trouble code?

A. Mode 8

B. Mode 9

C. Mode 10

D. Mode 11

The correct mode to access for checking if the Engine Control Module (ECM) has saved a permanent record of a failure after clearing a trouble code is Mode 10. This mode is specifically designed to read permanent diagnostic trouble codes (DTCs). Permanent DTCs are those that are stored in the ECM even after a trouble code has been cleared. They indicate that a malfunction was present and may help technicians assess whether the issue has been resolved or if it remains. In contrast, other modes such as Mode 8, Mode 9, and Mode 11 serve different purposes. Mode 8 is used primarily for vehicle-specific diagnostic functions, such as special tests for components or systems. Mode 9 is utilized to report vehicle information, including the VIN and calibration ID. Mode 11 provides access to non-permanent DTCs that can be cleared and don't necessarily indicate a permanent failure status. Understanding the specific functions of each mode is essential for effective diagnostics, and knowing that Mode 10 is the one focused on permanent records helps technicians not only in troubleshooting but also in ensuring compliance with emissions regulations.

2. If a vehicle's STFT is stable at -10% and LTFT is at -22%, what might be responsible for excessive fuel consumption?

A. Faulty throttle position sensor

B. Leaking fuel injector

C. Faulty fuel pressure regulator

D. Clogged catalytic converter

When assessing fuel trims, a stable short-term fuel trim (STFT) at -10% indicates that the engine control module (ECM) is adjusting the fuel mixture slightly richer by reducing fuel injector pulse width. Meanwhile, a long-term fuel trim (LTFT) at -22% means that the ECM has been compensating for a consistent lean condition over time by reducing fuel delivery by a larger amount. The significant difference between the STFT and LTFT suggests that the vehicle has been experiencing a persistent fuel delivery issue, likely due to incorrect fuel pressure. A faulty fuel pressure regulator can lead to low fuel pressure, causing the engine to be starved for fuel, which would result in the need for the ECM to adjust fuel trims negatively to compensate for this lean condition. Therefore, the combination of a stable STFT and a significantly negative LTFT points towards a problem related to fuel delivery, solidifying that the fuel pressure regulator is likely responsible for the excessive fuel consumption observed. While other options like a faulty throttle position sensor, leaking fuel injector, or clogged catalytic converter could impact fuel consumption, they would typically present with different fuel trim readings or symptoms. A leaking fuel injector, for instance, would likely cause a rich condition and have a

SAMPLE

3. What is a typical indicator of a failing mass airflow sensor?

A. Steady engine performance

B. Fluctuating idle speed

C. Increased lighting efficiency

D. Lower emission levels

A typical indicator of a failing mass airflow sensor is fluctuating idle speed. The mass airflow (MAF) sensor measures the amount of air entering the engine, which is crucial for determining the correct fuel-to-air ratio for optimal combustion. When the MAF sensor is malfunctioning, it may send incorrect readings to the engine control unit (ECU), causing the engine to struggle in maintaining a consistent idle speed. This leads to a condition where the engine may idle too high, too low, or exhibit erratic fluctuations, all of which can indicate problems with air intake measurement. In contrast, steady engine performance would not typically point to a malfunctioning MAF sensor, as a properly functioning sensor contributes to smooth operation. Increased lighting efficiency and lower emission levels also suggest normal functioning of the vehicle's systems, not issues originating from a faulty MAF sensor. Therefore, observing fluctuations in idle speed is a clear sign that the MAF sensor may need to be inspected or replaced.

4. What is typically indicated by a NOx reading of 2400 ppm in a smog test?

A. Normal engine operation

B. Clogged EGR passages

C. Excessive fuel vaporization

D. Defective fuel injectors

A NOx reading of 2400 ppm during a smog test indicates a significant emission of nitrogen oxides, which suggests that there is an issue with the vehicle's emissions control systems. In this context, the reading is much higher than acceptable levels, which can indicate a malfunction. One of the primary causes of elevated NOx emissions is clogged EGR (Exhaust Gas Recirculation) passages. The EGR system is designed to recirculate a portion of the exhaust gas back into the intake manifold, which helps to reduce combustion temperatures and therefore lowers NOx emissions. When the passages are clogged, the EGR system cannot operate effectively, resulting in higher combustion temperatures and an increase in NOx production. This scenario directly correlates with the high NOx reading observed in the smog test. The other choices do relate to potential issues with the vehicle but do not directly lead to such a high level of NOx emissions. For example, normal engine operation would not result in such elevated readings, while excessive fuel vaporization and defective fuel injectors typically relate more to hydrocarbon emissions rather than NOx, making them less likely sources of the elevated reading observed.

SAMPLE

5. Which of the following is a common symptom of a stuck-closed EGR valve?

A. High CO emissions

B. High NOx emissions

C. Rough idle

D. Increased fuel consumption

A stuck-closed EGR (Exhaust Gas Recirculation) valve is often associated with increased NOx (nitrogen oxides) emissions. The EGR valve serves to recirculate a portion of the exhaust gases back into the intake system. This process lowers the combustion temperature, which helps to reduce the formation of NOx emissions. When the EGR valve is stuck closed, exhaust gases are unable to mix with the incoming fresh air-fuel mixture. As a result, the temperature in the combustion chamber remains high, leading to an increase in NOx production. Under normal circumstances, the EGR valve helps to mitigate this by allowing some exhaust back into the intake, hence controlling combustion temperatures effectively. Therefore, high NOx emissions are a direct symptom of a malfunctioning EGR system when the valve is stuck in the closed position. The other symptoms, while they can be related to various engine issues, are not directly caused by a stuck-closed EGR valve. Understanding the role of the EGR system is crucial for diagnosing emissions-related problems effectively.

6. What is indicated when a vehicle's exhaust gas analyzer shows high levels of hydrocarbons?

A. Incomplete combustion

B. Excessive fuel flow

C. Lower octane fuel usage

D. Bad fuel filter

When a vehicle's exhaust gas analyzer shows high levels of hydrocarbons, it indicates incomplete combustion of the fuel within the engine. Incomplete combustion occurs when there is insufficient oxygen present during the combustion process, or when the combustion temperatures are too low. This leads to unburned fuel being expelled into the exhaust system, resulting in elevated hydrocarbon levels. Incomplete combustion can stem from a variety of issues, such as a faulty fuel injector that delivers too much fuel or a malfunctioning ignition system that prevents proper ignition of the fuel-air mixture. The increased hydrocarbons not only contribute to smog but can also indicate that the engine is not operating efficiently, which can lead to reduced performance and increased fuel consumption. While excessive fuel flow, use of lower octane fuel, or a bad fuel filter could also create problems in a vehicle's performance, they do not directly correlate with high hydrocarbon readings in the exhaust gas. Excessive fuel flow would likely lead to other indicators, like poor fuel economy or a rich running condition but may not specifically result in high hydrocarbon levels. Lower octane fuel mainly affects engine knock and performance, and a bad fuel filter would typically restrict fuel flow rather than increase unburned hydrocarbons. Thus, high hydrocarbon levels

SAMPLE

7. If no trouble codes are present and diagnostic tests need to be reviewed for emissions control devices, which mode is essential?

A. Mode 6

B. Mode 7

C. Mode 8

D. Mode 9

Mode 6 is crucial for this scenario because it allows technicians to access specific diagnostic data related to the performance of vehicle emissions control components. In this mode, information about the on-board diagnostic (OBD) system's readiness monitors is provided, along with data concerning the results of individual component tests that are not associated directly with trouble codes. This is particularly useful when no trouble codes are present, as it enables the technician to review the operational status of emissions devices, troubleshooting potential issues that may not trigger a fault code but still impact emissions performance. Using Mode 6, technicians can conduct a more thorough investigation into how well emissions-related components, such as the catalytic converter or oxygen sensors, are functioning. This module can reveal historical information about previous tests, current statuses, and specific parameters that help in diagnosing whether the emissions control systems are operating effectively.

8. A post-catalytic converter oxygen sensor should ideally:

A. Fluctuate between 0.1V - 0.9V

B. Remain steady at about 0.45V

C. Signal a continuous high voltage

D. Vary significantly with engine load

A post-catalytic converter oxygen sensor plays a critical role in monitoring the efficiency of the catalytic converter and ensuring optimal fuel mixture adjustments. After the exhaust gases have passed through the catalytic converter, the primary function of the post-catalytic converter oxygen sensor is to provide feedback on the catalytic converter's performance by measuring the amount of oxygen in the exhaust gas downstream of the catalyst. Ideally, this sensor should remain steady at approximately 0.45V, indicating that the catalytic converter is effectively performing its job of converting harmful emissions into less harmful substances. A stable voltage around this level means that the exhaust gases have a balanced oxygen content, which signifies that the catalytic converter is functioning correctly in its role of reducing emissions. This consistent reading helps the engine control module (ECM) ascertain that the vehicle is running efficiently with minimal unnecessary emissions. In contrast, significant fluctuations in voltage would suggest that the catalytic converter is not functioning effectively, as the oxygen levels in the exhaust would be inconsistent, indicating incomplete combustion or perhaps a failure of the catalytic component itself. A continuous high voltage might imply an overly rich mixture or malfunctions, while variations with engine load are not typical behavior for a post-catalytic converter sensor, as it should reflect a more stable state after

SAMPLE

9. If an oxygen sensor voltage range is 0.6 - 1.0V, what does it signify?

A. Normal fuel mixture

B. Rich fuel mixture

C. Lean fuel mixture

D. Faulty oxygen sensor

An oxygen sensor reading within a voltage range of 0.6 to 1.0 volts indicates a rich fuel mixture. In this scenario, the oxygen sensor is detecting a higher concentration of fuel in relation to the amount of air present in the exhaust gases. When the voltage is elevated, it typically suggests that there is insufficient oxygen to fully combust the fuel, leading to a richer mix. In contrast, a normal fuel mixture would generally produce a voltage reading closer to 0.45 volts, while a lean fuel mixture would be represented by a lower voltage, typically below 0.5 volts. Additionally, a faulty oxygen sensor might provide erratic readings or stay at a constant value that does not correspond with the actual air-fuel mixture, indicating a malfunction in the sensor itself rather than a specific mixture condition. Thus, understanding the significance of these voltage ranges is crucial for diagnosing air-fuel mixture issues in an engine's operation.

10. What are typical signs that a leaking fuel injector is present in a vehicle?

A. Decreased engine temperature

B. Increased power output

C. Excessive fuel consumption

D. Negligible changes in performance

A leaking fuel injector often leads to excessive fuel consumption because the injector is designed to deliver a precise amount of fuel into the engine's combustion chamber. When it leaks, it allows fuel to escape into the intake manifold or the combustion chamber without being used efficiently, resulting in a richer fuel mixture and thereby causing the engine to consume more fuel than normal. This excess fuel not only affects fuel economy but can also lead to other issues such as rough idling, increased emissions, and potential engine misfires. The other choices do not align with the typical symptoms of a leaking fuel injector. Decreased engine temperature is not directly linked to fuel injector leaks, as the issue primarily impacts combustion efficiency. Increased power output typically signifies optimal fuel delivery and combustion, not a problem with leakage, while negligible changes in performance would suggest that the injector is functioning properly to some extent, which contradicts the characteristic of a leaking injector. Thus, excessive fuel consumption is a definitive indicator of this issue.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://smogrepairtech.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE