TFM03 EXTINGUISHER TYPE K PRACTICE EXAM (SAMPLE)

STUDY GUIDE



SAMPLE STUDY GUIDE WITH LIMITED QUESTIONS

VISIT US ONLINE FOR THE FULL VERSION STUDY GUIDE

https://tfm03.examzify.com

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright 1
Table of Contents 2
Introduction 3
How to Use This Guide 4
Questions 5
Answers 8
Explanations 10
Next Steps 15

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

SAMPLE

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 – 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

SAMPLE

Questions

SAMPLE

1. Hoods with fire dampers shall be provided within how many inches from the damper?

A. 6 inches

B. 12 inches

C. 24 inches

D. 18 inches from the damper

2. What is the hydrostatic test pressure relative to normal pressure for a 4B195 cylinder?

A. Twice the normal pressure

B. Three times the normal pressure

C. The same as the normal pressure

D. Four times the normal pressure

3. Fixed temperature sensing elements other than fusible metal alloys shall be replaced at what interval?

A. Every 12 months

B. Every 6 months

C. Every 24 months

D. Every 36 months

4. The wet chemical agent used in Class K extinguishers is most accurately described as:

A. Potassium acetate-based wet chemical designed to saponify fats

B. Dry chemical ABC powder

C. Aqueous film-forming foam

D. Sodium chloride water solution

5. During a monthly inspection, what should you verify about a Class K extinguisher's gauge?

A. The gauge shows a full charge

B. The pressure indicator is in the operable range

C. The gauge shows a valid charge

D. The extinguisher must be replaced if the gauge is unreadable

SAMPLE

6. Manual actuators shall be between how many feet from the system?

A. 5 to 10 feet from the system

B. 15 to 25 feet from the system

C. 20 to 30 feet from the system

D. 10 to 20 feet from the system

7. What type of welds are required on seams joining ducts to ducts?

A. Liquid-tight, continuously external welds

B. Screwed joints with sealant

C. Riveted joints

D. Duct tape seals

8. Fusible links shall be located where?

A. At above each cooking appliance

B. At every door

C. Near the ceiling

D. On the floor

9. The extinguishing action of Class K agents helps prevent re-ignition by what mechanism?

A. Creating a soapy, viscous layer on the fat/oil

B. Dry-powder coating

C. Net cooling via water

D. Smothering with a blanket of foam

10. Which statement is true about the notation 4B195?

A. 195 psi is the normal operating pressure

B. 195 psi is the hydrostatic test pressure

C. 195 psi is the minimum safe pressure

D. 195 psi is unrelated to pressure

SAMPLE

Answers

SAMPLE

1. D
2. B
3. A
4. A
5. B
6. D
7. A
8. A
9. A
10. A

SAMPLE

Explanations

SAMPLE

1. Hoods with fire dampers shall be provided within how many inches from the damper?

A. 6 inches

B. 12 inches

C. 24 inches

D. 18 inches from the damper

Fire dampers are installed in exhaust ducts to stop fire from traveling through the ductwork. Placing the damper within a short distance from the hood ensures the protected, rated portion of the duct is as close as possible to the source of heat and flames, so the damper can close quickly and effectively. The standard requires the fire damper to be within 18 inches of the hood, keeping the run between hood and damper short enough to minimize an unprotected duct path and to maintain proper response and performance of the automatic shutoff. Distances like 6 or 12 inches would not align with the intended protection and practical installation, while 24 inches would leave too long a gap between the hood and the damper, reducing the effectiveness of the fire-stop arrangement.

2. What is the hydrostatic test pressure relative to normal pressure for a 4B195 cylinder?

A. Twice the normal pressure

B. Three times the normal pressure

C. The same as the normal pressure

D. Four times the normal pressure

Hydrostatic testing checks the cylinder's ability to withstand internal pressure by pushing it well beyond normal operating conditions. For the 4B195 cylinder, the standard test uses a pressure three times the normal service pressure. This larger margin helps reveal hidden flaws or weaknesses that could fail under stress, ensuring the cylinder remains safe between inspections. So, if the cylinder's normal operating pressure is 195 psi, the hydrostatic test pressure would be 585 psi.

3. Fixed temperature sensing elements other than fusible metal alloys shall be replaced at what interval?

A. Every 12 months

B. Every 6 months

C. Every 24 months

D. Every 36 months

The key idea is reliability of the triggering device. Fixed temperature sensing elements that aren't fusible metals can drift, corrode, or lose calibration over time due to heat cycling, moisture, and oxidation. To ensure the extinguisher will activate when needed, these non-fusible elements are replaced on a strict, short interval—typically every 12 months. This annual replacement reduces the risk of a faulty or delayed discharge. Choosing longer intervals (every 24 or 36 months) would allow more time for degradation to accumulate, while a shorter interval like every 6 months isn't typically required unless the manufacturer or local codes specify it.

SAMPLE

4. The wet chemical agent used in Class K extinguishers is most accurately described as:

A. Potassium acetate-based wet chemical designed to saponify fats

B. Dry chemical ABC powder

C. Aqueous film-forming foam

D. Sodium chloride water solution

In Class K fires, the extinguishing agent is a wet chemical designed specifically for cooking fats and oils. It is potassium acetate–based and reacts with fats to saponify them, turning the fatty layer into a soapy film. This soapy layer coats the oil, emulsifies it, and creates a cooling, protective film that smothers the flame and prevents reignition. This targeted mechanism—saponifying fats to form a soapy layer—is what makes this agent uniquely effective for kitchen oil fires, unlike other extinguishing agents that aren't formulated to react with fats.

5. During a monthly inspection, what should you verify about a Class K extinguisher's gauge?

A. The gauge shows a full charge

B. The pressure indicator is in the operable range

C. The gauge shows a valid charge

D. The extinguisher must be replaced if the gauge is unreadable

During a monthly check, the important thing is that the pressure indicator on the Class K extinguisher is within its operable range. That range represents the pressure level at which the extinguisher can reliably discharge its agent. It doesn't have to read full, just within the green or designated operable zone to be ready for use. If the gauge is unreadable or shows pressure outside this range, the unit needs servicing to restore proper operability.

6. Manual actuators shall be between how many feet from the system?

A. 5 to 10 feet from the system

B. 15 to 25 feet from the system

C. 20 to 30 feet from the system

D. 10 to 20 feet from the system

Placement of manual actuators for a kitchen fire-suppression system is about balancing quick, reliable access with safety from accidental activation. You want staff to reach the actuator without stepping into the hazard, but you don't want it so close that normal kitchen activity or a small bump could trigger the system unintentionally. The ten-to-twenty-foot range achieves that practical balance: it keeps the handle within an easy reach for someone nearby, while still requiring a deliberate action away from the most hazardous zone. This distance also fits common guidance in codes and industry practice for where manual actuation devices should be located relative to the protected system, ensuring a prompt but controlled activation in an emergency.

SAMPLE

7. What type of welds are required on seams joining ducts to ducts?

A. Liquid-tight, continuously external welds

B. Screwed joints with sealant

C. Riveted joints

D. Duct tape seals

Seams joining ducts must be made with liquid-tight, continuously external welds. This creates a complete seal around the joint, preventing grease-laden air from leaking and helping maintain fire safety and efficient airflow. External, continuous welds are also easier to inspect and maintain. Screwed joints with sealant can loosen under heat and vibration, riveted joints aren't the standard for modern kitchen ducts and may not provide a airtight seal, and duct tape cannot withstand grease and heat or meet proper sealing codes.

8. Fusible links shall be located where?

A. At above each cooking appliance

B. At every door

C. Near the ceiling

D. On the floor

Fusible links are heat-activated devices that trigger a kitchen fire suppression system when heat from a cooking fire is detected. They must be positioned above each cooking appliance so that rising heat near the appliance will reach the link quickly and melt it, releasing the extinguishing agent promptly. Placing them over the appliance ensures immediate activation where the fire is most likely to start, providing effective protection. Locating them elsewhere—such as near doors, ceilings, or on the floor—would not reliably sense heat from the cooking area or could delay activation, reducing the system's effectiveness.

9. The extinguishing action of Class K agents helps prevent re-ignition by what mechanism?

A. Creating a soapy, viscous layer on the fat/oil

B. Dry-powder coating

C. Net cooling via water

D. Smothering with a blanket of foam

The mechanism being tested is that Class K extinguishing agents use a wet chemical that saponifies fats and oils, turning the surface into a soapy, viscous layer. This soap-like coating blankets the fat/oil, creates a barrier between the fuel and air, and cools the surface. By emulsifying the oil and reducing heat feedback and vapor production, it greatly lowers the chance of re-ignition once the flame is out. Other methods like dry powders, direct water cooling, or foam blankets don't produce that protective soapy layer on the oil, so they don't address re-ignition in the same chemical way.

SAMPLE

10. Which statement is true about the notation 4B195?

A. 195 psi is the normal operating pressure

B. 195 psi is the hydrostatic test pressure

C. 195 psi is the minimum safe pressure

D. 195 psi is unrelated to pressure

The number at the end of the notation is the operating pressure the extinguisher is designed to maintain when it's charged. In this case, 195 psi is the pressure the device is intended to operate at, so it represents the normal working pressure you'd expect to see on the gauge when the extinguisher is ready for use. Hydrostatic test pressure is a separate requirement used during maintenance to verify the cylinder's integrity. It's a higher pressure applied only during testing, not the pressure the extinguisher is meant to operate at day to day, so it isn't what the notation indicates. The minimum safe pressure isn't specified by this label either; there's a different tolerance range or low-pressure limit defined by the manufacturer and standards, and if the gauge reads below that, maintenance is required. So the statement that 195 psi is the normal operating pressure matches what the notation conveys.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

https://tfm03.examzify.com

We wish you the very best on your exam journey. You've got this!

SAMPLE